
CEMENT BOND
LOGGING PLOT
COLLAR CORRELATION LOG
Operator: JAPEX UK EXPLORATION LIMITED
Well: 48/15-A-4
Field: BETTANIA
Date: 11/11/2022
Run No: ONE
Depth Datum: Kelly Bushing
Elevation: 25.00 m Above Perm. Datum
Log Measured From: Kelly Bushing
Drilling Measured From: Kelly Bushing
Permanent Datum: Mean Sea Level
Elevation: 0.00 m
Elevation: 25.00 m
Elevation: 25.00 m
Depth Logged: 1,000.00 m
Depth Driller: 1,000.00 m
Depth Logger: 1,000.00 m
Bottom Log Interval: 1,000.00 m
Top Log Interval: 0.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 1
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 2
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 3
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 4
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 5
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 6
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 7
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 8
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 9
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 10
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 11
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 12
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 13
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 14
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 15
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 16
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 17
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 18
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 19
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 20
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 21
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 22
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 23
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 24
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 25
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 26
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 27
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 28
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 29
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 30
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 31
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 32
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 33
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 34
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 35
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 36
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 37
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 38
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 39
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 40
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmc @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.00 ohm.m @ 0.00 °C
Max Recorded Temp: 0.00 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run 41
Top Log Int.: 0.00 m
Bottom Log Int.: 1,000.00 m
Casing Driller: 244.5 mm @ 0.00 m
Casing Logger: 244.5 mm @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.10 g/cm3
Viscosity: 50.00 s
Fluid Loss: 6.00 cm3
Source of Sample: Flowline
Rm @ Meas. Temp: 0.00 ohm.m @ 0.00 °C
Rmf @ Meas. Temp: 0.00