

Proposed BMP's - I02 697 Pad

THE FOLLOWING IS A LIST OF BEST MANAGEMENT PRACTICES THAT WILL BE IMPLEMENTED BY BERRY DURING THE PAD CONSTRUCTION, WELL DRILLING, WELL COMPLETION, NATURAL GAS PRODUCTION, AND RECLAMATION PHASES OF ACTIVITY ON THE LATHAM I02 697 WELL PAD LOCATION.

A TOTAL OF NINE WELLS WILL BE DIRECTIONALLY DRILLED FROM THE I02 697 WELL PAD. DIRECTIONAL DRILLING HAS ENABLED BERRY TO REDUCE THE NUMBER OF WELL PADS REQUIRED FOR GAS RECOVERY AND WILL MINIMIZE SURFACE DISTURBANCE. IN GENERAL, BERRY WILL COMPLY WITH APPLICABLE FEDERAL, STATE AND LOCAL STATUTES, RULES, REGULATIONS AND ORDINANCES, INCLUDING, THOSE OF OSHA, THE COGCC AND CDPHE RELATING TO SAFETY AND THE ENVIRONMENT. DURING CONSTRUCTION OF THE WELL PAD, TOPSOIL WILL BE ISOLATED FROM OTHER SOILS AND PLACED AND STACKED PER COGCC REQUIREMENTS. ALL CUTS, FILL SLOPES, PIT AND TOPSOIL PILES AND SOIL PILES WILL BE STABILIZED AND REVEGETATED IMMEDIATELY FOLLOWING CONSTRUCTION. THE PADS WILL BE CONSTRUCTED IN COMPLIANCE WITH CDPHE STORM WATER DISCHARGE REGULATIONS. THE RESERVE/COMPLETION PIT WILL BE FENCED/FLAGGED AND/OR NETTED TO PREVENT ENTRY OF WILDLIFE (INCLUDING BIRDS) AND LIVESTOCK. BEAR PROOF DUMPSTERS OR TRASH CAGES WILL BE USED ON THE LOCATION FOR SOLID/FOOD WASTE STORAGE. NOXIOUS WEEDS WILL BE CONTROLLED. TEMPORARY HOUSING FOR THE DRILL RIG CREWS WILL MEET ALL GARFIELD COUNTY REGULATIONS. THE HOUSING QUARTERS WILL RECEIVE 24/7 SUPERVISION BY BERRY. PRODUCTION TANKS SHALL BE PLACED ON A NON PERMEABLE LINER.