

## State of Colorado

## Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303)894-2100 Fax: (303)894-2109



## SUNDRY NOTICE

Submit original plus one copy. This form is to be used for general, technical and environmental sundry information. For proposed or completed operations, describe in full on Technical Information Page (Page 2 of this form.) Identify well or other facility by API Number or by OGCC Facility ID. Operator shall send an informational copy of all sundry notices for wells located in High Density Areas to the Local Government Designee (Rule 603b.)

1. OGCC Operator Number:	28600	4. Contact Name	
2. Name of Operator:	Exxon Mobil Corporation	Lynn Neely	
3. Address:	P. O. Box 4358, COPR-MI-205	Phone:	281-654-1949
City:	Houston	State:	Tx.
		Zip	77210-4358
		Fax:	262-313-9747
5. API Number	05-103-11636-00	OGCC Facility ID Number	
6. Well/Facility Name:	Freedom Unit	7. Well/Facility Number	197-28A9
8. Location (Qtr/Qtr, Sec, Twp, Rng, Meridian):	NWSW, Sec. 28, T1S, R97W, 6th P.M.		
9. County:	Rio Blanco	10. Field Name:	Piceance Creek
11. Federal, Indian or State Lease Number:	N/A		

Complete the Attachment  
Checklist

OP OGCC

Survey Plat	
Directional Survey	
Surface Exgmt Diagram	
Technical Info Page	
Other	

## General Notice

<input type="checkbox"/> <b>CHANGE OF LOCATION:</b>	<b>Attach New Survey Plat</b>	(a change of surface qtr/qtr is substantive and requires a new permit)
Change of <b>Surface</b> Footage from Exterior Section Lines:	FNL/FSL	
Change of <b>Surface</b> Footage to Exterior Section Lines:		
Change of <b>Bottomhole</b> Footage from Exterior Section Lines:		
Change of <b>Bottomhole</b> Footage to Exterior Section Lines:		
Bottomhole location Qtr/Qtr, Sec, Twp, Rng, Mer		attach directional survey
Latitude	Distance to nearest property line	Distance to nearest bldg, public rd, utility or RR
Longitude	Distance to nearest lease line	Is location in a High Density Area (rule 603b)?
Ground Elevation	Distance to nearest well same formation	Surface owner consultation date:

## GPS DATA:

Date of Measurement \_\_\_\_\_ PDOP Reading \_\_\_\_\_ Instrument Operator's Name \_\_\_\_\_

<input type="checkbox"/> <b>CHANGE SPACING UNIT</b>	<input type="checkbox"/> <b>Remove from surface bond</b>
Formation	Signed surface use agreement attached
Formation Code	Unit Acreage
Spacing order number	Unit configuration

<input type="checkbox"/> <b>CHANGE OF OPERATOR (prior to drilling):</b>	<input type="checkbox"/> <b>CHANGE WELL NAME</b>	<b>NUMBER</b>
Effective Date:	From:	
Plugging Bond:	To:	
<input type="checkbox"/> Blanket <input type="checkbox"/> Individual	Effective Date:	

<input type="checkbox"/> <b>ABANDONED LOCATION:</b>	<input type="checkbox"/> <b>NOTICE OF CONTINUED SHUT IN STATUS</b>
Was location ever built? <input type="checkbox"/> Yes <input type="checkbox"/> No	Date well shut in or temporarily abandoned:
Is site ready for inspection? <input type="checkbox"/> Yes <input type="checkbox"/> No	Has Production Equipment been removed from site? <input type="checkbox"/> Yes <input type="checkbox"/> No
Date Ready for Inspection:	MIT required if shut in longer than two years. Date of last MIT

<input type="checkbox"/> <b>SPUD DATE:</b>	<input type="checkbox"/> <b>REQUEST FOR CONFIDENTIAL STATUS</b> (6 mos from date casing set)
--	--

<input type="checkbox"/> <b>SUBSEQUENT REPORT OF STAGE, SQUEEZE OR REMEDIAL CEMENT WORK</b>	*submit cbl and cement job summaries
Method used	Cementing tool setting/perf depth
Cement volume	Cement top
Cement bottom	Date

<input type="checkbox"/> <b>RECLAMATION:</b>	Attach technical page describing final reclamation procedures per Rule 1004.
Final reclamation will commence on approximately	<input type="checkbox"/> Final reclamation is completed and site is ready for inspection.

## Technical Engineering/Environmental Notice

<input checked="" type="checkbox"/> <b>Notice of Intent</b>	<input type="checkbox"/> <b>Report of Work Done</b>
Approximate Start Date:	Date Work Completed:
02/01/2010	

## Details of work must be described in full on Technical Information Page (Page 2 must be submitted.)

<input type="checkbox"/> <b>Intent to Recomplete</b> (submit form 2)	<input type="checkbox"/> <b>Request to Vent or Flare</b>	<input type="checkbox"/> <b>E&amp;P Waste Disposal</b>
<input type="checkbox"/> <b>Change Drilling Plans</b>	<input type="checkbox"/> <b>Repair Well</b>	<input type="checkbox"/> <b>Beneficial Reuse of E&amp;P Waste</b>
<input type="checkbox"/> <b>Gross Interval Changed?</b>	<input checked="" type="checkbox"/> <b>Rule 502 variance requested</b>	<input type="checkbox"/> <b>Status Update/Change of Remediation Plans</b>
<input type="checkbox"/> <b>Casing/Cementing Program Change</b>	<input type="checkbox"/> <b>Other:</b>	for Spills and Releases

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct and complete.

Signed: Lynn Neely Date: 02/01/2010 Email: [lynn.r.neely@exxonmobil.com](mailto:lynn.r.neely@exxonmobil.com)

Print Name: Lynn Neely Title: Regulatory Specialist

OGCC Approved: Kim J. King Title: **EIT III** Date: **FEB 02 2010**

CONDITIONS OF APPROVAL, IF ANY:

TECHNICAL INFORMATION PAGE



FOR OGCC USE ONLY

RECEIVED

FEB 01 2010

OGCC/Rifle Office

1. OGCC Operator Number: 28600 API Number: 05-103-11636-00
2. Name of Operator: Exxon Mobil Corporation OGCC Facility ID # 0
3. Well/Facility Name: Freedom Unit Well/Facility Number: 197-28A9
4. Location (QtrQtr, Sec, Twp, Rng, Meridian): NWSW, Sec. 28, T1S, R97W, 6th P.M.

This form is to be completed whenever a Sundry Notice is submitted requiring detailed report of work to be performed or completed. This form shall be transmitted within 30 days of work completed as a "subsequent" report and must accompany Form 4, page 1.

5. DESCRIBE PROPOSED OR COMPLETED OPERATIONS

Operator seeks exception to the part of COGCC Rule 317 that state that cement placed behind production casing must achieve at least 300 psi compressive strength after 24 hours and at least 800 psi compressive strength after 72 hours, when tested at 95 degF and 800 psi. The cement slurry design stated above for all slurries is capable of achieving the 300 psi /24 hours and 800 psi / 72 hours requirement under bottomhole temperature conditions. High-temperature-capable retarders used in the slurry design prevent the cement from achieving compressive strength in 72 hours at the lower 95 degF test temperature required by the Rule. All proposed cement designs comply with the subject rule when downhole temperature is taken into effect.

ExxonMobil Oil Corporation has made a good faith effort to comply, or is unable to comply with the compressive strength specifications of COGCC Rule 317.1., and the requested variance will not violate the basic intent of the Oil and Gas Conservation Act.