Run No. One, Bottom Log Interval 4,710 ft
Scale 1 in = 100 ft
Top Log Interval 1,000 ft
Scale 1 in = 100 ft
Run No. One, Bottom Log Interval 4,710 ft
Scale 1 in = 100 ft
Top Log Interval 1,000 ft
Scale 1 in = 100 ft

Log Variables

Gamma Ray (GR) (API units)
Caliper (CALI) (in)
Bit Size (BS) (in)
Deep Resistivity (RDEP) (ohm.m)
Medium Resistivity (RMED) (ohm.m)
Shallow Resistivity (RSHA) (ohm.m)
Density Correction (DRHO) (g/cm3)
Photoelectric Factor (PEF) (b/e)
Neutron Porosity (NPHI) (dec)
Density Porosity (RHOB) (g/cm3)

Gamma Ray (GR) (API units)
Caliper (CALI) (in)
Bit Size (BS) (in)
Deep Resistivity (RDEP) (ohm.m)
Medium Resistivity (RMED) (ohm.m)
Shallow Resistivity (RSHA) (ohm.m)
Density Correction (DRHO) (g/cm3)
Photoelectric Factor (PEF) (b/e)
Neutron Porosity (NPHI) (dec)
Density Porosity (RHOB) (g/cm3)



HALLIBURTON

FREE PIPE

Calibration Report

Database File: bb_s_34c-26-692_cbl.db
Dataset Pathname: pass8
Dataset Creation: Thu Mar 13 12:53:45 2008 by Log Halliburton Casedho

Temperature Calibration Report

Serial Number: CSS1012
Tool Model: CSSMRAD
Performed: Tue Nov 13 08:53:57 2001

	Reference	Reading
Low Reference:	80.00 degF	35.00 cps
High Reference:	321.00 degF	169.00 cps

Gain: 1.80
Offset: 17.05
Delta Spacing 1

Gamma Ray Calibration Report

Type / Serial: Probe170 / 070841

SHOP CALIBRATION — Thu Mar 13 11:47:00 2008

	Counts/Sec.	Gain	Offset	Jig	Units
Background	44.6				cps
Calibrator	217.4				cps
		1.3656			GAPI/cps

PRIMARY VERIFICATION — Thu Mar 13 11:48:58 2008

Background	62.6				cps
Calibrator	302.1				cps
Difference				239.6	GAPI

BEFORE SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

AFTER SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

Segmented Cement Bond Log Calibration Report

Serial Number: 070760
Tool Model: Probe170

Calibration Casing Diameter: 4.500 in
Calibration Depth: 749.793 ft

Master Calibration, performed Thu Mar 13 12:14:28 2008:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.013	0.326	2.000	82.000	255.441	-1.299
CAL	0.012	0.209				
5'	0.013	0.313	2.000	82.000	266.277	-1.384
SUM						
S1	0.014	0.332	0.250	82.000	256.775	-3.229
S2	0.012	0.336	0.250	82.000	252.401	-2.769
S3	0.013	0.343	0.250	82.000	247.971	-2.953
S4	0.012	0.354	0.250	82.000	239.459	-2.685
S5	0.010	0.345	0.250	82.000	244.005	-2.094
S6	0.014	0.318	0.250	82.000	269.138	-3.505
S7	0.015	0.311	0.250	82.000	276.642	-3.975
S8	0.010	0.325	0.250	82.000	260.137	-2.468

Internal Reference Calibration, performed Wed Dec 31 18:00:00 1969:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.012	0.209	1.000	0.000

Air Zero Calibration, performed Wed Dec 31 18:00:00 1969:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			7FT	7.00	1.69	110.00
			Probe169 Probe 1 11/16" Centralizer	3.38	1.69	15.00
			RBT_PRB_170-Probe170 (070760) Probe 1-11/16" Radii Bond Tool	15.00	1.69	63.00
WVF3FT	15.90					
WVFCAL	15.90					
WVFS8	15.89					
WVFS7	15.80					
WVFS6	15.89					
WVFS5	15.89					
WVFS4	15.89					
WVFS3	15.89					
WVFS2	15.86		Probe169 Probe 1 11/16" Centralizer	3.38	1.69	15.00
WVFS1	15.89					
WVF5FT	14.90					
CCL	7.17					
			GR-Probe170 (070841) Probe 1 11/16" - High Temp Gamma Ray - CCL Tool	7.65	1.69	54.00
GR	1.54					
TEMP	0.21		TEMP-CSSMRAD (CSS1012) Computer Sonics CSSM Radial Temperature	0.63	3.13	30.00

Dataset: bb_s_34c-26-692_cbl.db: field/well/run1/pass8
Total Length: 37.02 ft
Total Weight: 287.00 lb
O.D. 3.13 in

Company	BILL BARRETT CORPORATION
Well	SNYDER 34C-26-692
Field	MAMM CREEK
County	GARFIELD
State	COLORADO

HALLIBURTON

ACOUSTIC CEMENT
BOND LOG