PSI
Precision Survey Instruments

COMPENSATED DENSITY
DUAL INDUCTION

Company: Petroleum Development Corp.
Well: Hickey 3-23
Field: Wildcat
County: Arapahoe
State: Colorado
Other Services: Sidetracked
Permanent Datum: Ground Level
Elevation: 5,574.00 ft
Log Measured From: Kelly Bushing
Drilling Measured From: Kelly Bushing
Elevation: 5,574.00 ft
Elevation: 5,574.00 ft
API#: 05-013-06099-00
Location: Sec 23 Twp 3S Rge 63W
Date: 10-31-2008
Run Number: One
Depth Driller: 7,800.00 ft
Depth Logger: 7,800.00 ft
Bottom Logged Interval: 7,800.00 ft
Top Logged Interval: 4,000.00 ft
Casing Driller: 8.625 @ 1,000.00 ft
Casing Logger: 1,000.00 ft
Bit Size: 7.875 in
Type Fluid: Water Based Mud
Density / Viscosity: 9.00 lb/gal / 40.00 s/qt
pH / Fluid Loss: 10.00 / 6.00 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.600 @ 70.00 °F
Rmf @ Meas Temp: 0.450 @ 70.00 °F
Rmc @ Meas Temp: 0.750 @ 70.00 °F
Source of Rmf / Rmc: Measured / Measured
Rm @ BHT: 0.350 @ 150.00 °F
Time Since Circulation: 12.00 hrs
Max Rec Temp: 150.00 °F
Equipment Number: 3
Location: Greeley
Recorded By: Chris Cash
Witnessed By: Mr. Jones

All data relative to an optimum bean or reference that is identical in all measurements and not an exact set of curves that fits the survey. It is understood that the interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not guarantee the accuracy or correctness of any interpretations and we shall not be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions as set out in our current price schedule.

Comments

Annular volume calculated for 4 1/2" casing
Fallowing OTTag 3rd
Thank you for using Phoenix Surveys?
API # 05-013-06099-00

Database File: SCPI.db
Dataset Pathname: pass3
Presentation Format: dual ind
Dataset Creation: Mon Mar 01 21:26:45 2009 by Log Data Caswell B1T1CR
Charted by: Depth in Feet scaled 1 / 240

0 Gamma Ray (GAPI) 150
Casing Ray (GAPI) 150
SP (mV) 100

Caliper (in) 16
Bit Size (in) 16
SP (mV) -100

Deep Resistivity (Ohm-m) .200 2K
Medium Resistivity (Ohm-m) .200 2K
Shallow Resistivity (Ohm-m) .200 2K

Density Porosity (pu) 45
Neutron Porosity (pu) -15

1:240

1000
1100
1200
1300
1400
1500
1600
1700
1800
1900
2000
2100
2200
2300
2400
2500
2600
2700
2800
2900
3000
3100
3200
3300
3400
3500
3600
3700
3800
3900
4000
4100
4200
4300
4400
4500
4600
4700
4800
4900