PSI

COMPENSATED DENSITY
DUAL SPACED NEUTRON
DUAL INDUCTION

Company: Bill Barrett Corporation
Well: Gold 4-2-32
Field: Wildcat
State/Prov: Colorado
Country: United States
Rig: Cyclone 30 # 5 (SEMI) Inc
Location: Sec 32 T5S R97W 1,800' FNL 330' FWL
Sec 32 T5S R97W 1,800' FNL 330' FWL
Elevation: KB: 7,000.00 ft GL: 6,974.00 ft
Coordinate System: NAD83 Colorado Central
Latitude: 39° 34' 19.32" N
Longitude: 108° 11' 39.96" W
Survey Type: Definitive
Survey Date: 31-Jul-2008
Tool Name: DGR EWR-P4 ADN CTN
Serial No: 3913 3913 3913 3913
Top Log Interval: 0.00 ft
Bottom Log Interval: 7,000.00 ft
Drill Fluid Type: Water Based Mud
Max Rec Temp: 150 degF
Equipment Location: Rifle
Recorded By: Jeff Hall
Witnessed By: Bill Barrett Corporation

Run Number: 1
Depth Driller: 7,000.00 ft
Schlumberger Depth: 7,000.00 ft
Bottom Log Interval: 7,000.00 ft
Top Log Interval: 0.00 ft
Casing Driller Size @ Depth: 4.500 in @ 7,000.00 ft
Casing Schlumberger: 7,000.00 ft
Bit Size: 3.875 in
Type Fluid in Hole: Water Based Mud
Density: 9.00 lbm/gal
Viscosity: 40.00 s
PH: 8.00
Fluid Loss: 0.00 in3
Source of Sample: Flowline
Rm @ Meas Temp: 0.000 ohmm @ 0.00 degF
Rmf @ Meas Temp: 0.000 ohmm @ 0.00 degF
Rmc @ Meas Temp: 0.000 ohmm @ 0.00 degF
Source Rmf & Rmc: Measured
Rm @ BHT: 0.000 ohmm @ 0.00 degF
Time Circulation Stopped: 0.00 hr
Time Logger on Bottom: 0.00 hr
Maximum Recorded Temperature: 0.00 degF
Equipment: 0.00 hr
Location: 0.00 hr
Recorded By: 0.00 hr
Witnessed By: 0.00 hr