PSI
PRECISION SURVEYS INC.

COMPENSATED DENSITY
COMPENSATED NEUTRON
DUAL INDUCTION

Company: Bill Barrett Corporation
Well: Cade Drilling Rig 2
Field: Wattenberg
County: Weld
State/Province: Colorado
Country: USA
Location: Sec. 4 T1N R67W, 6th PM
Elevation: 5281 ft
Permanent Datum: Ground Level
Log Measured From: KB
Drilling Measured From: KB
Date: 10-Jul-2008
Run Number: ONE
Depth Driller: 9400 ft
Depth Logger: 9400 ft
Bottom Logged Interval: 9400 ft
Top Logged Interval: 4400 ft
Casing Driller: 8.625 in @ 1000 ft
Casing Logger: 1000 ft
Bit Size: 7.875 in
Type Fluid in Hole: Water Based Mud
Density: 9.2 lb/gal
Viscosity: 40 s
PH: 9.5
Fluid Loss: 6.4 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.98 @ 70 °F
Rmf @ Measured Temp: 0.75 @ 70 °F
Rmc @ Measured Temp: 1.2 @ 70 °F
Source of Rmf and Rmc: Calculated
Rm @ BHT: 0.55 @ 150 °F
Time Since Circulation: 4 hrs
Max Recorded Temperature: 150 °F
Equipment Number: 3
Location: Evans
Recorded By: Jason Hall
Witnessed By: Bill Barrett Corporation

Comments

Annular volume calculated for 4.57" casing
Cade Drilling Rig 2
Thank you for using Precision Surveys!
API # 05-123-24105-00

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Database File: 6463.db
Dataset Pathname: main
Presentation Format: encana
Dataset Creation: Sun Oct 19 01:53:16 2008
Charted by: Depth in Feet scaled 1:240

0 Density Caliper (in) 10	2 Deep Resistivity (Ohmm) .2(0.4)	Density Porosity (pu) 0
50 Gamma Ray (GAPI) 300	2 Medium Resistivity (Ohmm) .2(0.4)	Neutron Porosity (pu) 60
60 SP (mV) 140	2 Shallow Resistivity (Ohmm) .2(0.4)	

4400
4500
4600
4700
4800
4900
5000
5100
5200
5300
5400
5500
5600
5700
5800
5900
6000
6100
6200
6300
6400
6500
6600
6700
6800
6900
7000
7100
7200
7300
7400
7500
7600
7700
7800
7900
8000
8100
8200
8300
8400
8500
8600
8700
8800
8900
9000
9100
9200
9300
9400

2.69 SS Mathr.

Database File: 6463.db
Dataset Pathname: main
Presentation Format: encana
Dataset Creation: Sun Oct 19 01:53:16 2008
Charted by: Depth in Feet scaled 1:240

0 Density Caliper (in) 10	2 Deep Resistivity (Ohmm) .2(0.4)	Density Porosity (pu) 0
50 Gamma Ray (GAPI) 300	2 Medium Resistivity (Ohmm) .2(0.4)	Neutron Porosity (pu) 60
60 SP (mV) 140	2 Shallow Resistivity (Ohmm) .2(0.4)	

5100
5200
5300
5400
5500
5600
5700
5800
5900
6000
6100
6200
6300
6400
6500
6600
6700
6800
6900
7000
7100
7200
7300
7400
7500
7600
7700
7800
7900
8000
8100
8200
8300
8400
8500
8600
8700
8800
8900
9000
9100
9200
9300
9400

-99.99 Mathr.

Database File: 6463.db
Dataset Pathname: main
Presentation Format: encana
Dataset Creation: Sun Oct 19 01:53:16 2008
Charted by: Depth in Feet scaled 1:240

0 Caliper (in) 10	2 Deep Resistivity (Ohmm) .2(0.4)	Density Porosity (pu) 0
0 Gamma Ray (GAPI) 300	2 Medium Resistivity (Ohmm) .2(0.4)	Neutron Porosity (pu) 60
60 SP (mV) 200	2 Shallow Resistivity (Ohmm) .2(0.4)	

7500
7600
7700
7800
7900
8000
8100
8200
8300
8400
8500
8600
8700
8800
8900
9000
9100
9200
9300
9400

2.71 LS Mathr.
Mathr. Change

-49.55 Mathr.
Mathr. Change

-97.00 Mathr.
Neutron Porosity
Density Porosity
Shallow Resistivity
Deep Resistivity
Medium Resistivity
Caliper
SP
Gamma Ray
Logged to TD: 9,400'