Mud Type: Water Based Mud
Density: 8.4 lb/gal
Viscosity: 26 s/qt
Chlorides: 0 mg/l
Fluid Loss: 0 cc
Source: Rig Tank
Rm @ Meas. Temp: 0.000 @ 0 °F
Rmf @ Meas. Temp: 0.000 @ 0 °F
Rmc @ Meas. Temp: 0.000 @ 0 °F
Rm @ BHT: 0.000 @ 0 °F
Time Circulation Ended: 00:00
Time Logger on Bottom: 00:00
Max Recorded Temperature: 0 °F
Equipment: 0
Location: 0
Recorded By: 0
Witnessed By: 0
Run Number: 1
Depth Driller: 0 ft
Depth Logger: 0 ft
Bottom Logged Interval: 0 ft
Top Logged Interval: 0 ft
Casing Driller Size @ Depth: 0 @ 0 ft
Casing Logger Size @ Depth: 0 @ 0 ft
Bit Size: 0 in
Type Fluid in Hole: Water Based Mud
Density / Viscosity: 8.4 lb/gal / 26 s/qt
PH / Fluid Loss: 0 / 0 cc
Source of Sample: Rig Tank
Rm @ Meas. Temp: 0.000 @ 0 °F
Rmf @ Meas. Temp: 0.000 @ 0 °F
Rmc @ Meas. Temp: 0.000 @ 0 °F
Source of Rmf / Rmc: 0 / 0
Rm @ BHT: 0.000 @ 0 °F
Time Since Circulation: 0
Time



Company: Pan Am
Well: Lockhart Unit 1
Field: Wildcat (New Field)
County: Hidalgo
State: Texas
Elevation: 1,247 ft. above sea level
Location: 1,980 ft. N. of N. line and 660 ft. W. of E. line of Sec. 14, Block 3, H.&T.C. RR. Survey
Drilling Commenced: 3-12-1951
Drilling Completed: 4-28-1951
Total Depth: 9,847 ft.
Initial Production: 1,240 BOPD, 0% BS&W, GOR 1,180
Casing: 13-3/8" @ 1,502 ft. w/ 1,200 sx; 9-5/8" @ 6,214 ft. w/ 1,850 sx
Completion: Perforated 9,712–9,734 ft. (Frio); acidized with 2,000 gal.
Status: Producing
Remarks: Discovery well for the Lockhart Unit. Core taken 9,700–9,734 ft. Drill stem test 9,710–9,734 ft. Electrical log run by Schlumberger.