PSI

COMPENSATED DENSITY
COMPENSATED NEUTRON
DUAL INDUCTION

Company: EnCana Oil & Gas (USA) Inc
Field: Wattenberg
County: Boulder
State: Colorado
Location: Sec 36 T1N R68W
Well: Chatfield 36-26
API #: 05-013-06511-00
Drilling Measured From: KB
Permanent Datum: Ground Level
Elevation: KB 4917 ft, GL 4906 ft
Log Measured From: KB, 11 ft above Perm. Datum
Date: 21-Jul-10
Run Number: ONE
Depth Driller: 8200 ft
Depth Logger: 8200 ft
Bottom Logged Interval: 8200 ft
Top Logged Interval: 3100 ft
Casing Driller: 8.625 in @ 3100 ft
Casing Logger: 3100 ft
Bit Size: 7.875 in
Type Fluid in Hole: Water Based Mud
Density: 9.2 lb/gal
Viscosity: 40 s/qt
Fluid Loss: 6.4 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.75 @ 70 °F
Rmf @ Measured Temp: 0.56 @ 70 °F
Rmc @ Measured Temp: 1.01 @ 70 °F
Source of Rmf and Rmc: Measured
Rm @ BHT: 0.36 @ 160 °F
Time Since Circulation: 4 hrs
Max Rec Temp: 160 °F
Equipment Number: 3
Location: Boulder
Recorded By: Jeff Hall
Witnessed By: Jeff Hall

Comments

Annular volume calculated for 4.5" casing
Cade Rig 22
Thank you for using Phoenix Surveys!
API #: 05-013-06511-00

Database File: 6117.db
Dataset Pathname: PASS
Presentation Format: PSCX
Dataset Creation: Wed Jul 21 05:46:46 2010 by Log2_2w
Charted by: Depth only scaled 2.00 in/100 ft

Density Caliper (in) 16 / Gamma Ray (GAPI) 150 / SP (mV) 150
Deep Resistivity (Ohm-m) .2(0) 2000 / Density Porosity (pu) 45
Medium Resistivity (Ohm-m) .2(0) 2000 / Neutron Porosity (pu) 45
Shallow Resistivity (Ohm-m) .2(0) 2000

2.65 SS MATRIX

Database File: 6117.db
Dataset Pathname: PASS
Presentation Format: PSCX
Dataset Creation: Wed Jul 21 05:46:46 2010 by Log2_2w
Charted by: Depth only scaled 2.00 in/100 ft

Caliper (in) 16 / Gamma Ray (GAPI) 150 / SP (mV) 150
Deep Resistivity (Ohm-m) .2(0) 2000 / Density Porosity (pu) 45
Medium Resistivity (Ohm-m) .2(0) 2000 / Neutron Porosity (pu) 45
Shallow Resistivity (Ohm-m) .2(0) 2000

2.71 LS MATRIX
2.71 LS MATRIX
MATRIX CHANGE
2.65 SS MATRIX
MATRIX CHANGE
2.65 SS MATRIX
2.65 SS MATRIX

Caliper (in) 16 / Gamma Ray (GAPI) 150 / SP (mV) 150
Logger's TD= 8197
Caliper
GR
SP
Shallow Resistivity
Medium Resistivity
Deep Resistivity
Density Porosity
Neutron Porosity
2.65 SS MATRIX
Deep Resistivity (Ohm-m) .2(0) 2000 / Density Porosity (pu) 45
Medium Resistivity (Ohm-m) .2(0) 2000 / Neutron Porosity (pu) 45
Shallow Resistivity (Ohm-m) .2(0) 2000