

FORM
2
Rev
12/05

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80205 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:
400057833
Plugging Bond Surety
20090078

APPLICATION FOR PERMIT TO:

1. **Drill,** Deepen, Re-enter, Recomplete and Operate

2. TYPE OF WELL

OIL GAS COALBED OTHER _____
SINGLE ZONE MULTIPLE ZONE COMMINGLE ZONE

Refiling
Sidetrack

3. Name of Operator: PETROLEUM DEVELOPMENT CORPORATION 4. COGCC Operator Number: 69175

5. Address: 1775 SHERMAN STREET - STE 3000
City: DENVER State: CO Zip: 80203

6. Contact Name: Sarah Garrett Phone: (303)860-5803 Fax: (303)860-5838
Email: sgarrett@petd.com

7. Well Name: Guttersen Well Number: 24J

8. Unit Name (if appl): _____ Unit Number: _____

9. Proposed Total Measured Depth: 7500

WELL LOCATION INFORMATION

10. QtrQtr: NWNW Sec: 24 Twp: 3N Rng: 64W Meridian: 6
Latitude: 40.217810 Longitude: -104.504280

Footage at Surface: _____ FNL/FSL _____ FEL/FWL _____
50 FNL 1308 FWL

11. Field Name: Wattenberg Field Number: 90750

12. Ground Elevation: 4750 13. County: WELD

14. GPS Data:

Date of Measurement: 11/19/2009 PDOP Reading: 6.0 Instrument Operator's Name: Thomas G. Carlson

15. If well is Directional Horizontal (highly deviated) **submit deviated drilling plan.**

Footage at Top of Prod Zone: _____ FNL/FSL _____ FEL/FWL _____ Bottom Hole: _____ FNL/FSL _____ FEL/FWL _____
Sec: _____ Twp: _____ Rng: _____ Sec: _____ Twp: _____ Rng: _____

16. Is location in a high density area? (Rule 603b)? Yes No

17. Distance to the nearest building, public road, above ground utility or railroad: 3194

18. Distance to nearest property line: 50 ft 19. Distance to nearest well permitted/completed in the same formation: 825 ft

20. **LEASE, SPACING AND POOLING INFORMATION**

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
J Sand	JSND	232-240	160	GWA
Niobrara-Codell	NB-CD	407-87	160	GWA
Sussex-Shannon	SX-SN	N/A	160	GWA

21. Mineral Ownership: Fee State Federal Indian Lease #: _____

22. Surface Ownership: Fee State Federal Indian

23. Is the Surface Owner also the Mineral Owner? Yes No Surface Surety ID#: 19990086

23a. If 23 is Yes: Is the Surface Owner(s) signature on the lease? Yes No

23b. If 23 is No Surface Owners Agreement Attached or \$25,000 Blanket Surface Bon \$2,000 Surface Bond \$5,000 Surface Bond

24. Using standard QtrQtr, Sec, Twp, Rng format enter entire mineral lease description upon which this proposed wellsite is located (attach separate sheet/map if you prefer):
 Township 3 North, Range 64 West, 6th P.M. Section 24: NW/4, SW/4SW/4, E/2SE/4 (and other acreage not included)

25. Distance to Nearest Mineral Lease Line: 50 ft 26. Total Acres in Lease: 2889

DRILLING PLANS AND PROCEDURES

27. Is H2S anticipated? Yes No If Yes, attach contingency plan.

28. Will salt sections be encountered during drilling? Yes No

29. Will salt (>15,000 ppm TDS CL) or oil based muds be used during drilling? Yes No

30. If questions 27 or 28 are yes, is this location in a sensitive area (Rule 903)? Yes No **If 28, 29, or 30 are "Yes" a pit permit may be required.**

31. Mud disposal: Offsite Onsite
 Method: Land Farming Land Spreading Disposal Facility Other: _____

Note: The use of an earthen pit for Recompletion fluids requires a pit permit (Rule 905b). If air/gas drilling, notify local fire officials.

Casing Type	Size of Hole	Size of Casing	Weight Per Foot	Setting Depth	Sacks Cement	Cement Bottom	Cement Top
SURF	12+1/4	8+5/8	24	650	390	650	0
S.C. 1.1	7+7/8	4+1/2	10.5	7,000	193	7,000	6,100
S.C. 1.2	7+7/8	4+1/2	10.5	7,500	324	7,500	7,000

32. BOP Equipment Type: Annular Preventer Double Ram Rotating Head None

33. Comments Conductor casing will not be used. The Gutteresen 24J will be tied into an existing tank battery facility at the Gutteresen 11-24 well site which already services the Gutteresen 23-11 and Gutteresen 11-24 wells. Petroleum Development Corporation requests approval of a Rule 603.a.(2) exception location: Wellhead is to be located less than 150' from a property line. Petroleum Development Corporation requests approval of a Rule 318Aa, Rule 318Ae, and Rule 318Ac exception location: Wellhead is to be located outside of a GWA drilling window, the well will be drilled to a 318Ae infill location from outside of a GWA drilling window, and the wellhead will be located more than 50' from an existing well location.

34. Location ID: _____

35. Is this application in a Comprehensive Drilling Plan ? Yes No

36. Is this application part of submitted Oil and Gas Location Assessment ? Yes No

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Sarah Garrett

Title: Landman Date: 5/6/2010 Email: sgarrett@petd.com

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: David S. Neslin Director of COGCC Date: 6/25/2010

Permit Number: _____ Expiration Date: 6/24/2012

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

COGCC ENG COA 1) Provide 24 hour notice of MIRU to Bo Brown at 970-330-6085 or email at bo.brown@state.co.us. 2) Set surface casing per Rule 317d, with cement to surface. Setting surface casing less than the approved depth is a permit violation unless prior written approval is obtained from the COGCC. 3) If completed, provide cement coverage from TD to a minimum of 200' above Niobrara and from 200' below Shannon to 200' above Sussex. Verify coverage with cement bond log. 4) If dry hole, set 60 sks cement from 50' below D Sand base to 100' above D Sand top, 40 sks cement 50' above Niobrara top, 40 sks cement 50' above Shannon top, 40 sks cement 50' above Sussex top, 50 sks cement ½ out, ½ in surface casing, 10 sks cement top of surface casing, cut 4' below GL, weld on plate, 5 sks cement in rat hole & 5 sks cement in mouse hole. Restore surface location.

COGCC ENG COA 1) Provide 24 hour notice of MIRU to Bo Brown at 970-330-6085 or email at bo.brown@state.co.us. 2) Set surface casing per Rule 317d, with cement to surface. Setting surface casing less than the approved depth is a permit violation unless prior written approval is obtained from the COGCC. 3) If completed, provide cement coverage from TD to a minimum of 200' above Niobrara and from 200' below Shannon to 200' above Sussex. Verify coverage with cement bond log. 4) If dry hole, set 60 sks cement from 50' below D Sand base to 100' above D Sand top, 40 sks cement 50' above Niobrara top, 40 sks cement 50' above Shannon top, 40 sks cement 50' above Sussex top, 50 sks cement ½ out, ½ in surface casing, 10 sks cement top of surface casing, cut 4' below GL, weld on plate, 5 sks cement in rat hole & 5 sks cement in mouse hole. Restore surface location.

Attachment Check List

Att Doc Num	Name	Doc Description
1725823	SURFACE CASING CHECK	LF@2475621 1725823
400057833	FORM 2 SUBMITTED	LF@2465820 400057833
400059747	PLAT	LF@2465821 400059747
400059748	TOPO MAP	LF@2465822 400059748
400059749	30 DAY NOTICE LETTER	LF@2465823 400059749
400059750	EXCEPTION LOC WAIVERS	LF@2465824 400059750
400059751	EXCEPTION LOC WAIVERS	LF@2465825 400059751
400059839	PROPOSED SPACING UNIT	LF@2465826 400059839
400059946	EXCEPTION LOC REQUEST	LF@2465827 400059946
400059947	EXCEPTION LOC REQUEST	LF@2465828 400059947

Total Attach: 10 Files