



02054461

Andrews, David

---

**From:** GJRig01@oxy.com  
**Sent:** Saturday, August 07, 2010 7:15 AM  
**To:** Andrews, David  
**Cc:** Brad\_Ahlquist@Oxy.com; Ronald\_Bevans@oxy.com; Simon\_Benevides@oxy.com; Dmitry\_Smushkov@oxy.com  
**Follow Up Flag:** Follow up  
**Flag Status:** Flagged

Mr. Andrews,

The following 9-5/8" Surface casing string has been set at 2,708' and cemented on Oxy's 609 - 14 pad:

Well 697-08-62A, API# 05-0451928600 PUMPED 20 BBLS FRESH WATER, 20 BBLS OF SUPER FLUSH, 20 BBLS OF FRESH WATER.  
CEMENTED 9-5/8" SURFACE CASING WITH:  
1030 SACKS - 427.4 BBLS OF 12.3 PPG - 2.33 CU. FT/SK VERSACEM LEAD WITH TUFF FIBER, 160 SACKS - 59 BBLS OF 12.8 PPG - 2.07 CU. FT/SK VERSACEM TAIL. DISPLACED WITH 205.5 BBLS FRESH WATER AT 5-4-2 BPM.  
SAW 489 PSI LIFT PRESSURE AT 2 BPM. BUMPED PLUG WITH 1090 PSI.  
PRESSURED UP TO 1500 PSI FOR 15 MIN. - GOOD TEST. FLOATS HELD.  
CIP AT 0956 HRS 6 AUGUST 2010.  
SAW 0 BBLS CEMENT RETURNS TO SURFACE. LOST 486 BBLS OF MUD.

FLUSHED PARASITE LINE WITH SUGAR WATER - HAD RETURNS AFTER 4.6 BBLS - CIRCULATED AT 123 PSI @ 1.1 BPM.

TOPPED OUT WITH 18.1 BBLS (150') OF 12.5 PPG - 1.78 CU. FT/SK HALCEM TOPOUT BLEND. WITH 3 BBLS CEMENT TO SURFACE.

Thanks,

George Lyerly, Marco Silva, Curt Claussen, Victor Benavides  
281-436-6424