COMPENSATED NEUTRON
DUAL INDUCTION

Company:	Sinclair Oil & Gas (USA) Inc.
Well:	Patterson UTI Drilling Rig 34
Field:	Wattenberg
County:	Weld
State:	Colorado
Location:	API #: 05-123-25511-00 SW/4 NW/4 Sec 19, T3N, R67W, 6th PM
Permanent Datum:	Ground Level
Elevation:	Elev.: 4,915 ft.
Log Measured From:	KB, 15 ft. above Perm. Datum
Drilling Measured From:	KB
Date:	28-Jul-20
Run Number:	ONE
Depth Driller:	9,600 ft.
Depth Logger:	9,600 ft.
Bottom Logged Interval:	9,600 ft.
Top Logged Interval:	4,000 ft.
Casing Driller Size @ Depth:	8.625 in. @ 4,000 ft.
Casing Logger Size @ Depth:	8.625 in. @ 4,000 ft.
Type Fluid in Hole:	Water Based Mud
Density / Viscosity:	9.0 lb/gal / 40 s/qt
PH / Fluid Loss:	9.0 / 6.0 cc
Source of Sample:	Flowline
Rm @ Measured Temp:	0.058 @ 63 °F
Rmf @ Measured Temp:	0.049 @ 63 °F
Rmc @ Measured Temp:	0.069 @ 63 °F
Source of Rmf / Rmc:	Calculated / Calculated
Rm @ BHT:	0.031 @ 180 °F
Time Since Circulation:	6 hours
Max Rec. Temp. Deg. F:	180 °F
Equipment Number:	Unit 2
Location:	Greeley, CO
Recorded By:	Jared Hall
Witnessed By:	Mr. Jeff Lasley

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set forth in our current Price Schedule.

COMMENTS

Annular volume calculated for 4.5" casing
Patterson UTI Drilling Rig 34
Thank you for using Phoenix Surveys!
API #: 05-123-25511-00

Database File: SOS.db
Dataset Pathname: pass4
Presentation Format: monitor
Dataset Creation: Sun Sep 26 20:47:08 2038 by Log Open Caesar 070814
Charted by: Depth in Feet scaled 1:240

Caliper (in) 10 | Deep Resistivity (Ohm-m) .200 40 | Density Porosity (pu) 0
Gamma Ray (GAPI) 300 | Medium Resistivity (Ohm-m) .200 40 | Neutron Porosity (pu) 60
SP (mV) 100 | Shallow Resistivity (Ohm-m) .200 40

ABAYI (RJ)

2.06 SS Marks

2.75 LS Marks

Marks Change

2.06 SS Marks

Marks Change

2.06 SS Marks

Gamma Ray

Caliper

SP

Loggers TD 9600

Deep Resistivity

Medium Resistivity

Shallow Resistivity

Neutron Porosity

Density Porosity