DRILLING PROGRAM

Well Name: [redacted]
Location: [redacted]
Rig: [redacted]
Date: [redacted]

Casing Program

Hole Size	Casing Size	Weight	Grade	Connection	Depth (MD)	Depth (TVD)
36"	30"	310	X-56	BTC	120	120
26"	20"	133	K-55	BTC	1,500	1,500
17-1/2"	13-3/8"	68	L-80	BTC	5,200	5,200
12-1/4"	9-5/8"	47	P-110	LTC	10,800	10,800
8-1/2"	7"	29	P-110	BTC	12,500	12,500
6"	4-1/2"	13.5	P-110	BTC	14,200	14,200

Mud Program

Interval	Mud Type	Density (ppg)	Viscosity (sec/qt)	Fluid Loss (cc/30min)
0 - 1,500	Spud Mud	8.6 - 9.0	40 - 50	N/C
1,500 - 5,200	Low Solids Non-Dispersed	9.0 - 9.5	45 - 55	6 - 8
5,200 - 10,800	Low Solids Non-Dispersed	9.5 - 10.5	50 - 60	4 - 6
10,800 - 12,500	Low Solids Non-Dispersed	10.5 - 11.0	55 - 65	3 - 5
12,500 - 14,200	Low Solids Non-Dispersed	11.0 - 11.5	60 - 70	3 - 4

Cementing Program

Casing	Lead Cement	Tail Cement	Top of Cement
30"	Ready Mix		Surface
20"	Class G + 2% CaCl2	Class G + 0.2% Retarder	Surface
13-3/8"	Class G + 2% CaCl2	Class G + 0.2% Retarder	Surface
9-5/8"	Class G + 0.3% Fluid Loss + 0.2% Retarder	Class G + 0.2% Retarder	4,500' MD
7"	Class G + 0.3% Fluid Loss + 0.2% Retarder	Class G + 0.2% Retarder	10,300' MD
4-1/2"	Class G + 0.3% Fluid Loss + 0.2% Retarder		12,000' MD

Logging Program

Open Hole Logs: [redacted]
Cased Hole Logs: [redacted]
Mud Logging: [redacted]

Directional Program

Kick Off Point: [redacted]
Build Rate: [redacted]
Maximum Inclination: [redacted]
Target: [redacted]

Notes

[redacted]


6000
6050
6100
6150
6200
6250
6300
6350
6400
6450
6500
6550
6600
6650
6700
6750
6800
6850
6900
9
Collar Locator
-1
0
Gamma Ray (GAPI)
230
0
Amplitude (mV)
100
200
VDL
1200