



CEMENT BOND LOG
GR CCL
VDL

Company G3 OPERATING, LLC

Well TREMBLY 4-16

Field WILDCAT

County YUMA

State COLORADO

Location: AP # : 05-125-1026-00

SEC 4 TWP 2S RGE 42W

SE SE 79' FSL & 103' FEL

Other Services SYRAB PERF

Permanent Datum GL Elevation 3456

Log Measured From KB

Drilling Measured From KB

Date DECEMBER 3, 2008

Run Number 1

Depth Driller 1725

Depth Logger 1647

Bottom Logged Interval 1645

Top Log Interval 700

Open Hole Size 6.125

Type Fluid WATER

Density / Viscosity ---

Max. Recorded Temp. ---

Estimated Cement Top 350

Time Well Ready ROA

Time Logger on Bottom ---

Equipment Number 443

Location YUMA

Recorded By PHIL LOPEZ

Witnessed By RAY BIVENS

Run Number Bit From To Size Weight From To

Casing Record Size Variift Top Bottom

Production String

Line

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR CHOOSING JW WIRELINE
DEPTH REFERENCE TO OPEN HOLE LOG DATED NOV. 9, 2008
PERF INTERVAL 1464-1492 28' 2-SPF

Database File: trembly 4-16.db
Dataset Pathname: pass6
Presentation Format: scbl_sr
Dataset Creation: Wed Dec 03 07:21:53 2008 by Log Std Casedhole 07122
Charted by: Depth in Feet scaled 1:240

