
SECTOR BOND
GAMMA RAY
COLLAR CORRELATION LOG
Company: PHILLIPS PRODUCTION
Well: 3H-7
Field: BAY TRENDS
County: LOGAN
State: COLORADO
Other Services: NEUTRON
Permanent Datum: GL
Elevation: 4,218 ft
Log Measured From: KB
Drilling Measured From: KB
Elevation: KB 4,232 ft
DF 4,231 ft
GL 4,218 ft
Date: 11-Jan-2026
Run Number: ONE
Depth Driller: 10,000 ft
Depth Logger: 9,998 ft
Bottom Logged Interval: 9,996 ft
Top Logged Interval: 3,000 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Type Fluid in Hole: WATER BASED MUD
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Source of Sample: FLOWLINE
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Source of Rmf / Rmc: MEASURED / MEASURED
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 1
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 2
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 3
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 4
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 5
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 6
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 7
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 8
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 9
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 10
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 11
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 12
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 13
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 14
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 15
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 16
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 17
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 18
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 19
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 20
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 21
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 22
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 23
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 24
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 25
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 26
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 27
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 28
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 29
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 30
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 31
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 32
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 33
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 34
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 35
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 36
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 37
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 38
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 39
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 40
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 41
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 42
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 43
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. HOLLOWAY
Run 44
Top Log Int: 3,000 ft
Bottom Log Int: 9,998 ft
Casing Driller: 9.625 in @ 3,000 ft
Casing Logger: 9.625 in @ 3,000 ft
Bit Size: 8.500 in
Density / Viscosity: 9.2 lb/gal / 38 s
PH / Fluid Loss: 9.5 / 6.2 cc
Rm @ Meas Temp: 0.18 @ 72 °F
Rmf @ Meas Temp: 0.14 @ 72 °F
Rmc @ Meas Temp: 0.22 @ 72 °F
Rm @ BHT: 0.11 @ 168 °F
Time Since Circulation: 6 hr
Max Recorded Temp: 168 °F
Equipment Number: SLB-0412
Location: 38°12'44.6"N 103°41'27.3"W
Recorded By: M. ALVAREZ
Witnessed By: R. H