Schlumberger
Platform Express
Three Detector Lithology Density
Compensated Neutron
Array Induction Imager Tool
Gamma Ray
Cable Head Tension
Mud Resistivity
Mud Temperature
Mud Density
Mud Viscosity
Mud pH
Fluid Loss
Source
Rm @ Measured Temperature
Rmf @ Measured Temperature
Rmc @ Measured Temperature
Rm @ BHT
Time Since Circulation
Max Recorded Temperature
Equipment Number
Location
Recorded By
Witnessed By
Run Number
Depth Driller
Schlumberger Depth
Bottom Logged Interval
Top Logged Interval
Casing Driller Size @ Depth
Casing Schlumberger Size @ Depth
Bit Size
Type Fluid in Hole
Density
Viscosity
pH
Fluid Loss
Source of Sample



PEAK WIRELINE SERVICES, INC.

REPEAT SECTION

Database File:	wiepking.db
Dataset Pathname:	frs21305/run1/pass1
Presentation Format:	cbl_dr
Dataset Creation:	Mon Dec 01 13:01:29 2008 by Log Std Casedhole 07081
Charted by:	Depth in Feet scaled 1:240



Calibration Report

Database File:	wiepking.db
Dataset Pathname:	frs21305/run1/pass1
Dataset Creation:	Mon Dec 01 13:01:29 2008 by Log Std Casedhole 07081

Gamma Ray Calibration Report

Serial Number:	061120GR	
Tool Model:	PROBE	
Performed:	Tue Mar 25 10:18:41 2008	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	1.0000	GAPI/cps

Cement Bond Log Calibration Report

Serial Number:	040601		
Tool Model:	probe		
Performed:	Mon Dec 01 13:00:04 2008		
Depth:	1528.03	ft	
Casing Diameter:	5.5	in	
	3' Spacing	5' Spacing	
Signal Zero:	1	0	mV
Calibrated Amplitude:	71.921	71.921	mV
Reading at Signal Zero:	0.187012	0.0652344	V
Reading in Free Pipe:	1.09407	1.09182	V
Gain:	78.1881	70.0584	
Offset:	-13.6221	-4.57021	