
COMPANY REPORT
CASING PLOT
COLLAR CORRELATION LOG
Company: APACHE CORPORATION
Well: FEE 'A' 1 (API-42-317-35289)
Field: MIDLAND FARM
County: MIDLAND
State: TEXAS
Location: 660' FSL & 1980' FEL
SEC 38 BLK 38 T-3S R-9E
Elevation: KB 2,870 ft DF 2,869 ft GL 2,859 ft
Permanent Datum: GROUND LEVEL
Log Measured From: KB 11 ft above Perm. Datum
Drilling Measured From: KB
Date: 11/1/2023
Run Number: ONE
Depth Driller: 11,000 ft
Schlumberger Depth: 11,000 ft
Bottom Log Interval: 10,998 ft
Top Log Interval: 9,000 ft
Casing Driller: 9.625 in @ 4,000 ft
Casing Schlumberger: 4,000 ft
Bit Size: 8.5 in
Type Fluid in Hole: WBM
Density / Viscosity: 9.8 lb/gal 50 s
PH / Fluid Loss: 10.5 pH 6.4 cc
Source of Sample: FLOWLINE
Rm @ Meas. Temp: 0.14 ohm @ 70 degF
Rmf @ Meas. Temp: 0.11 ohm @ 70 degF
Rmc @ Meas. Temp: 0.18 ohm @ 70 degF
Source Rmf / Rmc: MEASURED / MEASURED
Rm @ BHT: 0.07 ohm @ 180 degF
Time Since Circulation: 4 hr
Max Rec. Temp: 180 degF
Equipment / Location: 1 / MIDLAND
Recorded By: J. SMITH
Witnessed By: M. JONES
Run 1
Top Log Int.: 9,000 ft
Base Log Int.: 10,998 ft
Bit Size: 8.5 in
Casing Driller: 9.625 in @ 4,000 ft
Casing Schlumberger: 4,000 ft
Density / Viscosity: 9.8 lb/gal 50 s
PH / Fluid Loss: 10.5 pH 6.4 cc
Rm @ Meas. Temp: 0.14 ohm @ 70 degF
Rmf @ Meas. Temp: 0.11 ohm @ 70 degF
Rmc @ Meas. Temp: 0.18 ohm @ 70 degF
Rm @ BHT: 0.07 ohm @ 180 degF
Max Rec. Temp: 180 degF
Equipment / Location: 1 / MIDLAND
Recorded By: J. SMITH
Witnessed By: M. JONES
Schlumberger
Gamma Ray (GR) API
Casing Collar Locator (CCL)
Tension (TENS) lbf
Cable Speed (CS) ft/min



Company: [redacted]
Well: [redacted]
Field: [redacted]
County: [redacted]
State: [redacted]
Country: [redacted]
API: [redacted]
Permanent Datum: Ground Level
Elevation: [redacted]
Log Measured From: Kelly Bushing
Drilling Measured From: Kelly Bushing
Date: [redacted]
Run: [redacted]
Service Order: [redacted]
Depth Reference: [redacted]
Depth Driller: [redacted]
Depth Logger: [redacted]
Bottom Log Interval: [redacted]
Top Log Interval: [redacted]
Casing Driller: [redacted]
Casing Logger: [redacted]
Bit Size: [redacted]
Type Fluid in Hole: [redacted]
Density / Viscosity: [redacted]
PH / Fluid Loss: [redacted]
Source of Sample: [redacted]
Rm @ Measured Temp: [redacted]
Rmf @ Measured Temp: [redacted]
Rmc @ Measured Temp: [redacted]
Rm @ BHT: [redacted]
Max Recorded Temp: [redacted]
Equipment Number: [redacted]
Location: [redacted]
Recorded By: [redacted]
Witnessed By: [redacted]

Schlumberger

Company: [redacted]
Well: [redacted]
Field: [redacted]
County: [redacted]
State: [redacted]
Country: [redacted]
API: [redacted]
Permanent Datum: Ground Level
Elevation: [redacted]
Log Measured From: Kelly Bushing
Drilling Measured From: Kelly Bushing
Date: [redacted]
Run: [redacted]
Service Order: [redacted]
Depth Reference: [redacted]
Depth Driller: [redacted]
Depth Logger: [redacted]
Bottom Log Interval: [redacted]
Top Log Interval: [redacted]
Casing Driller: [redacted]
Casing Logger: [redacted]
Bit Size: [redacted]
Type Fluid in Hole: [redacted]
Density / Viscosity: [redacted]
PH / Fluid Loss: [redacted]
Source of Sample: [redacted]
Rm @ Measured Temp: [redacted]
Rmf @ Measured Temp: [redacted]
Rmc @ Measured Temp: [redacted]
Rm @ BHT: [redacted]
Max Recorded Temp: [redacted]
Equipment Number: [redacted]
Location: [redacted]
Recorded By: [redacted]
Witnessed By: [redacted]

Schlumberger