Service Ticket No. 6900731 API No. 05051606600 PGM Ver. WARRIOR 7.0

The Well Name, Location, Borehole Description, and / or Cementing Data Furnished by Client

EQUIPMENT DATA

TELEMETRY		RST			
Run No.	TWO	Run No.	TWO	Run No.	
Serial No.	219455	Serial No.	115002214	Serial No.	
Model No.	TTS-C	Model No.	TTS-C-1.375	Model No.	
Diameter	1.69"	Diameter	1.375"	Diameter	

LOGGING DATA

General Data

Pass	Depths		Weight Head		Logging Run Comments
	From	To	Pressure	Volume	
ONE	354	SURFACE	0 PSI	0.0	MAIN SECTION

	GR		CCL		AMPLITUDE			
Pass	Scale		Scale		Scale		Scale	
No.	L	R	L	R	L	R	L	L
ONE	0	200	27	-3	0	100		

DIRECTIONAL INFORMATION

Maximum Deviation	deg. @	MD

MAIN SECTION

5" = 100'

HALLIBURTON

Database File: federal_11_9S_17_1_rbt.db
Dataset Pathname: MAIN
Presentation Format: radial
Dataset Creation: Sun Sep 06 11:46:38 2009
Charted by: Depth in Feet scaled 1:240

SPD	TT (usec)	325	TENSION (lb)	0	AMP (mV)	100	AMPAVG	100	200	MSG	1200	SECTORS	8
20	CCL	-20	(lb) 500	0	AMPS (mV)	20	AMPMAX	700					100
0	GR (GAPI)	200					0	AMPMIN	100				



SPD TT (usec) 325 TENSION (lb) 0 AMP (mV) 100 AMPAVG 100 200 MSG 1200 SECTORS 8
20 CCL -20 (lb) 500 0 AMPS (mV) 20 AMPMAX 700 100
0 GR (GAPI) 200 0 AMPMIN 100

MAIN SECTION

5" = 100'

HALLIBURTON

REPEAT SECTION

5" = 100'

HALLIBURTON

Database File: federal_11_9S_17_1_rbt.db
Dataset Pathname: REPT1
Presentation Format: radial
Dataset Creation: Sun Sep 06 11:46:56 2009
Charted by: Depth in Feet scaled 1:240

SPD TT (usec) 325 TENSION (lb) 0 AMP (mV) 100 AMPAVG 100 200 MSG 1200 SECTORS 8
20 CCL -20 (lb) 500 0 AMPS (mV) 20 AMPMAX 700 100
0 GR (GAPI) 200 0 AMPMIN 100



SPD TT (usec) 325 TENSION (lb) 0 AMP (mV) 100 AMPAVG 100 200 MSG 1200 SECTORS 8
20 CCL -20 (lb) 500 0 AMPS (mV) 20 AMPMAX 700 100
0 GR (GAPI) 200 0 AMPMIN 100

REPEAT SECTION

5" = 100'

HALLIBURTON

Database File: federal_11_9S_17_1_rbt.db Calibration Report
Dataset Pathname: REPT1
Dataset Creation: Sun Sep 06 11:46:56 2009

Segmented Cement Bond Log Calibration Report

Serial Number:	115002214
Tool Model:	004
Calibration Casing Diameter:	5.625 in
Calibration Depth:	174.655 ft

Master Calibration, performed Tue Aug 18 17:43:57 2009

	Raw (v)		Calibrated (inv.)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3FT	0.002	0.429	2.000	51.280	114.459	1.777
5FT	0.002	0.429	2.000	51.280	114.627	2.147
51	0.002	0.428	0.000	100.000	230.518	-0.389
52	0.002	0.428	0.000	100.000	229.671	-0.288
53	0.002	0.428	0.000	100.000	234.504	-0.470
54	0.002	0.428	0.000	100.000	227.122	-0.227
55	0.003	0.447	0.000	100.000	225.322	-0.764
56	0.007	0.447	0.000	100.000	227.259	-1.517
57	0.007	0.445	0.000	100.000	226.560	-0.240
58	0.007	0.427	0.000	100.000	237.781	-1.547

Calibration Report

Serial Number:	115002214
Tool Model:	004
Performed:	

Reference (degF)	Reading ()
Low: 0.000	0.000
High: 1.000	1.000
Gain = 1.000	Offset= 0.000

Gamma Ray Calibration Report

Serial Number:	216301
Tool Model:	ULTRA_LINK
Performed:	Sun Sep 06 10:40:15 2009
Calibrator Value:	230.0 GAPI
Background Reading:	25.9 cps
Calibrator Reading:	162.9 cps
Sensitivity:	1.6178 GAPI/cps

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	ID (in)
CCL	20.20		TTC(ULTRA_LINK (216315) Thruout Tubing Telemetry Cartridge - Ultrasonic	6.55	1.69	33.00
GR	17.34		ALH-001 (200001) Adapter Ultrasonic/Hydraulics	0.33	1.69	1.00
			TITAN_SNDH	2.85	2.63	20.00
			RBT-004 (115002214) Radial Bond Tool (OD 1 1/8)	9.47	3.13	140.00
			TITAN_SNDH	2.85	2.63	20.00
			SNDH_TERM	0.72	1.69	7.00

VVF3FT	0.21		
VVF5I	0.21		
VVF5O	0.21		
VVF51	0.21		
VVF52	0.21		
VVF53	0.21		
VVF54	0.21		
VVF55	0.21		
VVF56	0.21		
VVF57	0.21		
VVF58	0.21		
CBLFILT	0.21		
VVFPST	0.21		
LLMTEN	0.00		
RATEMP	0.00		
XHCLVRR	0.00		
XHVOLT	0.00		
XHJSTAT	0.00		
TSTAMP	0.00		
ITEMP1	0.00		
HVOLTX	0.00		

Dataset: federal_11_9S_17_1_rbt.db : field/wellman1/REPT1
Total Length: 22.28 ft
Total Weight: 215.00 lb
O.D. 3.13 in

Company	SG INTERESTS
Well	FEDERAL 11-9S-17 #1
Field	GUNNISON
County	WILDCAT
State	CO

RADIAL CEMENT BOND LOG

HALLIBURTON