

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	DLeg	TFace	VSec	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	700.0	0.00	0.00	700.0	0.0	0.0	0.00	0.00	0.0	
3	950.0	5.00	55.00	949.7	6.3	8.9	2.00	55.00	9.7	
4	1534.8	15.89	82.88	1524.2	30.9	109.6	2.00	39.15	112.8	
5	5165.1	15.89	82.88	5015.8	154.1	1095.6	0.00	0.00	1106.4	
6	5959.4	0.00	0.00	5800.0	167.6	1204.2	2.00	180.00	1215.8	Target BHL 1980'FNL & 1980'FEL
7	7138.4	0.00	0.00	6979.0	167.6	1204.2	0.00	0.00	1215.8	



Directional

NOBLE ENERGY INC WELD COUNTY CO

SEC.8-T6N-R63W

NCLP PC AA08-17D Pad Sec.8-T6N-R63W

NCLP PC AA08-07D

Wellbore #1

Plan: Noble NCLP PC AA08-07D Plan #1 (8-05-10)

Standard Planning Report

12 August, 2010



Database: EDM den0-adp01 Server Data
Company: NOBLE ENERGY INC WELD COUNTY CO
Project: SEC.8-T6N-R63W
Site: NCLP PC AA08-17D Pad Sec.8-T6N-R63W
Well: NCLP PC AA08-07D
Wellbore: Wellbore #1
Design: Noble NCLP PC AA08-07D Plan #1 (8-05-10)

Local Co-ordinate Reference: Well NCLP PC AA08-07D
TVD Reference: WELL @ 4724.0ft (Original Well Elev)
MD Reference: WELL @ 4724.0ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature

Project	SEC.8-T6N-R63W, Weld County, Colorado		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		Using Well Reference Point
Map Zone:	Colorado Northern Zone		Using geodetic scale factor

Site	NCLP PC AA08-17D Pad Sec.8-T6N-R63W				
Site Position:		Northing:	1,427,614.45 ft	Latitude:	40° 30' 9.252 N
From:	Lat/Long	Easting:	3,288,499.60 ft	Longitude:	104° 27' 45.144 W
Position Uncertainty:	0.0 ft	Slot Radius:	"	Grid Convergence:	0.67 °

Well	NCLP PC AA08-07D					
Well Position	+N/-S	-21.9 ft	Northing:	1,427,592.71 ft	Latitude:	40° 30' 9.036 N
	+E/-W	11.1 ft	Easting:	3,288,510.98 ft	Longitude:	104° 27' 45.000 W
Position Uncertainty		0.0 ft	Wellhead Elevation:	ft	Ground Level:	4,711.0 ft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	8/10/2010	8.82	67.21	53,308

Design: Noble NCLP PC AA08-07D Plan #1 (8-05-10)

Audit Notes:

Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (ft)	+N/-S (ft)	+E/-W (ft)	Direction (°)
	0.0	0.0	0.0	82.08

Plan Sections

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
700.0	0.00	0.00	700.0	0.0	0.0	0.00	0.00	0.00	0.00	
950.0	5.00	55.00	949.7	6.3	8.9	2.00	2.00	0.00	55.00	
1,534.8	15.89	82.88	1,524.2	30.9	109.6	2.00	1.86	4.77	39.15	
5,165.1	15.89	82.88	5,015.8	154.1	1,095.6	0.00	0.00	0.00	0.00	
5,959.4	0.00	0.00	5,800.0	167.6	1,204.2	2.00	-2.00	0.00	180.00	Target BHL 1980°FI
7,138.4	0.00	0.00	6,979.0	167.6	1,204.2	0.00	0.00	0.00	0.00	

Database: EDM den0-adp01 Server Data
Company: NOBLE ENERGY INC WELD COUNTY CO
Project: SEC.8-T6N-R63W
Site: NCLP PC AA08-17D Pad Sec.8-T6N-R63W
Well: NCLP PC AA08-07D
Wellbore: Wellbore #1
Design: Noble NCLP PC AA08-07D Plan #1 (8-05-10)

Local Co-ordinate Reference: Well NCLP PC AA08-07D
TVD Reference: WELL @ 4724.0ft (Original Well Elev)
MD Reference: WELL @ 4724.0ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
40.0	0.00	0.00	40.0	0.0	0.0	0.0	0.00	0.00	0.00
80.0	0.00	0.00	80.0	0.0	0.0	0.0	0.00	0.00	0.00
120.0	0.00	0.00	120.0	0.0	0.0	0.0	0.00	0.00	0.00
160.0	0.00	0.00	160.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
240.0	0.00	0.00	240.0	0.0	0.0	0.0	0.00	0.00	0.00
280.0	0.00	0.00	280.0	0.0	0.0	0.0	0.00	0.00	0.00
320.0	0.00	0.00	320.0	0.0	0.0	0.0	0.00	0.00	0.00
360.0	0.00	0.00	360.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
440.0	0.00	0.00	440.0	0.0	0.0	0.0	0.00	0.00	0.00
480.0	0.00	0.00	480.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
8 5/8"									
520.0	0.00	0.00	520.0	0.0	0.0	0.0	0.00	0.00	0.00
560.0	0.00	0.00	560.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
640.0	0.00	0.00	640.0	0.0	0.0	0.0	0.00	0.00	0.00
680.0	0.00	0.00	680.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
720.0	0.40	55.00	720.0	0.0	0.1	0.1	2.00	2.00	0.00
760.0	1.20	55.00	760.0	0.4	0.5	0.6	2.00	2.00	0.00
800.0	2.00	55.00	800.0	1.0	1.4	1.6	2.00	2.00	0.00
840.0	2.80	55.00	839.9	2.0	2.8	3.0	2.00	2.00	0.00
880.0	3.60	55.00	879.9	3.2	4.6	5.0	2.00	2.00	0.00
920.0	4.40	55.00	919.8	4.8	6.9	7.5	2.00	2.00	0.00
950.0	5.00	55.00	949.7	6.3	8.9	9.7	2.00	2.00	0.00
960.0	5.16	56.41	959.6	6.8	9.7	10.5	2.00	1.57	14.05
1,000.0	5.81	61.25	999.5	8.7	12.9	14.0	2.00	1.63	12.11
1,040.0	6.50	65.10	1,039.2	10.6	16.8	18.1	2.00	1.71	9.62
1,080.0	7.21	68.20	1,078.9	12.5	21.1	22.7	2.00	1.77	7.76
1,120.0	7.93	70.74	1,118.6	14.4	26.1	27.8	2.00	1.82	6.36
1,160.0	8.67	72.86	1,158.2	16.2	31.6	33.5	2.00	1.85	5.29
1,200.0	9.42	74.64	1,197.7	17.9	37.6	39.7	2.00	1.87	4.46
1,240.0	10.18	76.17	1,237.1	19.6	44.2	46.5	2.00	1.89	3.81
1,280.0	10.94	77.48	1,276.4	21.3	51.3	53.8	2.00	1.91	3.28
1,320.0	11.71	78.62	1,315.6	22.9	59.0	61.6	2.00	1.92	2.86
1,360.0	12.48	79.63	1,354.8	24.5	67.2	70.0	2.00	1.93	2.51
1,400.0	13.26	80.52	1,393.7	26.0	76.0	78.9	2.00	1.94	2.22
1,440.0	14.03	81.31	1,432.6	27.5	85.3	88.3	2.00	1.94	1.98
1,480.0	14.81	82.02	1,471.4	29.0	95.2	98.3	2.00	1.95	1.78
1,520.0	15.60	82.66	1,510.0	30.4	105.6	108.8	2.00	1.96	1.60
1,534.8	15.89	82.88	1,524.2	30.9	109.6	112.8	2.00	1.96	1.50
1,560.0	15.89	82.88	1,548.4	31.7	116.4	119.7	0.00	0.00	0.00
1,600.0	15.89	82.88	1,586.9	33.1	127.3	130.6	0.00	0.00	0.00
1,640.0	15.89	82.88	1,625.4	34.4	138.1	141.6	0.00	0.00	0.00
1,680.0	15.89	82.88	1,663.9	35.8	149.0	152.5	0.00	0.00	0.00
1,720.0	15.89	82.88	1,702.3	37.2	159.9	163.5	0.00	0.00	0.00
1,760.0	15.89	82.88	1,740.8	38.5	170.7	174.4	0.00	0.00	0.00
1,800.0	15.89	82.88	1,779.3	39.9	181.6	185.4	0.00	0.00	0.00
1,840.0	15.89	82.88	1,817.7	41.2	192.5	196.3	0.00	0.00	0.00
1,880.0	15.89	82.88	1,856.2	42.6	203.3	207.3	0.00	0.00	0.00
1,920.0	15.89	82.88	1,894.7	43.9	214.2	218.2	0.00	0.00	0.00

Database: EDM den0-adp01 Server Data
Company: NOBLE ENERGY INC WELD COUNTY CO
Project: SEC.8-T6N-R63W
Site: NCLP PC AA08-17D Pad Sec.8-T6N-R63W
Well: NCLP PC AA08-07D
Wellbore: Wellbore #1
Design: Noble NCLP PC AA08-07D Plan #1 (8-05-10)

Local Co-ordinate Reference: Well NCLP PC AA08-07D
TVD Reference: WELL @ 4724.0ft (Original Well Elev)
MD Reference: WELL @ 4724.0ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
1,960.0	15.89	82.88	1,933.2	45.3	225.1	229.2	0.00	0.00	0.00
2,000.0	15.89	82.88	1,971.6	46.7	235.9	240.1	0.00	0.00	0.00
2,040.0	15.89	82.88	2,010.1	48.0	246.8	251.1	0.00	0.00	0.00
2,080.0	15.89	82.88	2,048.6	49.4	257.7	262.0	0.00	0.00	0.00
2,120.0	15.89	82.88	2,087.1	50.7	268.5	272.9	0.00	0.00	0.00
2,160.0	15.89	82.88	2,125.5	52.1	279.4	283.9	0.00	0.00	0.00
2,200.0	15.89	82.88	2,164.0	53.4	290.2	294.8	0.00	0.00	0.00
2,240.0	15.89	82.88	2,202.5	54.8	301.1	305.8	0.00	0.00	0.00
2,280.0	15.89	82.88	2,240.9	56.2	312.0	316.7	0.00	0.00	0.00
2,320.0	15.89	82.88	2,279.4	57.5	322.8	327.7	0.00	0.00	0.00
2,360.0	15.89	82.88	2,317.9	58.9	333.7	338.6	0.00	0.00	0.00
2,400.0	15.39	82.88	2,356.4	60.2	344.6	349.6	0.00	0.00	0.00
2,440.0	15.89	82.88	2,394.8	61.6	355.4	360.5	0.00	0.00	0.00
2,480.0	15.89	82.88	2,433.3	63.0	366.3	371.5	0.00	0.00	0.00
2,520.0	15.89	82.88	2,471.8	64.3	377.2	382.4	0.00	0.00	0.00
2,560.0	15.89	82.88	2,510.2	65.7	388.0	393.4	0.00	0.00	0.00
2,600.0	15.89	82.88	2,548.7	67.0	398.9	404.3	0.00	0.00	0.00
2,640.0	15.89	82.88	2,587.2	68.4	409.8	415.3	0.00	0.00	0.00
2,680.0	15.89	82.88	2,625.7	69.7	420.6	426.2	0.00	0.00	0.00
2,720.0	15.89	82.88	2,664.1	71.1	431.5	437.2	0.00	0.00	0.00
2,760.0	15.89	82.88	2,702.6	72.5	442.3	448.1	0.00	0.00	0.00
2,800.0	15.89	82.88	2,741.1	73.8	453.2	459.1	0.00	0.00	0.00
2,840.0	15.89	82.88	2,779.6	75.2	464.1	470.0	0.00	0.00	0.00
2,880.0	15.89	82.88	2,818.0	76.5	474.9	481.0	0.00	0.00	0.00
2,920.0	15.89	82.88	2,856.5	77.9	485.8	491.9	0.00	0.00	0.00
2,960.0	15.89	82.88	2,895.0	79.2	496.7	502.9	0.00	0.00	0.00
3,000.0	15.89	82.88	2,933.4	80.6	507.5	513.8	0.00	0.00	0.00
3,040.0	15.89	82.88	2,971.9	82.0	518.4	524.7	0.00	0.00	0.00
3,080.0	15.89	82.88	3,010.4	83.3	529.3	535.7	0.00	0.00	0.00
3,120.0	15.89	82.88	3,048.9	84.7	540.1	546.6	0.00	0.00	0.00
3,160.0	15.89	82.88	3,087.3	86.0	551.0	557.6	0.00	0.00	0.00
3,200.0	15.89	82.88	3,125.8	87.4	561.9	568.5	0.00	0.00	0.00
3,240.0	15.89	82.88	3,164.3	88.7	572.7	579.5	0.00	0.00	0.00
3,280.0	15.89	82.88	3,202.7	90.1	583.6	590.4	0.00	0.00	0.00
3,320.0	15.89	82.88	3,241.2	91.5	594.5	601.4	0.00	0.00	0.00
3,360.0	15.89	82.88	3,279.7	92.8	605.3	612.3	0.00	0.00	0.00
3,400.0	15.89	82.88	3,318.2	94.2	616.2	623.3	0.00	0.00	0.00
3,440.0	15.89	82.88	3,356.6	95.5	627.0	634.2	0.00	0.00	0.00
3,480.0	15.89	82.88	3,395.1	96.9	637.9	645.2	0.00	0.00	0.00
3,520.0	15.89	82.88	3,433.6	98.2	648.8	656.1	0.00	0.00	0.00
3,560.0	15.89	82.88	3,472.1	99.6	659.6	667.1	0.00	0.00	0.00
3,600.0	15.89	82.88	3,510.5	101.0	670.5	678.0	0.00	0.00	0.00
3,640.0	15.89	82.88	3,549.0	102.3	681.4	689.0	0.00	0.00	0.00
3,680.0	15.89	82.88	3,587.5	103.7	692.2	699.9	0.00	0.00	0.00
3,720.0	15.89	82.88	3,625.9	105.0	703.1	710.9	0.00	0.00	0.00
3,760.0	15.89	82.88	3,664.4	106.4	714.0	721.8	0.00	0.00	0.00
3,800.0	15.89	82.88	3,702.9	107.7	724.8	732.8	0.00	0.00	0.00
3,840.0	15.89	82.88	3,741.4	109.1	735.7	743.7	0.00	0.00	0.00
3,880.0	15.89	82.88	3,779.8	110.5	746.6	754.7	0.00	0.00	0.00
3,920.0	15.89	82.88	3,818.3	111.8	757.4	765.6	0.00	0.00	0.00
3,960.0	15.89	82.88	3,856.8	113.2	768.3	776.5	0.00	0.00	0.00
4,000.0	15.89	82.88	3,895.3	114.5	779.1	787.5	0.00	0.00	0.00
4,040.0	15.89	82.88	3,933.7	115.9	790.0	798.4	0.00	0.00	0.00
4,080.0	15.89	82.88	3,972.2	117.2	800.9	809.4	0.00	0.00	0.00

Database: EDM den0-adp01 Server Data
Company: NOBLE ENERGY INC WELD COUNTY CO
Project: SEC.8-T6N-R63W
Site: NCLP PC AA08-17D Pad Sec.8-T6N-R63W
Well: NCLP PC AA08-07D
Wellbore: Wellbore #1
Design: Noble NCLP PC AA08-07D Plan #1 (8-05-10)

Local Co-ordinate Reference: Well NCLP PC AA08-07D
TVD Reference: WELL @ 4724.0ft (Original Well Elev)
MD Reference: WELL @ 4724.0ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
4,120.0	15.89	82.88	4,010.7	118.6	811.7	820.3	0.00	0.00	0.00
4,160.0	15.89	82.88	4,049.1	120.0	822.6	831.3	0.00	0.00	0.00
4,200.0	15.89	82.88	4,087.6	121.3	833.5	842.2	0.00	0.00	0.00
4,240.0	15.89	82.88	4,126.1	122.7	844.3	853.2	0.00	0.00	0.00
4,280.0	15.89	82.88	4,164.6	124.0	855.2	864.1	0.00	0.00	0.00
4,320.0	15.89	82.88	4,203.0	125.4	866.1	875.1	0.00	0.00	0.00
4,360.0	15.89	82.88	4,241.5	126.7	876.9	886.0	0.00	0.00	0.00
4,400.0	15.89	82.88	4,280.0	128.1	887.8	897.0	0.00	0.00	0.00
4,440.0	15.89	82.88	4,318.4	129.5	898.7	907.9	0.00	0.00	0.00
4,480.0	15.89	82.88	4,356.9	130.8	909.5	918.9	0.00	0.00	0.00
4,520.0	15.89	82.88	4,395.4	132.2	920.4	929.8	0.00	0.00	0.00
4,560.0	15.89	82.88	4,433.9	133.5	931.2	940.8	0.00	0.00	0.00
4,600.0	15.89	82.88	4,472.3	134.9	942.1	951.7	0.00	0.00	0.00
4,640.0	15.89	82.88	4,510.8	136.2	953.0	962.7	0.00	0.00	0.00
4,680.0	15.89	82.88	4,549.3	137.6	963.8	973.6	0.00	0.00	0.00
4,720.0	15.89	82.88	4,587.8	139.0	974.7	984.6	0.00	0.00	0.00
4,760.0	15.89	82.88	4,626.2	140.3	985.6	995.5	0.00	0.00	0.00
4,800.0	15.89	82.88	4,664.7	141.7	996.4	1,006.5	0.00	0.00	0.00
4,840.0	15.89	82.88	4,703.2	143.0	1,007.3	1,017.4	0.00	0.00	0.00
4,880.0	15.89	82.88	4,741.6	144.4	1,018.2	1,028.3	0.00	0.00	0.00
4,920.0	15.89	82.88	4,780.1	145.7	1,029.0	1,039.3	0.00	0.00	0.00
4,960.0	15.89	82.88	4,818.6	147.1	1,039.9	1,050.2	0.00	0.00	0.00
5,000.0	15.89	82.88	4,857.1	148.5	1,050.8	1,061.2	0.00	0.00	0.00
5,040.0	15.89	82.88	4,895.5	149.8	1,061.6	1,072.1	0.00	0.00	0.00
5,080.0	15.89	82.88	4,934.0	151.2	1,072.5	1,083.1	0.00	0.00	0.00
5,120.0	15.89	82.88	4,972.5	152.5	1,083.3	1,094.0	0.00	0.00	0.00
5,160.0	15.89	82.88	5,010.9	153.9	1,094.2	1,105.0	0.00	0.00	0.00
5,165.1	15.89	82.88	5,015.8	154.1	1,095.6	1,106.4	0.00	0.00	0.00
5,200.0	15.19	82.88	5,049.5	155.2	1,104.9	1,115.7	2.00	-2.00	0.00
5,240.0	14.39	82.88	5,088.2	156.5	1,115.0	1,125.9	2.00	-2.00	0.00
5,280.0	13.59	82.88	5,127.0	157.7	1,124.6	1,135.6	2.00	-2.00	0.00
5,320.0	12.79	82.88	5,165.9	158.8	1,133.7	1,144.7	2.00	-2.00	0.00
5,360.0	11.99	82.88	5,205.0	159.9	1,142.2	1,153.3	2.00	-2.00	0.00
5,400.0	11.19	82.88	5,244.2	160.9	1,150.1	1,161.3	2.00	-2.00	0.00
5,440.0	10.39	82.88	5,283.5	161.8	1,157.6	1,168.8	2.00	-2.00	0.00
5,480.0	9.59	82.88	5,322.9	162.7	1,164.5	1,175.8	2.00	-2.00	0.00
5,520.0	8.79	82.88	5,362.3	163.5	1,170.8	1,182.1	2.00	-2.00	0.00
5,560.0	7.99	82.88	5,401.9	164.2	1,176.6	1,188.0	2.00	-2.00	0.00
5,600.0	7.19	82.88	5,441.6	164.8	1,181.8	1,193.3	2.00	-2.00	0.00
5,640.0	6.39	82.88	5,481.3	165.4	1,186.5	1,198.0	2.00	-2.00	0.00
5,680.0	5.59	82.88	5,521.1	165.9	1,190.7	1,202.2	2.00	-2.00	0.00
5,720.0	4.79	82.88	5,560.9	166.4	1,194.2	1,205.8	2.00	-2.00	0.00
5,760.0	3.99	82.88	5,600.8	166.8	1,197.3	1,208.8	2.00	-2.00	0.00
5,800.0	3.19	82.88	5,640.7	167.1	1,199.8	1,211.3	2.00	-2.00	0.00
5,840.0	2.39	82.88	5,680.7	167.3	1,201.7	1,213.3	2.00	-2.00	0.00
5,880.0	1.59	82.88	5,720.6	167.5	1,203.1	1,214.7	2.00	-2.00	0.00
5,920.0	0.79	82.88	5,760.6	167.6	1,203.9	1,215.5	2.00	-2.00	0.00
5,959.4	0.00	0.00	5,800.0	167.6	1,204.2	1,215.8	2.00	-2.00	0.00
Target BHL 1980'FNL & 1980'FEL									
5,960.0	0.00	0.00	5,800.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,000.0	0.00	0.00	5,840.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,040.0	0.00	0.00	5,880.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,080.0	0.00	0.00	5,920.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,120.0	0.00	0.00	5,960.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00

Database: EDM den0-adp01 Server Data
Company: NOBLE ENERGY INC WELD COUNTY CO
Project: SEC.8-T6N-R63W
Site: NCLP PC AA08-17D Pad Sec.8-T6N-R63W
Well: NCLP PC AA08-07D
Wellbore: Wellbore #1
Design: Noble NCLP PC AA08-07D Plan #1 (8-05-10)

Local Co-ordinate Reference: Well NCLP PC AA08-07D
TVD Reference: WELL @ 4724.0ft (Original Well Elev)
MD Reference: WELL @ 4724.0ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
6,160.0	0.00	0.00	6,000.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,200.0	0.00	0.00	6,040.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,240.0	0.00	0.00	6,080.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,280.0	0.00	0.00	6,120.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,320.0	0.00	0.00	6,160.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,360.0	0.00	0.00	6,200.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,400.0	0.00	0.00	6,240.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,440.0	0.00	0.00	6,280.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,480.0	0.00	0.00	6,320.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,520.0	0.00	0.00	6,360.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,560.0	0.00	0.00	6,400.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,600.0	0.00	0.00	6,440.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,640.0	0.00	0.00	6,480.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,680.0	0.00	0.00	6,520.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,683.4	0.00	0.00	6,524.0	167.6	1,204.2	1,215.8	0.00	0.00	0.00
NIOBRARA - Legal Box 400' x 400' 1979'FNL, 2009'FEL - Target Circle 1980'FNL & 1980'FEL									
6,720.0	0.00	0.00	6,560.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,760.0	0.00	0.00	6,600.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,800.0	0.00	0.00	6,640.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,840.0	0.00	0.00	6,680.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,880.0	0.00	0.00	6,720.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,920.0	0.00	0.00	6,760.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,960.0	0.00	0.00	6,800.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
6,988.4	0.00	0.00	6,829.0	167.6	1,204.2	1,215.8	0.00	0.00	0.00
CODELL									
7,000.0	0.00	0.00	6,840.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
7,040.0	0.00	0.00	6,880.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
7,080.0	0.00	0.00	6,920.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
7,120.0	0.00	0.00	6,960.6	167.6	1,204.2	1,215.8	0.00	0.00	0.00
7,138.4	0.00	0.00	6,979.0	167.6	1,204.2	1,215.8	0.00	0.00	0.00

Targets

Target Name

- hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Northing (ft)	Easting (ft)	Latitude	Longitude
Legal Box 400' x 400'	0.00	0.00	6,524.0	168.6	1,175.2	1,427,775.04	3,289,684.09	40° 30' 10.702 N	104° 27' 29.787 W
- plan misses target center by 29.0ft at 6683.4ft MD (6524.0 TVD, 167.6 N, 1204.2 E)									
- Rectangle (sides W400.0 H400.0 D455.0)									
Target Circle 1980'FN	0.00	0.00	6,524.0	167.6	1,204.2	1,427,774.41	3,289,713.05	40° 30' 10.692 N	104° 27' 29.412 W
- plan hits target center									
- Circle (radius 75.0)									
Target BHL 1980'FNL	0.00	0.00	5,800.0	167.6	1,204.2	1,427,774.41	3,289,713.05	40° 30' 10.692 N	104° 27' 29.412 W
- plan hits target center									
- Point									

Database: EDM den0-adp01 Server Data
Company: NOBLE ENERGY INC WELD COUNTY CO
Project: SEC.8-T6N-R63W
Site: NCLP PC AA08-17D Pad Sec.8-T6N-R63W
Well: NCLP PC AA08-07D
Wellbore: Wellbore #1
Design: Noble NCLP PC AA08-07D Plan #1 (8-05-10)

Local Co-ordinate Reference: Well NCLP PC AA08-07D
TVD Reference: WELL @ 4724.0ft (Original Well Elev)
MD Reference: WELL @ 4724.0ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature

Casing Points

Measured Depth (ft)	Vertical Depth (ft)	Name	Casing Diameter (")	Hole Diameter (")
500.0	500.0	8 5/8"	8-5/8	12-1/4

Formations

Measured Depth (ft)	Vertical Depth (ft)	Name	Lithology	Dip (°)	Dip Direction (°)
6,683.4	6,524.0	NIOBRARA		0.00	
6,988.4	6,829.0	CODELL		0.00	