

NORTH AMERICA - NORTH AMERICA GAS - BP

Region: NORTH AMERICA	Event: COM- ONSHORE	Wellbore #: OH	Datum Elevation: 6,746.0ft
Bus Unit: NORTH AMERICA GAS	Start Date: 12/8/2009	Top TMD: 16.0ft	Ground Level: 6,730.0ft
Perf Unit: WEST	End Date: 8/27/2010	Bottom TMD: 3,483.0ft	Datum: ROTARY KELLY BUSHING
Field: IGNACIO BLANCO	Objective: NEW DRILL	Spud: 12/4/2009 10:15	Report Date: 8/27/2010
Asset: SAN JUAN	State/Prov: COLORADO	API No.: 0506709691	Slot No.:

Casing Details	Casing Depths	Wellsketch (8/27/2010)	Equip. Depth	Equip. Details	Perforations	STIM	LOG	Hole Depths
CASING PUPJOINT 8.625 in. , J-55, 24 CASING HANGER 5.5 in. , L-80 CASING PUPJOINT 8.625 in. , J-55, 24 CASING JOINTS 8.63 in. , J-55, 24 CASING JOINTS 5.5 in. , J-55, 15.5 CASING JOINTS 5.5 in. , J-55, 15.5 FLOAT COLLAR 8.625 in. , L-80 CASING JOINTS 8.625 in. , J-55, 24 FLOAT SHOE 8.625 in. , L-80	16.5ft 16.5ft 17.9ft 22.9ft 17.9ft 20.2ft 430.4ft 431.8ft 473.0ft 474.7ft	<p>16.0ft (TOC) 16.5ft (TOC) 26.0ft 12.250in 475.0ft 7.875in 3483.0ft</p>	12.0ft 12.0ft 38.0ft 63.0ft 67.0ft 12.8ft	TBG HANGER 26'FT POLISH ROD 1" X 25'FT GUIDED MOLDED STICK ROD 1" X 4'FT GUIDED MOLDED PONY ROD 1" #6R CO-ROD Tubing, Tubing, 2 7/8 , 6.5 , P-110, External-Ups 1" X 4'FT PONY ROD 1" 20K DOG BONE SHEAR TOOL .875" X 25' FULL STICK ROD .875" X 4'FT PONY ROD 2.875 F-NIPPLE - L-80 2.5" X 1.5" X 16'FT RWAC INSERT PUMP EXPENDABLE CHECK VALVE 2.875 - N-80 PORTED PUP Tubing, Tubing, 2 7/8 , 6.5 , P-110, External-Ups MULESHOE	 <			