PSI

COMPENSATED DENSITY
DUAL SPACED NEUTRON
GAMMA RAY

Company: Petroleum Services, Inc.
Well: Amanda #2-H
Field: Spearfish
County, State: Crook, Wyoming
API #: 49-005-03148-00-00
Location: 1,000' FNL & 1,000' FWL
Sec. 16, T54N, R64W
Elevations: GL: 3,600' KB: 3,625'
Drilling Fluid Type: Fresh Water Gel
Max Temp: 240°F
Logging Date: 10-Jul-2015
Run Number: One
Depth Driller: 10,000'
Depth Logger: 9,999'
Bottom Logged Interval: 9,999'
Top Logged Interval: 1,500'
Casing Driller: 9-5/8" @ 1,500'
Casing Logger: 1,500'
Bit Size: 8-3/4"
Type Fluid in Hole: Fresh Water Gel
Density / Viscosity: 8.4 ppg / 28 sec
pH / Fluid Loss: 9.0 / 6.0 cc
Source of Sample: Flowline
Rm @ Meas. Temp: 0.0 @ 0°F
Rmf @ Meas. Temp: 0.0 @ 0°F
Rmc @ Meas. Temp: 0.0 @ 0°F
Source of Rmf / Rmc: Measured / Calculated
Rm @ BHT: 0.0 @ 240°F
Time Since Circulation: 12 hours
Time on Bottom: 10-Jul-2015 @ 18:00
Max Recorded Temperature: 240°F
Equipment / Location: 8866 / Sundance, Colorado
Recorded By: Jeff Hall
Witnessed By: Mr. Ted Wilson

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and will not guarantee the accuracy or correctness of any interpretation and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current price schedule.

Comments:

Annular volume calculated for 4.5" casing
Mid Continent Rig 1
Thank you for using Phoenix Surveys!!
API #: 49-05-03148-00-00

Cellulose Fiber 10035 lb
Deepest Penetration 9999 ft
Deepest Location Sec 16 T54N R64W
Contact Location Start Mon, Mar 23, 15 08:56 [CST] by Log: Open Casedl [MCH1]
Contact Time Finish Fri, Jul 10, 15 18:00 [CST]

Density Caliper Ave 8.5 in
Gamma Ray (GAPI) 150
Density Porosity (pu) 45
Neutron Porosity (pu) -15

Data Resolution: 2 Points 0.5ft
Medium Resolution: 5 Points 1ft
Smallest Resolution: 10 Points 2ft

Density Porosity (pu) 45
Neutron Porosity (pu) -15

DEPTH (MD)

1:240 (5" Wide)

1:1200 (1" Wide)

Cellulose Fiber 10035 lb
Deepest Penetration 9999 ft
Deepest Location Sec 16 T54N R64W
Contact Location Start Mon, Mar 23, 15 08:56 [CST] by Log: Open Casedl [MCH1]
Contact Time Finish Fri, Jul 10, 15 18:00 [CST]

Caliper (in) 6
Gamma Ray (GAPI) 150
Density Porosity (pu) 45
Neutron Porosity (pu) -15

DEPTH (MD)

1:1200 (1" Wide)

1:240 (5" Wide)

Gamma Ray

Caliper

Density Porosity

Neutron Porosity

Logged TD: 9999'

Caliper (in) 6
Gamma Ray (GAPI) 150
Density Porosity (pu) 45
Neutron Porosity (pu) -15

DEPTH (MD)

Data Resolution: 2 Points 0.5ft
Medium Resolution: 5 Points 1ft
Smallest Resolution: 10 Points 2ft

Density Porosity (pu) 45
Neutron Porosity (pu) -15