Company: Crescent Petroleum Oil & Gas, LLC
Well: Ute Tribal 15-19-2-1E
Field: Wonsits Valley
County: Uintah
State: Utah
Location: SW SE Sec 19 T2S R1E
Elevation: Ground Level: 5,313.00 ft
Kelly Bushing: 5,328.00 ft
Drilling Measured From: Kelly Bushing
Permanent Datum: Ground Level
Log Measured From: Kelly Bushing, 15.00 ft above Permanent Datum
Date: 10-Jul-12
Run Number: ONE
Depth Driller: 10,000.00 ft
Depth Logger: 9,997.00 ft
Bottom Logged Interval: 9,997.00 ft
Top Logged Interval: 3,500.00 ft
Casing Driller Size: 9.625 in @ 3,500.00 ft
Casing Logger Size: 9.625 in @ 3,500.00 ft
Bit Size: 8.750 in
Type Fluid in Hole: Water Based Mud
Density: 9.20 lbm/gal
Viscosity: 38.00 s/qt
PH: 9.00
Fluid Loss: 8.00 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.900 @ 70.00 degF
Rmf @ Measured Temp: 0.700 @ 70.00 degF
Rmc @ Measured Temp: 1.200 @ 70.00 degF
Source of Rmf and Rmc: Measured
Rm @ BHT: 0.450 @ 180.00 degF
Time Circulation Stopped: 03:00
Time Logger on Bottom: 08:00
Maximum Recorded Temperature: 180.00 degF
Equipment Number: 3
Location: Vernal, UT
Recorded By: Jeff Hall
Witnessed By: Jeff Hall

Comments

All calculations performed and interpreted in accordance with generally accepted principles and practices. Schlumberger is not responsible for the use of, or any interpretation of, any information, or any consequence of its use, or any decision based upon, or action taken in reliance on, any such data, interpretation or information furnished or rendered. Schlumberger will not be liable for any loss, cost, damage or expense in connection therewith. These interpretations are also subject to our general terms and conditions set forth in our current price schedule.

Comments

Annular volume calculated for 4.5" casing
Design Drilling Rig 33
Thank you for using Phoenix Surveys
API # 43-125-36140

Database File: 12Sec.db
Dataset Pathname:
Presentation Format: Main2
Dataset Creation: Wed Aug 15 10:34:06 2012
Charted by: Depth in Feet scaled 1:240

Gamma Ray (GAPI) 0 150
Density Caliper (in) 6 16
Density Porosity (pu) 45 -15
Neutron Porosity (pu) 45 -15
Caliper (in) 6 16
Connection (gtm) 0 1
Mains (ft) 1 : 240

3,500
3,600
3,700
3,800
3,900
4,000
4,100
4,200
4,300
4,400
4,500
4,600
4,700
4,800
4,900
5,000
5,100
5,200
5,300
5,400
5,500
5,600
5,700
5,800
5,900
6,000
6,100
6,200
6,300
6,400
6,500
6,600
6,700
6,800
6,900
7,000
7,100
7,200
7,300
7,400
7,500
7,600
7,700
7,800
7,900
8,000
8,100
8,200
8,300
8,400
8,500
8,600
8,700
8,800
8,900
9,000
9,100
9,200
9,300
9,400
9,500
9,600
9,700
9,800
9,900
10,000

3.94 Min Mains

3.95 Min Mains

3.94 Min Mains

3.95 Min Mains

3.94 Min Mains

3.95 Min Mains