


Bmp's

WEXPRO COMPANY CONSTRUCTION LAYOUT FOR

FIGURE #1

CARL ALLEN #38 & #39
SECTION 33, T12N, R97W, 6th P.M.
NE 1/4 SW 1/4

CONSTRUCT
DIVERSION
DITCH



SCALE: 1" = 60'
DATE: 07-28-08
Drawn By: S.L.
REVISED: 08-02-10

C-6.9'
El. 597.4'

Approx.
Top of
Cut Slope

Topsoil Stockpile

EROSION CONTROL DEVICE

F-0.9'
El. 589.6'

Round Corners
as Needed

GRADE
El. 590.5'

Sta. 4+00

Construct
Berm

NOTE:
Flare Pit is to
be located a min.
of 100' from the
Well Head.



C-1.8'
El. 592.3'

C-0.7'
El. 591.2'

Sta. 2+00

El. 597.9'
C-19.4'
(btm. pit)

Total Pit Capacity
W/2' of Freeboard
= 38,470 Bbls.±
Total Pit Volume
= 9,890 Cu. Yds

C-0.4'
El. 590.9'

F-3.0'
El. 587.5'

Reserve Pit Backfill
& Spoils Stockpile

10' WIDE BENCH

RESERVE PITS
12' DEEP

CONSTRUCT
DIVERSION
DITCH

El. 600.8'
C-22.3'
(btm. pit)

1 1/2 : 1 SLOPE

10' WIDE BENCH

MAX. AREA OF DISTURBANCE

C-4.6'
El. 595.1'

C-3.4'
El. 593.9'

Sta. 0+50

Sta. 0+00

Proposed Access
Road

Approx.
Toe of
Fill Slope

F-2.5'
El. 588.0'

Install CMP
as Needed

Elev. Ungraded Ground at #39 Location Stake = 6591.2'

Elev. Graded Ground at #39 Location Stake = 6590.5'

UINTAH ENGINEERING & LAND SURVEYING
85 So. 200 East * Vernal, Utah 84078 * (435) 789-1017