PSI

PHOENIX SURVEYS, INC.

Cement Bond Log
Gamma Ray - CCL - VDL

Company	Rosetta Resources Operating, LP
Well	Bowman 11-09
Field	Blizzard
County	Yuma
State	Colorado

Company	Rosetta Resources Operating LP
Well	Bowman 11-09
Field	Blizzard
County	Yuma
State	Colorado

Location	API # - 05-125-31102
Other Services	
Permanent Datum	GL
Log Measured From	KB, 10 Ft. Above Perm. Datum
Drilling Measured From	KB
Elevation	GL 3,974 Ft. KB 3,984 Ft.
Date	8-Apr-2010
Run Number	ONE
Depth Driller	2,822 Ft.
Depth Logger	2,822 Ft.
Bottom Logged Interval	2,815 Ft.
Top Logged Interval	SURFACE
Casing Driller	8.625 in @ 1,240 Ft.
Casing Logger	1,240 Ft.
Bit Size	7.875 in
Type Fluid in Hole	FRESH WATER
Density	8.4 lb/gal
Viscosity	28 s
Fluid Loss	0 cc
Source of Sample	FLOWLINE
Rm @ Meas. Temp.	0.1 @ 70 °F
Rmf @ Meas. Temp.	0.1 @ 70 °F
Rmc @ Meas. Temp.	0.1 @ 70 °F
Source of Rmf & Rmc	MEASURED
Rm @ BHT	0.1 @ 70 °F
Time Since Circulation	2 HRS
Max. Rec. Temp.	70 °F
Equipment Number	3002
Location	Burlington
Recorded By	Brandon
Witnessed By	Mr. Rosetta

Full Name

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except to the extent of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Depth Ref to PSI Tripple Combo Log dated 8-Apr-2010.
Run CBL from TD to 200' above cement top.
Perforate 2182-2192 @ 4 SPF, 10' NET, 40 Shots,
using Titan 15gm, 0.40"EHD, 40.80"PENE, 120deg phasing.
API# 05-125-11754-00
Thank you for using Phoenix Surveys!!

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			STH3RD Standard Cable Head	1.00	1.69	1.00
			SDS/CENT Centralizer	2.67	2.75	24.00
WVF3	12.04		CBL-Probe (650215)	8.75	2.75	93.00
WVF5	11.04					
			SDS/CENT Centralizer	2.67	2.75	24.00
CCL	3.63		GR_CCL-6DS (SDS5EMOD) GR/CCL collar/Perf/Temp	4.92	2.75	60.00
GR	0.90					

Dataset: rosetta_bowman_11-09.db: fieldrelrun1/pass2
Total Length: 20.41 ft
Total Weight: 276.67 lb
O.D: 2.75 in

Database File: rosetta_bowman_11-09.db
Dataset Pathname: rel_pf
Presentation Format: cbl_pf
Dataset Creation: Mon May 03 09:40:20 2010 by Log Std Case2hole 09001
Charted by: Depth in Feet scaled 1:240

324	Travel Time (usec)	225
0	CCL	10
0	GR (GAPI)	250

0	Amplified Amplitude (mV)	20,000
0	Amplitude (mV)	100

Variable Density 1200

End Top of Cement

Flag Joint

Amplified Amplitude

Casing Collars

Amplitude

Gamma Ray

Total Depth @ 2445'

Travel Time

324	Travel Time (usec)	225
0	CCL	10
0	GR (GAPI)	250

0	Amplified Amplitude (mV)	20,000
0	Amplitude (mV)	100

Variable Density 1200