



Well Details: CC 697-10-42B

+N/-S	+E/-W	TVD Reference: GL 8348' & RKB 30' @ 8378.00ft	Bound Level: 8348.00	Slot		
0.00	0.00	Northing	Easting	Latitude	Longitude	
		629189.19	1235006.02	39° 31' 46.511 N	108° 12' 44.799 W	R

REFERENCE INFORMATION

Co-ordinate (N/E) Reference: Well CC 697-10-42B - Slot R, True North
Vertical (TVD) Reference: GL 8348' & RKB 30' @ 8378.00ft
Section (VS) Reference: Slot - R(0.00N, 0.00E)
Measured Depth Reference: GL 8348' & RKB 30' @ 8378.00ft
Calculation Method: Minimum Curvature

PROJECT DETAILS: Garfield County, CO NAD27

Geodetic System: US State Plane 1927 (Exact solution)
Datum: NAD 1927 (NADCON CONUS)
Ellipsoid: Clarke 1866
Zone: Colorado Central 502

System Datum: Mean Sea Level

Plan: OH

10:02, February 24 2011
Created By: Rex Hall



Scientific
Drilling

Directional Survey Certification

7327 West Barton Road
Casper, WY 82604
(307)-472-6621 Fax (307) 472-5439

Operator	OXY USA RMAT
Well Name & No.	Cascade Creek 697-10-42B
County & State	Garfield County, CO
SDI Job No.	42DEF10121382
Rig	H&P 353

I, Rex Hall, having personal knowledge of all the facts, hereby
certify that the attached directional survey run from a measured depth of 0 feet to a
measured depth of 9204 feet is true and correct as determined from all available records.


Signature

24-Feb-11
Date

Rex Hall
Grand Junction Drilling Engineer
Scientific Drilling - Rocky Mountain District

OXY USA RMAT

**Garfield County, CO NAD27
Cascade Creek 697-15-01 Pad
CC 697-10-42B - Slot R**

OH

Design: OH

Standard Survey Report

24 February, 2011

Scientific Drilling International

Survey Report

Company:	OXY USA RMAT	Local Co-ordinate Reference:	Well CC 697-10-42B - Slot R
Project:	Garfield County, CO NAD27	TVD Reference:	GL 8348' & RKB 30' @ 8378.00ft
Site:	Cascade Creek 697-15-01 Pad	MD Reference:	GL 8348' & RKB 30' @ 8378.00ft
Well:	CC 697-10-42B	North Reference:	True
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	Rockies-R5000.1

Project	Garfield County, CO NAD27		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	Colorado Central 502		

Site						Cascade Creek 697-15-01 Pad, Sec 15 T6S R97W											
Site Position:			Northing:			629,156.97 usft			Latitude:			39° 31' 46.180 N					
From:			Map			Easting:			1,234,961.93 usft			Longitude:			108° 12' 45.350 W		
Position Uncertainty:			0.00 ft			Slot Radius:			13.200 in			Grid Convergence:			-1.71 °		

Well	CC 697-10-42B - Slot R					
Well Position	+N/-S	0.00 ft	Northing:	629,189.19 usft	Latitude:	39° 31' 46.511 N
	+E/-W	0.00 ft	Easting:	1,235,006.02 usft	Longitude:	108° 12' 44.799 W
Position Uncertainty		0.00 ft	Wellhead Elevation:	ft	Ground Level:	8,348.00 ft

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	2010/11/24	10.52	65.74	52,277

Design	OH				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (ft)	+N/-S (ft)	+E/-W (ft)	Direction (°)	
	0.00	0.00	0.00	8.56	

Survey Program	Date	2011/02/24			
From (ft)	To (ft)	Survey (Wellbore)	Tool Name	Description	
248.00	2,660.00	Survey #1 - Surface MWD (OH)	MWD-SDI	MWD - Standard ISCWSA	
2,787.00	9,204.00	Survey #2 - Production MWD (OH)	MWD-SDI	MWD - Standard ISCWSA	

Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
248.00	1.76	357.71	247.96	3.81	-0.15	3.74	0.71	0.71	0.00	
First SDI MWD Survey										
340.00	3.71	3.02	339.85	8.19	-0.05	8.09	2.14	2.12	5.77	
432.00	4.71	19.08	431.61	14.73	1.34	14.77	1.67	1.09	17.46	
525.00	5.89	3.56	524.21	23.10	2.88	23.28	1.99	1.27	-16.69	
617.00	6.42	359.16	615.68	32.96	3.10	33.05	0.77	0.58	-4.78	
710.00	7.83	1.54	707.96	44.49	3.20	44.47	1.55	1.52	2.56	
802.00	7.47	13.75	799.15	56.57	4.79	56.65	1.81	-0.39	13.27	
897.00	6.86	13.23	893.41	68.09	7.55	68.45	0.65	-0.64	-0.55	

Scientific Drilling International

Survey Report

Company:	OXY USA RMAT	Local Co-ordinate Reference:	Well CC 697-10-42B - Slot R
Project:	Garfield County, CO NAD27	TVD Reference:	GL 8348' & RKB 30' @ 8378.00ft
Site:	Cascade Creek 697-15-01 Pad	MD Reference:	GL 8348' & RKB 30' @ 8378.00ft
Well:	CC 697-10-42B	North Reference:	True
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	Rockies-R5000.1

Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
991.00	8.18	9.27	986.60	80.15	9.91	80.74	1.51	1.40	-4.21
1,086.00	9.23	8.13	1,080.50	94.37	12.08	95.11	1.12	1.11	-1.20
1,180.00	11.08	8.39	1,173.02	110.77	14.46	111.68	1.97	1.97	0.28
1,275.00	12.31	9.54	1,266.05	129.78	17.48	130.94	1.32	1.29	1.21
1,370.00	12.66	5.93	1,358.80	150.13	20.23	151.46	0.90	0.37	-3.80
1,464.00	13.81	7.25	1,450.31	171.50	22.71	172.97	1.26	1.22	1.40
1,559.00	13.45	6.81	1,542.63	193.72	25.45	195.35	0.39	-0.38	-0.46
1,653.00	14.51	6.37	1,633.85	216.28	28.05	218.04	1.13	1.13	-0.47
1,748.00	16.27	8.39	1,725.44	241.27	31.32	243.25	1.94	1.85	2.13
1,842.00	16.71	9.27	1,815.57	267.64	35.41	269.93	0.54	0.47	0.94
1,937.00	17.94	10.77	1,906.26	295.49	40.35	298.21	1.38	1.29	1.58
2,031.00	18.38	10.59	1,995.58	324.28	45.78	327.48	0.47	0.47	-0.19
2,126.00	18.11	10.24	2,085.80	353.53	51.15	357.21	0.31	-0.28	-0.37
2,220.00	19.08	10.06	2,174.89	383.04	56.44	387.17	1.03	1.03	-0.19
2,315.00	19.70	10.06	2,264.50	414.09	61.95	418.70	0.65	0.65	0.00
2,409.00	18.82	9.36	2,353.24	444.65	67.18	449.70	0.97	-0.94	-0.74
2,504.00	19.79	8.39	2,442.90	475.68	72.02	481.10	1.08	1.02	-1.02
2,598.00	19.61	8.30	2,531.40	507.04	76.62	512.79	0.19	-0.19	-0.10
2,660.00	18.99	7.07	2,589.91	527.34	79.36	533.28	1.20	-1.00	-1.98
Last Survey in 14 3/4" Hole									
2,787.00	18.02	5.53	2,710.35	567.40	83.80	573.55	0.86	-0.76	-1.21
First SDI Production MWD Survey									
2,882.00	16.35	3.79	2,801.10	595.37	86.10	601.55	1.84	-1.76	-1.83
2,976.00	15.38	7.51	2,891.52	620.93	88.60	627.20	1.49	-1.03	3.96
3,071.00	15.92	9.25	2,983.00	646.28	92.34	652.83	0.75	0.57	1.83
3,165.00	16.04	10.36	3,073.37	671.78	96.75	678.70	0.35	0.13	1.18
3,260.00	18.73	10.60	3,164.02	699.69	101.92	707.07	2.83	2.83	0.25
3,354.00	19.08	8.31	3,252.95	729.73	106.91	737.51	0.87	0.37	-2.44
3,449.00	18.99	8.84	3,342.76	760.36	111.53	768.50	0.21	-0.09	0.56
3,543.00	19.61	8.05	3,431.47	791.10	116.09	799.56	0.72	0.66	-0.84
3,638.00	19.79	10.16	3,520.91	822.71	121.16	831.58	0.77	0.19	2.22
3,732.00	19.61	10.86	3,609.41	853.87	126.94	863.25	0.32	-0.19	0.74
3,827.00	20.14	10.95	3,698.75	885.58	133.05	895.52	0.56	0.56	0.09
3,921.00	20.31	11.04	3,786.96	917.48	139.25	927.99	0.18	0.18	0.10
4,016.00	18.82	11.74	3,876.47	948.67	145.52	959.76	1.59	-1.57	0.74
4,110.00	21.28	12.62	3,964.77	980.16	152.34	991.92	2.64	2.62	0.94
4,205.00	21.54	8.67	4,053.22	1,014.23	158.73	1,026.55	1.54	0.27	-4.16
4,299.00	20.75	8.84	4,140.89	1,047.74	163.89	1,060.46	0.84	-0.84	0.18
4,394.00	19.08	9.55	4,230.20	1,079.68	169.05	1,092.82	1.78	-1.76	0.75
4,488.00	19.26	9.02	4,318.99	1,110.14	174.03	1,123.68	0.27	0.19	-0.56
4,583.00	18.38	8.49	4,408.91	1,140.43	178.70	1,154.33	0.94	-0.93	-0.56
4,677.00	17.32	8.93	4,498.38	1,168.91	183.06	1,183.14	1.14	-1.13	0.47
4,772.00	18.11	10.16	4,588.88	1,197.42	187.86	1,212.04	0.92	0.83	1.29

Scientific Drilling International

Survey Report

Company:	OXY USA RMAT	Local Co-ordinate Reference:	Well CC 697-10-42B - Slot R
Project:	Garfield County, CO NAD27	TVD Reference:	GL 8348' & RKB 30' @ 8378.00ft
Site:	Cascade Creek 697-15-01 Pad	MD Reference:	GL 8348' & RKB 30' @ 8378.00ft
Well:	CC 697-10-42B	North Reference:	True
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	Rockies-R5000.1

Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
4,867.00	17.59	10.25	4,679.30	1,226.08	193.02	1,241.15	0.55	-0.55	0.09	
4,961.00	16.36	8.14	4,769.21	1,253.16	197.42	1,268.59	1.46	-1.31	-2.24	
5,055.00	17.67	9.55	4,859.09	1,280.34	201.66	1,296.09	1.46	1.39	1.50	
5,150.00	18.82	8.67	4,949.31	1,309.70	206.37	1,325.83	1.24	1.21	-0.93	
5,245.00	16.36	7.88	5,039.87	1,338.11	210.51	1,354.54	2.60	-2.59	-0.83	
5,339.00	17.67	10.34	5,129.75	1,365.26	214.89	1,382.03	1.59	1.39	2.62	
5,434.00	16.27	10.07	5,220.61	1,392.55	219.80	1,409.75	1.48	-1.47	-0.28	
5,528.00	15.04	10.51	5,311.12	1,417.50	224.33	1,435.10	1.31	-1.31	0.47	
5,623.00	14.25	9.11	5,403.04	1,441.17	228.43	1,459.11	0.91	-0.83	-1.47	
5,717.00	13.54	6.91	5,494.29	1,463.52	231.58	1,481.68	0.94	-0.76	-2.34	
5,811.00	14.16	10.07	5,585.55	1,485.76	234.92	1,504.18	1.04	0.66	3.36	
5,906.00	13.81	9.55	5,677.74	1,508.38	238.83	1,527.13	0.39	-0.37	-0.55	
6,000.00	12.66	9.98	5,769.24	1,529.59	242.48	1,548.64	1.23	-1.22	0.46	
6,095.00	11.70	9.81	5,862.10	1,549.34	245.92	1,568.68	1.01	-1.01	-0.18	
6,190.00	10.38	9.37	5,955.34	1,567.27	248.96	1,586.87	1.39	-1.39	-0.46	
6,284.00	9.50	7.70	6,047.93	1,583.32	251.38	1,603.09	0.99	-0.94	-1.78	
6,379.00	10.73	8.84	6,141.45	1,599.82	253.79	1,619.78	1.31	1.29	1.20	
6,473.00	9.85	12.80	6,233.94	1,616.31	256.91	1,636.55	1.20	-0.94	4.21	
6,568.00	8.53	12.01	6,327.72	1,631.13	260.18	1,651.68	1.40	-1.39	-0.83	
6,663.00	8.71	12.27	6,421.64	1,645.05	263.17	1,665.89	0.19	0.19	0.27	
6,757.00	9.50	11.57	6,514.46	1,659.60	266.24	1,680.74	0.85	0.84	-0.74	
6,852.00	7.74	11.48	6,608.38	1,673.55	269.09	1,694.96	1.85	-1.85	-0.09	
6,946.00	8.18	9.55	6,701.48	1,686.35	271.46	1,707.97	0.55	0.47	-2.05	
7,041.00	10.55	10.95	6,795.20	1,701.56	274.23	1,723.42	2.51	2.49	1.47	
7,135.00	9.32	9.90	6,887.79	1,717.50	277.17	1,739.63	1.32	-1.31	-1.12	
7,230.00	8.79	8.23	6,981.61	1,732.27	279.54	1,754.58	0.62	-0.56	-1.76	
7,324.00	7.47	5.68	7,074.66	1,745.46	281.17	1,767.86	1.46	-1.40	-2.71	
7,419.00	6.95	5.85	7,168.91	1,757.32	282.37	1,779.77	0.55	-0.55	0.18	
7,513.00	6.60	11.57	7,262.25	1,768.27	284.03	1,790.85	0.81	-0.37	6.09	
7,608.00	7.83	12.62	7,356.50	1,779.93	286.54	1,802.75	1.30	1.29	1.11	
7,703.00	8.88	5.15	7,450.49	1,793.55	288.61	1,816.53	1.59	1.11	-7.86	
7,797.00	7.65	2.25	7,543.52	1,807.03	289.51	1,829.99	1.38	-1.31	-3.09	
7,892.00	8.62	8.49	7,637.56	1,820.39	290.81	1,843.40	1.38	1.02	6.57	
7,986.00	8.88	7.52	7,730.47	1,834.55	292.80	1,857.69	0.32	0.28	-1.03	
8,081.00	7.65	4.36	7,824.48	1,848.12	294.24	1,871.33	1.38	-1.29	-3.33	
8,175.00	6.60	0.32	7,917.75	1,859.77	294.74	1,882.92	1.24	-1.12	-4.30	
8,270.00	6.33	4.01	8,012.15	1,870.45	295.14	1,893.54	0.52	-0.28	3.88	
8,364.00	6.86	9.46	8,105.53	1,881.16	296.42	1,904.32	0.87	0.56	5.80	
8,459.00	5.89	9.81	8,199.94	1,891.56	298.19	1,914.87	1.02	-1.02	0.37	
8,553.00	4.04	16.14	8,293.58	1,899.49	299.93	1,922.97	2.05	-1.97	6.73	
8,648.00	3.69	20.18	8,388.37	1,905.57	301.91	1,929.28	0.47	-0.37	4.25	
8,743.00	2.81	7.52	8,483.21	1,910.75	303.27	1,934.61	1.19	-0.93	-13.33	
8,837.00	1.41	352.58	8,577.15	1,914.18	303.43	1,938.02	1.59	-1.49	-15.89	
8,932.00	0.70	287.63	8,672.13	1,915.52	302.72	1,939.24	1.35	-0.75	-68.37	

Scientific Drilling International

Survey Report

Company:	OXY USA RMAT	Local Co-ordinate Reference:	Well CC 697-10-42B - Slot R
Project:	Garfield County, CO NAD27	TVD Reference:	GL 8348' & RKB 30' @ 8378.00ft
Site:	Cascade Creek 697-15-01 Pad	MD Reference:	GL 8348' & RKB 30' @ 8378.00ft
Well:	CC 697-10-42B	North Reference:	True
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	Rockies-R5000.1

Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
9,026.00	1.14	225.67	8,766.12	1,915.04	301.51	1,938.58	1.08	0.47	-65.91	
9,121.00	2.20	223.38	8,861.08	1,913.05	299.58	1,936.33	1.12	1.12	-2.41	
9,147.00	2.37	220.48	8,887.06	1,912.28	298.89	1,935.47	0.79	0.65	-11.15	
Last SDI Production MWD Survey										
9,204.00	2.37	220.48	8,944.01	1,910.49	297.36	1,933.47	0.00	0.00	0.00	
Projection To TD - BHL = 631089.95, 1235360.28										

Design Annotations					
Measured Depth (ft)	Vertical Depth (ft)	Local Coordinates			
		+N/-S (ft)	+E/-W (ft)	Comment	
248.00	247.96	3.81	-0.15	First SDI MWD Survey	
2,660.00	2,589.91	527.34	79.36	Last Survey in 14 3/4" Hole	
2,787.00	2,710.35	567.40	83.80	First SDI Production MWD Survey	
9,147.00	8,887.06	1,912.28	298.89	Last SDI Production MWD Survey	
9,204.00	8,944.01	1,910.49	297.36	Projection To TD	
9,204.00	8,944.01	1,910.49	297.36	BHL = 631089.95, 1235360.28	

Checked By: _____ Approved By: _____ Date: _____