

FORM 2 Rev 12/05	State of Colorado Oil and Gas Conservation Commission 1120 Lincoln Street, Suite 801, Denver, Colorado 80205 Phone: (303) 894-2100 Fax: (303) 894-2109		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:25%;">DE</td> <td style="width:25%;">ET</td> <td style="width:25%;">OE</td> <td style="width:25%;">ES</td> </tr> </table>	DE	ET	OE	ES
DE	ET	OE	ES				

APPLICATION FOR PERMIT TO:

1. **Drill,** Deepen, Re-enter, Recomplete and Operate

2. TYPE OF WELL

OIL GAS COALBED OTHER _____
 SINGLE ZONE MULTIPLE ZONE COMMINGLE ZONE

Refiling
 Sidetrack

Document Number:

400139759

Plugging Bond Surety

20030009

3. Name of Operator: <u>NOBLE ENERGY INC</u>	4. COGCC Operator Number: <u>100322</u>
5. Address: <u>1625 BROADWAY STE 2200</u>	
City: <u>DENVER</u> State: <u>CO</u> Zip: <u>80202</u>	
6. Contact Name: <u>MARI CLARK</u> Phone: <u>(303)228-4413</u> Fax: <u>(303)228-4286</u>	
Email: <u>mclark@nobleenergyinc.com</u>	
7. Well Name: <u>ROMERO PC G</u>	Well Number: <u>10-79HN</u>
8. Unit Name (if appl): _____	Unit Number: _____
9. Proposed Total Measured Depth: <u>13010</u>	

WELL LOCATION INFORMATION

10. QtrQtr: SWNW Sec: 3 Twp: 4N Rng: 65W Meridian: 6
 Latitude: 40.342360 Longitude: -104.657750

Footage at Surface: <u>2235</u> feet	FNL/FSL <u>FNL</u> <u>273</u> feet	FEL/FWL <u>FWL</u>
--------------------------------------	---------------------------------------	-----------------------

11. Field Name: WATTENBERG Field Number: 90750
 12. Ground Elevation: 4670 13. County: WELD

14. GPS Data:
 Date of Measurement: 02/18/2011 PDOP Reading: 1.5 Instrument Operator's Name: BRIAN BRINKMAN

15. If well is Directional Horizontal (highly deviated) **submit deviated drilling plan.**

Footage at Top of Prod Zone: FNL/FSL	FEL/FWL	Bottom Hole: FNL/FSL	FEL/FWL
<u>2889</u> <u>FNL</u> <u>263</u> <u>FWL</u>	<u>1855</u> <u>FSL</u> <u>75</u> <u>FWL</u>		
Sec: <u>3</u> Twp: <u>4N</u> Rng: <u>65W</u>	Sec: <u>10</u> Twp: <u>4N</u> Rng: <u>65W</u>		

16. Is location in a high density area? (Rule 603b)? Yes No
 17. Distance to the nearest building, public road, above ground utility or railroad: 277 ft
 18. Distance to nearest property line: 273 ft 19. Distance to nearest well permitted/completed in the same formation: 427 ft

20. **LEASE, SPACING AND POOLING INFORMATION**

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
NIOBRARA	NBRR	407-87	480	GWA

IMPORTANT: SOME DATA FIELDS HAVE BEEN MODIFIED.

21. Mineral Ownership: Fee State Federal Indian Lease #: _____
22. Surface Ownership: Fee State Federal Indian
23. Is the Surface Owner also the Mineral Owner? Yes No Surface Surety ID#: _____
23a. If 23 is Yes: Is the Surface Owner(s) signature on the lease? Yes No
23b. If 23 is No: Surface Owners Agreement Attached or \$25,000 Blanket Surface Bond \$2,000 Surface Bond \$5,000 Surface Bond
24. Using standard QtrQtr, Sec, Twp, Rng format enter entire mineral lease description upon which this proposed wellsite is located (attach separate sheet/map if you prefer):
SEE ATTACHED MAP
25. Distance to Nearest Mineral Lease Line: 1245 ft 26. Total Acres in Lease: 3115

DRILLING PLANS AND PROCEDURES

27. Is H2S anticipated? Yes No If Yes, attach contingency plan.
28. Will salt sections be encountered during drilling? Yes No
29. Will salt (>15,000 ppm TDS CL) or oil based muds be used during drilling? Yes No
30. If questions 28 or 29 are yes, is this location in a sensitive area (Rule 901.e)? Yes No
31. Mud disposal: Offsite Onsite **If 28, 29, or 30 are "Yes" a pit permit may be required.**
Method: Land Farming Land Spreading Disposal Facility Other: _____
Note: The use of an earthen pit for Recompletion fluids requires a pit permit (Rule 905b). If air/gas drilling, notify local fire officials.

Casing Type	Size of Hole	Size of Casing	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
CONDUCTOR	18+1/2	16+0/0		0	100	6	100	0
SURF	12+1/4	9+5/8	36	0	650	205	650	0
1ST	8+3/4	7+0/0	26	0	7,264	645	7,264	
1ST LINER	6+1/8	4+1/2	11.6	6051	13,010			

32. BOP Equipment Type: Annular Preventer Double Ram Rotating Head None
33. Comments 1ST STRING TOP OF CEMENT = 200' ABOVE NIOBRARA. THE PRODUCTION LINER WILL BE HUNG OFF INSIDE 7" CASING. THE PRODUCTION FACILITIES WILL BE LOCATED ON THE SAME LOCATION & DEDICATED TO THE WELL LOCATION BEING PERMITTED. NOBLE ENERGY INC. CERTIFIES THAT THE LEASES SHALL BE COMMITTED TO THE UNIT. UNIT CONFIGURATION = Sec. 3: SW/4NW/4, W/2SW/4, Sec. 4: SE/4NE/4, E/2SE/4, Sec. 9: E2NE/4, NE/4SE/4, Sec. 10: W/2NW/4, NW/4SW/4. Noble requests approval of a Rule 318Aa and Rule 318Ac exception location: Wellhead is to be located outside of a GWA drilling window and will be located more than 50' from an existing well location. Waivers attached.

34. Location ID: _____
35. Is this application in a Comprehensive Drilling Plan ? Yes No
36. Is this application part of submitted Oil and Gas Location Assessment ? Yes No
I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.
Signed: _____ Print Name: MARI CLARK
Title: REG. ANALYST II Date: 6/28/2011 Email: mclark@nobleenergyinc.com

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: David S. Neslin Director of COGCC Date: 7/23/2011

API NUMBER

05 123 34018 00

Permit Number: _____ Expiration Date: 7/22/2013

CONDITIONS OF APPROVAL, IF ANY:

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

- 1) Provide 24 hour notice of MIRU to Bo Brown via e-mail at bo.brown@state.co.us.
- 2) Comply with Rule 317.i and provide cement coverage from the end of the production casing to a minimum of 200' above the Niobrara and from 200' below Sussex to 200' above Sussex. Verify coverage with cement bond log.
- 3) Comply with Rule 321. Run and submit Directional Survey from the end of production casing to base of surface casing. Ensure that the wellbore complies with setback requirements in commission orders or rules prior to producing the well.

Attachment Check List

Att Doc Num	Name
400139759	FORM 2 SUBMITTED
400179698	WELL LOCATION PLAT
400179699	30 DAY NOTICE LETTER
400179702	DEVIATED DRILLING PLAN
400179712	EXCEPTION LOC REQUEST
400179718	EXCEPTION LOC WAIVERS
400179719	PROPOSED SPACING UNIT
400180195	LEGAL/LEASE DESCRIPTION

Total Attach: 8 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Lease description comment box references "attached map", but no lease map is attached. NKP 6/29/2011 Map has been attached. NKP	6/29/2011 10:39:43 AM

Total: 1 comment(s)

BMP

<u>Type</u>	<u>Comment</u>
General Housekeeping	Housekeeping will consist of neat and orderly storage of materials and fluids. Wastes will be temporarily stored in sealed containers and regularly collected and disposed of at offsite, suitable facilities. If spills occur prompt cleanup is required to minimize any commingling of waste materials with stormwater runoff. Routine maintenance will be limited to fueling and lubrication of equipment. Drip pans will be used during routine fueling and maintenance to contain spills or leaks. Any waste product from maintenance will be containerized and transported offsite for disposal or recycling. There will be no major equipment overhauls conducted onsite. Equipment will be transported offsite for major overhauls. Cleanup of trash and discarded materials will be conducted at the end of each work day. Cleanup will consist of patrolling the roadway, access areas, and other work areas to pickup trash, scrap debris, other discarded materials, and any contaminated soil. These materials will be disposed of properly.
Material Handling and Spill Prevention	Spill Prevention Control and Countermeasures (SPCC) plans are in place to address any possible spill associated with Oil & Gas operations throughout the state of Colorado in accordance with CFR 112.
Storm Water/Erosion Control	Stormwater management plans (SWMP) are in place to address construction, drilling and operations associated with Oil & Gas development throughout the state of Colorado in accordance with Colorado Department of Public Health and Environment (CDPHE) General Permit No. COR-039527. BMP's will be constructed around the perimeter of the site prior to, or at the beginning of construction. BMP's used will vary according to the location, and will remain in place until the pad reaches final reclamation.

Total: 3 comment(s)