Schlumberger
Company: CHEVRON U.S.A. INC.
Well: LOS CORRALITOS 17 COM 1H
Field: WILDCAT
County: EDDY
State: NEW MEXICO
Location: 1,980' FSL & 330' FWL
Sec 17 Twp 17S Rge 28E
Other Services: DSN/SDL/HNGS/MAC
Permanent Datum: GROUND LEVEL
Elevation: 3,600'
Log Measured From: KELLY BUSHING
Drilling Measured From: KELLY BUSHING
API #: 30-015-45911
Date: 10-Jul-2019
Run No: ONE
Depth Driller: 12,000'
Depth Logger: 12,000'
Bottom Log Interval: 12,000'
Top Log Interval: 9,900'
Casing Driller: 9.625" @ 1,000'
Casing Logger: 9.625" @ 1,000'
Bit Size: 8.75"
Type Fluid in Hole: OIL BASED MUD
Density: 9.6 PPG
Viscosity: 50 S
Fluid Loss: 4.8 CC
Source of Sample: FLOWLINE
Rm @ Meas Temp: 0.1 @ 150°F
Rmf @ Meas Temp: 0.08 @ 150°F
Rmc @ Meas Temp: 0.12 @ 150°F
Source of Rmf/Rmc: CALC
Rm @ BHT: 0.06 @ 180°F
Time Since Circ: 12 HRS
Max Rec Temp: 180°F
Equip. Location: HOBBS, NM
Recorded By: J. SMITH
Witnessed By: M. JONES
Run Number


5600
5700
5800
5900
6000
6100
6200
6300
6400
6500
Marker Joint
6600
6700
Marker Joint
6800
6900
Amplified Amplitude
Gamma Ray
Amplitude
CCL
Variable Density
Gamma Ray (GAPI)
180
CCL
2.25
1.60
0
Amplified Amplitude (mV)
Amplitude (mV)
30.200
85
Variable Density
1200