
Schlumberger
Platform Express
Three-Detector Lithology Density
Compensated Neutron
Array Induction Imager Tool
Gamma Ray
Caliper
Bit Size
Density Correction
Neutron Porosity
Photoelectric Factor
Deep Resistivity
Medium Resistivity
Shallow Resistivity
Spherically Focused Resistivity
Rt
Rxo
Rm
Rmf
Rmc
Mud Type
Mud Density
Mud Resistivity
Mud Filtrate Resistivity
Mud Cake Resistivity
Source of Sample
Rm @ BHT
Rmf @ BHT
Rmc @ BHT
Time Since Circulation
Max Recorded Temperature
Equipment Number
Location
Recorded By
Witnessed By
Run Number
Depth Driller
Depth Logger
Bottom Logged Interval
Top Logged Interval
Casing Driller
Casing Logger
Bit Size
Type Fluid in Hole
Density
Viscosity
pH
Fluid Loss
Source of Sample
Rm @ Measured Temperature
Rmf @ Measured Temperature
Rmc @ Measured Temperature



Calibration Report

Database File: antelope 42-31_old.db
Dataset Pathname: pass2
Dataset Creation: Tue Jun 14 11:02:06 2011 by Log Std Casedhole 10121

Gamma Ray Calibration Report

Serial Number:	576	
Tool Model:	1.69TEKCO	
Performed:	Sun Jun 13 13:33:21 1993	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	1.0000	GAPI/cps

Cement Bond Log Calibration Report

Serial Number:	1	
Tool Model:	1.5hscr169	
Performed:	Tue Jun 14 10:49:23 2011	
Depth:	2188.09	ft
Casing Diameter:	4.5	in
	3' Spacing	5' Spacing
Signal Zero:	3	0 mV
Calibrated Amplitude:	81.1961	81.1961 mV
Reading at Signal Zero:	0.03	0.03 V
Reading in Free Pipe:	1.18293	1.55227 V
Gain:	67.8235	53.3388
Offset:	0.965294	-1.60016