

# Sunburst Inc.

## SURFACE CASING REPORT

Vader 33-15

SWSE SEC. 33 5N 68W

I-25 north to Johnstown exit, 1 west to deadend, 1 north, 1/2 west, north to location

11-Sep-10			1	35.40	21
PERMIT DEPTH	550		2	40.85	22
DRILLED TO	593		3	43.13	23
JTS ON RACK	14	563.91	4	41.95	24
JTS RUN	14	563.91	5	37.86	25
LANDED AT		580.71	6	41.90	26
JTS OUT	0	0.00	7	40.25	27
			8	42.10	28
			9	39.78	29
			10	41.10	30
			11	39.93	31
			12	39.98	32
			13	40.66	33
			14	39.02	34
			15		35
			16		36
			17		37
			18		38
			19		39
			20		40

0.80 SHOE  
16 KB

TIME BREAK DOWN				
TD ON SURFACE 9-11-10	7:30		PLUG DOWN	17:00
CIRCULATE	7:30	-	8:15	7 BBLS CEMENT TO SURFACE
WIPER TRIP	8:15	-	12:00	
CIRCULATE	12:00	-	13:15	
TOH	13:15		14:00	
RIG UP CASERS & S.M	14:00	-		
RUN CASING			15:15	
CIRCULATE	15:15		16:15	
CEMENT	16:15		17:00	

## CEMENT REPORT

Cementers pumped 15 bbls water pre-flush.

Then mixed and pumped 410 sks neat cmt w/ 3% CaCl and 0.125 lbs/sk floccel mixed at 15.2 PPG, Yield 1.18cu/ft/sk

Displace w/ 34 bbls water, bumped plug to 600 PSI. 7 BBLS. cement returns