

FORM
6Rev
12/05State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80205 Phone: (303) 894-2100 Fax: (303) 894-2109



DE ET OE ES

Date Received:

07/01/2011

Document Number:

2587192

WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set.

A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

OGCC Operator Number: 10148

Contact Name: BRETT WISNER

Name of Operator: KLABZUBA OIL & GAS INC

Phone: (303) 382-2170

Address: 930 WEST 1ST ST 4TH FLR

Fax: (303) 299-9087

City: FT WORTH State: TX Zip: 76102

Email: BWISNER@KLABZUBA.COM

For "Intent" 24 hour notice required,

Name: Tel:

COGCC contact:

Email:

API Number 05-087-05230-00

Well Name: CLAR

Well Number: 6

Location: QtrQtr: NWNW Section: 24 Township: 1N Range: 58W Meridian: 6

County: MORGAN

Federal, Indian or State Lease Number:

Field Name: ADENA

Field Number: 700

☐ Notice of Intent to Abandon☒ Subsequent Report of Abandonment

Only Complete the Following Background Information for Intent to Abandon

Latitude: 40.041710

Longitude: -103.826610

GPS Data:

Data of Measurement: 09/06/2011

PDOP Reading: 2.1

GPS Instrument Operator's Name: JEFF POZVEK

Reason for Abandonment: ☐ Dry ☐ Production for Sub-economic ☐ Mechanical Problems☐ OtherCasing to be pulled: ☐ Yes ☐ No Top of Casing Cement:Fish in Hole: ☐ Yes ☐ No If yes, explain details belowWellbore has Uncemented Casing leaks: ☐ Yes ☐ No If yes, explain details below

Details:

Current and Previously Abandoned Zones

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth
J SAND	5692	5712			

Total: 1 zone(s)

Casing History

Casing Type	Size of Hole	Size of Casing	Weight Per Foot	Setting Depth	Sacks Cement	Cement Bot	Cement Top	Status
SURF		8+5/8	24	95	90	95	0	
1ST		5+1/2	15.5	5,795	150	5,795	4,836	CBL

Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth 5290 with 2 sacks cmt on top. CIPB #2: Depth _____ with _____ sacks cmt on top.
CIBP #3: Depth _____ with _____ sacks cmt on top. CIPB #4: Depth _____ with _____ sacks cmt on top.
CIBP #5: Depth _____ with _____ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐
Set _____ sks cmt from _____ ft. to _____ ft. Plug Type: _____ Plug Tagged: ☐

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

(Cast Iron Cement Retainer Depth)

Set 65 sacks half in. half out surface casing from 211 ft. to 4 ft. Plug Tagged: ☐

Set _____ sacks at surface

Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: ☐ Yes ☒ No

Set _____ sacks in rat hole Set _____ sacks in mouse hole

Additional Plugging Information for Subsequent Report Only

Casing Recovered: 211 ft. of 5+1/2 inch casing

Plugging Date: 11/10/2010

*Wireline Contractor: J-W WIRELINE COMPANY

*Cementing Contractor: HALLIBURTON

Type of Cement and Additives Used: CLASS G, 94 LB SK (15.8 LBM/GAL)

Flowline/Pipeline has been abandoned per Rule 1103 ☐ Yes ☐ No

*ATTACH JOB SUMMARY

Technical Detail/Comments:

CBL RAN, SEE ATTACHED COPY FOR TOC.
ATTACHMENTS:
1. CEMENT BOND LOG
2. J-W WIRELINE DOWNHOLE PLUGGING TICKET
3. HALIBURTON SURFACE PLUGGING TICKET
4. WELLBORE DIAGRAM

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: MIKE COLLOM
Title: ENG MGR Date: 6/30/2011 Email: MCOLLOM@KLABZUBA.COM

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: SUTPHIN, DIRK Date: 9/8/2011

CONDITIONS OF APPROVAL, IF ANY:

Attachment Check List

Att Doc Num	Name
2587192	FORM 6 SUBSEQUENT SUBMITTED
2587193	CEMENT JOB SUMMARY
2587194	WELLBORE DIAGRAM
2587195	WIRELINE JOB SUMMARY

Total Attach: 4 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	REC AS DRILLED GPS	9/7/2011 3:48:14 PM
Permit	REQ AS DRILLED GPS INFO	8/24/2011 9:21:27 AM

Total: 2 comment(s)