PSI

HIGH RESOLUTION INDUCTION COMPENSATED SONIC

Company: Rosetta Crow Energy, Inc.
Well: Continent
Field: Wellenberg
Location: Sec. 27 T4 R6 W3M, NWNW, 1000' FNL & 660' FWL NWNW
Sec. 27 Tp. 4N Rge. 6W3M
Province: Alberta
Country: Canada

Permanent Datum: Ground Level
Elevation: 1107 m
Log Measured From: KB
Drilling Measured From: KB
Elevation: KB 1107 m, GL 1104 m

Date: Aug 27, 2021
Run Number: ONE
Depth Driller: 3450 m
Depth Logger: 3450 m
Bottom Logged Interval: 3450 m
Top Logged Interval: 2000 m
Casing Driller: 244.5 mm @ 2000 m
Casing Logger: 244.5 mm @ 2000 m
Bit Size: 222 mm
Type Fluid in Hole: Water Based Mud
Density: 1.10 kg/m3
Viscosity: 50 s
Fluid Loss: 10 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.2 @ 20 °C
Rmf @ Measured Temp: 0.15 @ 20 °C
Rmc @ Measured Temp: 0.3 @ 20 °C
Source of Rmf and Rmc: Measured
Rm @ BHT: 0.1 @ 80 °C
Time Since Circulation: 12 hrs
Time on Bottom: 08:00 Aug 27
Max Recorded Temp: 80 °C
Equipment Number: 1
Location: Grande Prairie
Recorded By: Jeff Hall
Witnessed By: Mr. Rosetta Crow Rep

All interpretations are opinions based on inferences from electrical or other measurements and we cannot warrant or not guarantee the accuracy or correctness of any interpretation, and we shall not be liable for any loss or damage occurred in connection with the interpretations. We shall not be liable, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions as set out in our current price schedule.

Annular volume calculated for 4 1/2" casing
Mid. Continent
Thank you for using Pason Surveys!
API # 05-123-34042-00

Database File: 11427.db
Dataset Pathname: Well
Presentation Format: Sat Aug 27 17:36:37 2021
Dataset Creation: Created by:
Charted by: Depth in Feet scaled 1:240

Gamma Ray (GAPI) 0 150
SP (mV) -150 150
Density Porosity (pu) 45 -15
Neutron Porosity (pu) 45 -15
Deep Resistivity (Ohm-m) .2 2000
Medium Resistivity (Ohm-m) .2 2000
Shallow Resistivity (Ohm-m) .2 2000
Rt (Ohm-m) .2 2000

Caliper (in) 16 6
Gamma Ray (GAPI) 0 150
SP (mV) -150 150
Density Caliper (in) 16 6
Gamma Ray (GAPI) 0 150
SP (mV) -150 150
HSNVI (PU) 45 -15

Deep Resistivity
Logarithmic TO: 1000

Neutron Porosity
Linear TO: 0

Density Porosity
Linear TO: 0

Gamma Ray
Linear TO: 200

Caliper
Linear TO: 16

Shallow Resistivity
Logarithmic TO: 1000

Medium Resistivity
Logarithmic TO: 1000

Density Porosity
Linear FROM: 0.45
Linear TO: -0.15

Neutron Porosity
Linear FROM: 0.45
Linear TO: -0.15

Gamma Ray
Linear FROM: 0
Linear TO: 150

SP
Linear FROM: -150
Linear TO: 150

Caliper
Linear FROM: 16
Linear TO: 6

Shallow Resistivity
Logarithmic FROM: 0.2
Logarithmic TO: 2000

Medium Resistivity
Logarithmic FROM: 0.2
Logarithmic TO: 2000

Deep Resistivity
Logarithmic FROM: 0.2
Logarithmic TO: 2