

Well: Scheller 10-8-66 1H
Zone of Interest: Niobrara Shale

1.0) Summary of Operations

Drill 12-1/4" surface hole to section TD at 1300'.

Set 9-5/8" 40# J-55 casing and cement with Lead and Tail cement (see details below). Cement will be circulated to surface.

Install 11" x 5,000 psi BOP and test as required

Drill 8-3/4" hole to KOP.

Kick off and drill 8-3/4" curve at 10 deg/100' to end of build.

Drill 7-7/8" open hole to well TD

Acquire shuttle logs: Triple combo and image logs in open hole

Set 4-1/2" x 5-1/2" casing and cement as shown below.

Suspend well and move drilling rig out in preparation for well completion

2.0 CASING AND CEMENTING PROGRAM

The proposed casing program will be as follows:

<u>Purpose</u>	<u>Interval</u>		<u>Hole Size</u>	<u>Casing Size</u>	<u>Weight</u>	<u>Grade</u>	<u>Thread</u>	<u>Condition</u>
	<u>From</u>	<u>To</u>	<u>(")</u>	<u>(")</u>	<u>Lbs/Ft</u>			
Surface	0	1300	12 1/4	9 5/8	40	J-55	LTC	New
Production	0	6876	8 3/4	5 1/2	17	P-110	LTC	New
	6876	11506	8 3/4	4 1/2	11.6	P-110	LTC	New

Casing design subject to revision based on geologic conditions encountered.

Casing Safety Factors:

Interval	Casing	Burst	Collapse	Axial
Surface	9 5/8	2.03	2.03	4.78
Production	4 1/2	1.32	2.26	1.63

Centralizer Program

Casing	9 5/8		4 1/2
# of Bow-type spring centralizer	11		26

Cement Program

Surface Casing	Slurry Volume			Weight	Yield	Mix H2O	TOC
	% Excess	(BBLS)	(Sacks)	(PPG)	(cuft/sk)	(GPS)	
Lead Slurry	100%	109	207	11.50	2.95	17.88	0
Tail Slurry	100%	42	204	15.80	1.15	4.96	975

	Lead	Tail
Surface Casing with TOC at surface	Rockies LT 0.2 % Versaset (Additive Material) 0.2 % D-AIR 3000 (Additive Material) 0.125 lbm/sk Poly-E-Flake (Additive Material) 0.25 lbm/sk Kwik Seal (Additive Material)	Premium Cement, 94 lbm/sk Premium Cement (Cement) 1 % Calcium Chloride, Pellet (Accelerator) 0.125 lbm/sk Poly-E-Flake (Lost Circulation Additive)

Cement must be circulated to surface

Production Casing Cement	Slurry Volume			Weight	Yield	Mix H2O	TOC
	% Excess	(BBLS)	(Sacks)	(PPG)	(cuft/sk)	(GPS)	
Lead Slurry	30%	162	415	12.00	2.20	12.30	3598'
Tail Slurry	30%	291	1121	14.60	1.46	6.10	

	Lead	Tail
Production Casing Cement	Poz Type I-II 50/50 1 % Bentonite (Light Weight Additive) 3 lbm/sk Silicalite Compacted (Additive Material) 3 % Microbond HT (Additive Material) 0.2 % Halad(R)-322 (Low Fluid Loss Control) 0.4 % Halad(R)-344 (Low Fluid Loss Control) 0.3 % HR-5 (Retarder)	50/50 Poz Premium 2 % Bentonite (Light Weight Additive) 5 lbm/sk Silicalite Compacted (Light Weight Additive) 0.5 % Versaset (Thixotropic Additive) 0.5 % Econolite (Cement Material) 0.6 % HR-7 (Retarder) 0.5 % D-AIR 3000 (Defoamer) 0.125 lbm/sk Poly-E-Flake (Lost Circulation Additive) 0.25 lbm/sk Kwik Seal (Lost Circulation Additive)

The cement must achieve a compressive strength of at least 500 psi at the shoe prior to casing test and drilling out the shoe track. WOC time shall be recorded in the driller's log.

MUD PROGRAM

<u>Purpose</u>	<u>Interval</u>		<u>Hole Size</u>	<u>Mud Type</u>	<u>Mud Weight</u>	<u>Viscosity</u>	<u>Fluid Loss</u>	<u>pH</u>
	<u>From</u>	<u>To</u>	(")	(")	<u>Lbs/Ft</u>			
Surface	0'	1300'	12 1/4	WBM	8.4 – 8.8	28 – 32	N/C	9
Production	1300'	7771'	8 3/4	WBM	8.5 – 9.5	35 – 46	4 – 6	9
	7771'	11506'	7 7/8	WBM	9.0 - 10.0	36 – 46	4 – 6	9

WBM = Water Based Mud