



EOG Resources

Weld Co., CO

Sec 22-T5N-R62W

Windmill #04-22H

Hz

Survey: Survey #2

Standard Survey Report

14 May, 2011



Company:	EOG Resources	Local Co-ordinate Reference:	Well Windmill #04-22H
Project:	Weld Co., CO	TVD Reference:	Windmill 4-22H KBE @ 4612.0ft (True 30)
Site:	Sec 22-T5N-R62W	MD Reference:	Windmill 4-22H KBE @ 4612.0ft (True 30)
Well:	Windmill #04-22H	North Reference:	True
Wellbore:	Hz	Survey Calculation Method:	Minimum Curvature
Design:	Hz	Database:	Local

Project	Weld Co., CO		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	Colorado North 501		

Site	Sec 22-T5N-R62W		
Site Position:		Northing:	
From:	Lat/Long	Easting:	
Position Uncertainty:	0.0 ft	Slot Radius:	
		Latitude:	
		Longitude:	
		Grid Convergence:	1.00

Well	Windmill #04-22H				
Well Position	+N/-S	0.0 ft	Northing:	383,354.49 ft	Latitude: 40° 22' 46.320 N
	+E/-W	0.0 ft	Easting:	2,333,928.17 ft	Longitude: 104° 18' 4.960 W
Position Uncertainty	0.0 ft		Wellhead Elevation:	ft	Ground Level: 4,587.0 ft

Wellbore	Hz				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010-14	04/20/11	8 63	67.11	53,187

Design	Hz				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (ft)	+N/-S (ft)	+E/-W (ft)	Direction (°)	
	0.0	0.0	0.0	334.06	

Survey Program	Date	05/14/11			
From (ft)	To (ft)	Survey (Wellbore)	Tool Name	Description	
837.0	10,669.0	Survey #2 (Hz)	MWD		

Survey											
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	Subsea Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
0.0	0.00	0.00	0.0	-4,612.0	0.0	0.0	0.0	0.00	0.00	0.00	
837.0	0.00	0.00	837.0	-3,775.0	0.0	0.0	0.0	0.00	0.00	0.00	
1,073.0	0.18	173.16	1,073.0	-3,539.0	-0.4	0.0	-0.4	0.08	0.08	0.00	
1,346.0	0.22	133.26	1,346.0	-3,266.0	-1.2	0.5	-1.2	0.05	0.01	-14.62	
1,621.0	0.35	228.97	1,621.0	-2,991.0	-2.1	0.2	-2.0	0.16	0.05	34.80	
1,895.0	0.53	275.91	1,895.0	-2,717.0	-2.5	-1.7	-1.5	0.14	0.07	17.13	
2,182.0	0.92	289.18	2,182.0	-2,430.0	-1.6	-5.2	0.8	0.15	0.14	4.62	
2,472.0	0.66	259.12	2,471.9	-2,140.1	-1.1	-9.0	2.9	0.17	-0.09	-10.37	
2,761.0	0.57	306.67	2,760.9	-1,851.1	-0.6	-11.8	4.6	0.17	-0.03	16.45	
3,049.0	0.26	81.05	3,048.9	-1,563.1	0.4	-12.3	5.7	0.27	-0.11	46.66	

Company:	EOG Resources	Local Co-ordinate Reference:	Well Windmill #04-22H
Project:	Weld Co., CO	TVD Reference:	Windmill 4-22H KBE @ 4612.0ft (True 30)
Site:	Sec 22-T5N-R62W	MD Reference:	Windmill 4-22H KBE @ 4612.0ft (True 30)
Well:	Windmill #04-22H	North Reference:	True
Wellbore:	Hz	Survey Calculation Method:	Minimum Curvature
Design:	Hz	Database:	Local

Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	Subsea Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
3,335.0	0.79	223.70	3,334.9	-1,277.1	-1.0	-13.0	4.8	0.35	0.19	49.88
3,622.0	0.22	136.69	3,621.9	-990.1	-2.8	-14.0	3.6	0.28	-0.20	-30.32
3,909.0	0.88	346.31	3,908.9	-703.1	-1.1	-14.1	5.2	0.38	0.23	-52.40
4,199.0	2.99	337.43	4,198.7	-413.3	8.1	-17.6	15.0	0.73	0.73	-3.06
4,262.0	2.99	336.46	4,261.6	-350.4	11.1	-18.9	18.2	0.08	0.00	-1.54
4,327.0	2.90	334.97	4,326.5	-285.5	14.2	-20.2	21.6	0.18	-0.14	-2.29
4,423.0	2.68	332.95	4,422.4	-189.6	18.4	-22.3	26.3	0.25	-0.23	-2.10
4,519.0	1.98	332.77	4,518.3	-93.7	21.8	-24.1	30.2	0.73	-0.73	-0.19
4,583.0	1.93	329.52	4,582.3	-29.7	23.7	-25.1	32.3	0.19	-0.08	-5.08
4,681.0	1.93	329.26	4,680.3	68.3	26.6	-26.8	35.6	0.01	0.00	-0.27
4,970.0	1.36	334.70	4,969.1	357.1	33.9	-30.7	43.9	0.20	-0.20	1.88
5,259.0	1.05	346.66	5,258.1	646.1	39.5	-32.8	49.9	0.14	-0.11	4.14
5,547.0	0.57	327.76	5,546.0	934.0	43.3	-34.2	53.9	0.19	-0.17	-6.56
5,721.0	0.44	318.62	5,720.0	1,108.0	44.6	-35.1	55.4	0.09	-0.07	-5.25
5,741.0	0.44	318.80	5,740.0	1,128.0	44.7	-35.2	55.6	0.01	0.00	0.90
5,773.0	1.85	333.91	5,772.0	1,160.0	45.2	-35.5	56.2	4.47	4.41	47.22
5,805.0	4.75	334.97	5,804.0	1,192.0	46.9	-36.3	58.0	9.06	9.06	3.31
5,837.0	8.31	334.35	5,835.8	1,223.8	50.2	-37.9	61.7	11.13	11.13	-1.94
5,870.0	12.04	333.47	5,868.2	1,256.2	55.4	-40.4	67.5	11.31	11.30	-2.67
5,902.0	15.56	333.74	5,899.3	1,287.3	62.3	-43.8	75.1	11.00	11.00	0.84
5,933.0	18.68	333.83	5,928.9	1,316.9	70.4	-47.9	84.3	10.06	10.06	0.29
5,965.0	21.63	333.30	5,959.0	1,347.0	80.3	-52.8	95.3	9.24	9.22	-1.66
5,997.0	24.75	333.12	5,988.4	1,376.4	91.6	-58.4	107.9	9.75	9.75	-0.56
6,029.0	28.40	333.65	6,017.0	1,405.0	104.4	-64.9	122.2	11.43	11.41	1.66
6,061.0	32.79	334.97	6,044.5	1,432.5	119.0	-71.9	138.5	13.88	13.72	4.13
6,094.0	37.27	334.97	6,071.5	1,459.5	136.2	-79.9	157.4	13.58	13.58	0.00
6,126.0	41.27	335.67	6,096.3	1,484.3	154.6	-88.4	177.7	12.58	12.50	2.19
6,158.0	43.25	336.20	6,120.0	1,508.0	174.2	-97.1	199.2	6.29	6.19	1.66
6,190.0	46.95	336.29	6,142.6	1,530.6	195.0	-106.3	221.8	11.56	11.56	0.28
6,222.0	50.95	336.46	6,163.6	1,551.6	217.1	-115.9	245.9	12.51	12.50	0.53
6,254.0	54.51	336.29	6,183.0	1,571.0	240.4	-126.1	271.4	11.13	11.13	-0.53
6,286.0	57.32	335.32	6,200.9	1,588.9	264.6	-137.0	297.9	9.13	8.78	-3.03
6,318.0	59.60	334.62	6,217.6	1,605.6	289.3	-148.5	325.1	7.36	7.13	-2.19
6,350.0	61.76	334.35	6,233.3	1,621.3	314.5	-160.6	353.0	6.79	6.75	-0.84
6,382.0	65.10	333.47	6,247.6	1,635.6	340.2	-173.1	381.6	10.72	10.44	-2.75
6,415.0	68.00	332.51	6,260.7	1,648.7	367.1	-186.9	411.9	9.18	8.79	-2.91
6,447.0	70.73	331.80	6,272.0	1,660.0	393.6	-200.9	441.8	8.78	8.53	-2.22
6,479.0	73.27	331.72	6,281.9	1,669.9	420.4	-215.3	472.2	7.94	7.94	-0.25
6,512.0	76.44	331.98	6,290.5	1,678.5	448.5	-230.3	504.1	9.64	9.61	0.79
6,544.0	80.88	332.51	6,296.8	1,684.8	476.3	-244.9	535.4	13.97	13.88	1.66
6,577.0	83.43	332.33	6,301.3	1,689.3	505.2	-260.0	568.1	7.75	7.73	-0.55
6,609.0	84.53	332.07	6,304.7	1,692.7	533.4	-274.9	599.9	3.53	3.44	-0.81
6,711.0	87.12	330.84	6,312.1	1,700.1	622.7	-323.5	701.5	2.81	2.54	-1.21

Company:	EOG Resources	Local Co-ordinate Reference:	Well Windmill #04-22H
Project:	Weld Co., CO	TVD Reference:	Windmill 4-22H KBE @ 4612.0ft (True 30)
Site:	Sec 22-T5N-R62W	MD Reference:	Windmill 4-22H KBE @ 4612.0ft (True 30)
Well:	Windmill #04-22H	North Reference:	True
Wellbore:	Hz	Survey Calculation Method:	Minimum Curvature
Design:	Hz	Database:	Local

Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	Subsea Depth (ft)	+N-S (ft)	+E-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
6,741.0	86.81	330.49	6,313.7	1,701.7	648.9	-338.2	731.4	1.56	-1.03	-1.17
6,772.0	86.24	330.22	6,315.6	1,703.6	675.8	-353.5	762.3	2.03	-1.84	-0.87
6,836.0	86.86	330.05	6,319.4	1,707.4	731.2	-385.3	826.0	1.00	0.97	-0.27
6,900.0	88.13	329.61	6,322.2	1,710.2	786.4	-417.4	889.8	2.10	1.98	-0.69
6,932.0	89.93	330.13	6,322.8	1,710.8	814.1	-433.5	921.7	5.85	5.63	1.63
6,996.0	90.37	329.78	6,322.6	1,710.6	869.5	-465.5	985.5	0.88	0.69	-0.55
7,060.0	89.93	329.52	6,322.4	1,710.4	924.7	-497.9	1,049.3	0.80	-0.69	-0.41
7,125.0	89.01	328.55	6,323.0	1,711.0	980.5	-531.3	1,114.1	2.06	-1.42	-1.49
7,158.0	88.22	328.02	6,323.8	1,711.8	1,008.5	-548.7	1,146.9	2.88	-2.39	-1.61
7,222.0	89.80	328.20	6,324.9	1,712.9	1,062.9	-582.5	1,210.6	2.48	2.47	0.28
7,287.0	91.47	328.55	6,324.2	1,712.2	1,118.2	-616.5	1,275.2	2.63	2.57	0.54
7,351.0	89.14	327.26	6,323.9	1,711.9	1,172.4	-650.5	1,338.9	4.16	-3.64	-2.02
7,383.0	89.80	327.94	6,324.2	1,712.2	1,199.4	-667.7	1,370.6	2.96	2.06	2.13
7,414.0	90.11	328.02	6,324.2	1,712.2	1,225.7	-684.1	1,401.5	1.03	1.00	0.26
7,479.0	88.18	329.26	6,325.2	1,713.2	1,281.2	-717.9	1,466.2	3.53	-2.97	1.91
7,510.0	87.82	329.43	6,326.2	1,714.2	1,307.9	-733.7	1,497.0	1.28	-1.16	0.55
7,574.0	88.09	329.61	6,328.5	1,716.5	1,363.0	-766.2	1,560.8	0.51	0.42	0.28
7,606.0	87.08	329.08	6,329.9	1,717.9	1,390.5	-782.5	1,592.7	3.56	-3.16	-1.66
7,639.0	86.24	328.38	6,331.8	1,719.8	1,418.6	-799.6	1,625.5	3.31	-2.55	-2.12
7,672.0	88.04	328.11	6,333.4	1,721.4	1,446.7	-816.9	1,658.3	5.52	5.45	-0.82
7,704.0	88.84	328.02	6,334.3	1,722.3	1,473.8	-833.8	1,690.1	2.52	2.50	-0.28
7,735.0	89.89	328.11	6,334.7	1,722.7	1,500.1	-850.2	1,720.9	3.40	3.39	0.29
7,768.0	89.41	328.02	6,334.9	1,722.9	1,528.1	-867.7	1,753.7	1.48	-1.45	-0.27
7,832.0	91.30	328.20	6,334.5	1,722.5	1,582.5	-901.5	1,817.4	2.97	2.95	0.28
7,896.0	90.59	327.59	6,333.4	1,721.4	1,636.7	-935.5	1,881.0	1.46	-1.11	-0.95
7,961.0	90.81	329.87	6,332.6	1,720.6	1,692.2	-969.2	1,945.7	3.52	0.34	3.51
8,025.0	90.64	331.01	6,331.8	1,719.8	1,747.9	-1,000.8	2,009.6	1.80	-0.27	1.78
8,058.0	89.41	332.42	6,331.8	1,719.8	1,776.9	-1,016.5	2,042.5	5.67	-3.73	4.27
8,090.0	89.14	331.72	6,332.2	1,720.2	1,805.2	-1,031.4	2,074.5	2.34	-0.84	-2.19
8,122.0	89.32	332.16	6,332.6	1,720.6	1,833.4	-1,046.5	2,106.5	1.49	0.56	1.38
8,155.0	89.85	333.21	6,332.9	1,720.9	1,862.8	-1,061.6	2,139.5	3.56	1.61	3.18
8,186.0	88.79	335.14	6,333.2	1,721.2	1,890.7	-1,075.1	2,170.5	7.10	-3.42	6.23
8,219.0	88.35	335.76	6,334.1	1,722.1	1,920.7	-1,088.8	2,203.4	2.30	-1.33	1.88
8,251.0	88.62	336.11	6,334.9	1,722.9	1,949.9	-1,101.9	2,235.4	1.38	0.84	1.09
8,282.0	89.93	337.60	6,335.3	1,723.3	1,978.4	-1,114.1	2,266.4	6.40	4.23	4.81
8,314.0	90.95	338.13	6,335.0	1,723.0	2,008.0	-1,126.1	2,298.3	3.59	3.19	1.66
8,346.0	89.85	336.81	6,334.8	1,722.8	2,037.6	-1,138.4	2,330.2	5.37	-3.44	-4.13
8,378.0	88.53	336.02	6,335.3	1,723.3	2,066.9	-1,151.2	2,362.2	4.81	-4.13	-2.47
8,411.0	89.14	336.11	6,335.9	1,723.9	2,097.1	-1,164.6	2,395.2	1.87	1.85	0.27
8,443.0	89.45	335.93	6,336.3	1,724.3	2,126.3	-1,177.6	2,427.2	1.12	0.97	-0.56
8,475.0	89.76	335.67	6,336.6	1,724.6	2,155.5	-1,190.7	2,459.2	1.26	0.97	-0.81
8,507.0	90.68	336.46	6,336.4	1,724.4	2,184.7	-1,203.7	2,491.1	3.79	2.88	2.47

Company:	EOG Resources	Local Co-ordinate Reference:	Well Windmill #04-22H
Project:	Weld Co., CO	TVD Reference:	Windmill 4-22H KBE @ 4612.0ft (True 30)
Site:	Sec 22-T5N-R62W	MD Reference:	Windmill 4-22H KBE @ 4612.0ft (True 30)
Well:	Windmill #04-22H	North Reference:	True
Wellbore:	Hz	Survey Calculation Method:	Minimum Curvature
Design:	Hz	Database:	Local

Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	Subsea Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
8,539.0	89.63	334.97	6,336.4	1,724.4	2,213.9	-1,216.8	2,523.1	5.70	-3.28	-4.66
8,571.0	88.48	335.32	6,336.9	1,724.9	2,242.9	-1,230.3	2,555.1	3.76	-3.59	1.09
8,603.0	88.97	335.85	6,337.6	1,725.6	2,272.1	-1,243.5	2,587.1	2.26	1.53	1.66
8,666.0	88.97	335.23	6,338.7	1,726.7	2,329.4	-1,269.6	2,650.1	0.98	0.00	-0.98
8,698.0	89.45	335.58	6,339.2	1,727.2	2,358.5	-1,282.9	2,682.0	1.86	1.50	1.09
8,730.0	90.37	336.02	6,339.2	1,727.2	2,387.7	-1,296.0	2,714.0	3.19	2.88	1.38
8,762.0	89.32	335.06	6,339.3	1,727.3	2,416.8	-1,309.3	2,746.0	4.45	-3.28	-3.00
8,794.0	89.71	334.62	6,339.6	1,727.6	2,445.8	-1,322.9	2,778.0	1.84	1.22	-1.38
8,825.0	89.80	333.74	6,339.7	1,727.7	2,473.7	-1,336.4	2,809.0	2.85	0.29	-2.84
8,858.0	89.58	332.51	6,339.9	1,727.9	2,503.1	-1,351.3	2,842.0	3.79	-0.67	-3.73
8,890.0	89.80	331.98	6,340.1	1,728.1	2,531.4	-1,366.2	2,874.0	1.79	0.69	-1.66
8,955.0	89.67	332.59	6,340.4	1,728.4	2,589.0	-1,396.4	2,939.0	0.96	-0.20	0.94
9,020.0	89.58	332.68	6,340.8	1,728.8	2,646.7	-1,426.3	3,003.9	0.20	-0.14	0.14
9,051.0	89.58	333.83	6,341.0	1,729.0	2,674.4	-1,440.3	3,034.9	3.71	0.00	3.71
9,082.0	90.02	335.50	6,341.1	1,729.1	2,702.4	-1,453.5	3,065.9	5.57	1.42	5.39
9,115.0	89.80	336.20	6,341.2	1,729.2	2,732.5	-1,467.0	3,098.9	2.22	-0.67	2.12
9,146.0	89.71	336.11	6,341.3	1,729.3	2,760.8	-1,479.6	3,129.9	0.41	-0.29	-0.29
9,177.0	89.23	336.90	6,341.6	1,729.6	2,789.3	-1,491.9	3,160.9	2.98	-1.55	2.55
9,210.0	89.89	336.81	6,341.8	1,729.8	2,819.6	-1,504.9	3,193.8	2.02	2.00	-0.27
9,242.0	89.67	336.29	6,342.0	1,730.0	2,849.0	-1,517.6	3,225.8	1.76	-0.69	-1.63
9,274.0	89.45	336.37	6,342.2	1,730.2	2,878.3	-1,530.5	3,257.8	0.73	-0.69	0.25
9,307.0	89.67	336.81	6,342.5	1,730.5	2,908.6	-1,543.6	3,290.7	1.49	0.67	1.33
9,338.0	89.45	337.87	6,342.7	1,730.7	2,937.2	-1,555.5	3,321.7	3.49	-0.71	3.42
9,403.0	89.58	336.73	6,343.3	1,731.3	2,997.1	-1,580.6	3,386.6	1.77	0.20	-1.75
9,467.0	89.41	334.70	6,343.8	1,731.8	3,055.5	-1,606.9	3,450.5	3.18	-0.27	-3.17
9,500.0	89.32	333.83	6,344.2	1,732.2	3,085.2	-1,621.2	3,483.5	2.65	-0.27	-2.64
9,532.0	89.45	334.53	6,344.5	1,732.5	3,114.0	-1,635.2	3,515.5	2.22	0.41	2.19
9,564.0	88.97	336.29	6,345.0	1,733.0	3,143.1	-1,648.5	3,547.5	5.70	-1.50	5.50
9,596.0	89.36	337.52	6,345.4	1,733.4	3,172.5	-1,661.1	3,579.5	4.03	1.22	3.84
9,627.0	89.45	337.08	6,345.8	1,733.8	3,201.1	-1,673.0	3,610.4	1.45	0.29	-1.42
9,659.0	88.57	337.69	6,346.3	1,734.3	3,230.6	-1,685.3	3,642.4	3.35	-2.75	1.91
9,692.0	89.63	338.66	6,346.8	1,734.8	3,261.3	-1,697.6	3,675.3	4.35	3.21	2.94
9,724.0	89.41	338.22	6,347.1	1,735.1	3,291.0	-1,709.3	3,707.2	1.54	-0.69	-1.38
9,756.0	88.40	338.48	6,347.7	1,735.7	3,320.8	-1,721.1	3,739.1	3.26	-3.16	0.81
9,787.0	87.43	338.84	6,348.8	1,736.8	3,349.6	-1,732.4	3,770.0	3.34	-3.13	1.16
9,819.0	87.43	338.92	6,350.3	1,738.3	3,379.5	-1,743.9	3,801.8	0.25	0.00	0.25
9,851.0	87.21	338.84	6,351.8	1,739.8	3,409.3	-1,755.5	3,833.7	0.73	-0.69	-0.25
9,883.0	87.65	338.66	6,353.2	1,741.2	3,439.1	-1,767.0	3,865.5	1.49	1.38	-0.56
9,916.0	87.43	338.40	6,354.6	1,742.6	3,469.7	-1,779.1	3,898.4	1.03	-0.67	-0.79
9,947.0	88.22	338.04	6,355.8	1,743.8	3,498.5	-1,790.6	3,929.3	2.80	2.55	-1.16
9,978.0	89.89	337.87	6,356.3	1,744.3	3,527.2	-1,802.2	3,960.2	5.41	5.39	-0.55
10,011.0	91.03	337.34	6,356.0	1,744.0	3,557.7	-1,814.8	3,993.2	3.81	3.45	-1.61
10,043.0	91.12	337.69	6,355.4	1,743.4	3,587.3	-1,827.0	4,025.1	1.13	0.28	1.09

Company:	EOG Resources	Local Co-ordinate Reference:	Well Windmill #04-22H
Project:	Weld Co., CO	TVD Reference:	Windmill 4-22H KBE @ 4612.0ft (True 30)
Site:	Sec 22-T5N-R62W	MD Reference:	Windmill 4-22H KBE @ 4612.0ft (True 30)
Well:	Windmill #04-22H	North Reference:	True
Wellbore:	Hz	Survey Calculation Method:	Minimum Curvature
Design:	Hz	Database:	Local


Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	Subsea Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
10,108.0	90.42	337.08	6,354.6	1,742.6	3,647.3	-1,852.0	4,090.0	1.43	-1.08	-0.94
10,171.0	89.32	336.81	6,354.7	1,742.7	3,705.3	-1,876.7	4,152.9	1.80	-1.75	-0.43
10,203.0	89.54	337.34	6,355.0	1,743.0	3,734.7	-1,889.2	4,184.9	1.79	0.69	1.66
10,236.0	90.55	337.34	6,355.0	1,743.0	3,765.2	-1,901.9	4,217.8	3.06	3.06	0.00
10,298.0	90.02	336.73	6,354.7	1,742.7	3,822.3	-1,926.1	4,279.7	1.30	-0.85	-0.98
10,330.0	90.64	336.90	6,354.5	1,742.5	3,851.7	-1,938.7	4,311.7	2.01	1.94	0.53
10,394.0	90.33	336.29	6,354.0	1,742.0	3,910.4	-1,964.1	4,375.6	1.07	-0.48	-0.95
10,459.0	89.93	336.11	6,353.8	1,741.8	3,969.9	-1,990.3	4,440.6	0.67	-0.62	-0.28
10,491.0	88.44	334.70	6,354.3	1,742.3	3,999.0	-2,003.6	4,472.6	6.41	-4.66	-4.41
10,523.0	88.09	334.26	6,355.2	1,743.2	4,027.9	-2,017.4	4,504.5	1.76	-1.09	-1.38
10,555.0	89.36	334.18	6,356.0	1,744.0	4,056.7	-2,031.3	4,536.5	3.98	3.97	-0.25
10,587.0	89.54	333.74	6,356.3	1,744.3	4,085.4	-2,045.4	4,568.5	1.49	0.56	-1.38
10,618.0	89.27	333.12	6,356.6	1,744.6	4,113.1	-2,059.2	4,599.5	2.18	-0.87	-2.00
Projection to Bit										
10,669.0	89.27	333.12	6,357.2	1,745.2	4,158.6	-2,082.3	4,650.5	0.00	0.00	0.00

Survey Annotations

Measured Depth (')	Vertical Depth (')	Local Coordinates		Comment
		+N/-S (')	+E/-W (')	
10,669.0	6,357.2	4,158.6	-2,082.3	Projection to Bit

Checked By: _____ Approved By: _____ Date: _____



WELL DETAILS: Windm 004-22H

Ground Level:		Longitude		Slot
±K.S.	±EUM	Northings	Eastings	
0.0	0.0	3833504.48	2335028.17	
		40° 22' 48.20 N	104° 18' 4.80 W	

SECTION DETAILS

SECTION DETAILS

No plan data is available

FORMATION TOP DETAILS

Ala formation data is available

ANNOTATIONS

TVD	MD	Annotation
6357.2	10669.0	Projection to GSI

CASING DETAILS

No caídas desde la escalera



WELLBORE TARGET DETAILS (LAT/LONG)				
Name	TVD	±N-Δ	Latitude	Longitude
		±E-Δ		ShoatNo wellbore target data is available.

