Company KERR-MCGEE OIL & GAS ONSHORE LP
Well CHRISTNER 8-66-5-3H
Field WILDCAT
County WELD
State COLO

J-W WIRELINE COMPANY

GAMMA RAY CCL
CEMENT BOND VDL

Company	KERR-MCGEE OIL & GAS ONSHORE LP
Well	CHRISTNER 8-66-5-3H
Field	WILDCAT
County	WELD
State	COLO

Location: API # : 05-123-33866
250' FNL & 1680' FWL
NE NW
SEC 5 TWP 8N RGE 66W

Other Services

Permanent Datum	GL	Elevation	5192
Log Measured From	KB		
Drilling Measured From	KB		

Elevation
K.B. 5217
D.F.
G.L. 5192

Date	NOV-19-2011
Run Number	ONE
Depth Driller	11400
Depth Logger	6700
Bottom Logged Interval	6700
Top Log Interval	
Open Hole Size	
Type Fluid	WATER
Density / Viscosity	
Max. Recorded Temp.	248
Estimated Cement Top	1830
Time Well Ready	
Time Logger on Bottom	
Equipment Number	2833
Location	STERLING
Recorded By	KYLE GIRDLER
Witnessed By	FRED KLAUSEN

Borehole Record				Tubing Record		
Run Number	Bit	From	To	Size	Weight	From	To

Casing Record	Size	Wgt/Ft	Top	Bottom
Surface String				
Prot. String	7			
Production String				
Liner	4.5			

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING J-W WIRELINE
LOGGED UNDER 2500 PSI

Database File: christner 8-66-5-3h.db
Dataset Pathname: pass3
Presentation Format: scbl
Dataset Creation: Sat Nov 19 10:58:51 2011 by Log Std Casedhole 07122
Charted by: Depth in Feet scaled 1:240


3800
3850
3900
3950
4000


4050
4100
4150
4200


4250
4300
4350
4400
4450


4500
4550
4600
4650


4700
4750
4800
4850
4900


4950
5000
5050
5100


5150
5200
5250
5300
5350


5400
5450
5500
5550


5600
5650
5700
5750


5800
5850
5900
5950


6000
6050
6100
6150


6200
6250
6300
6350


6400
6450
6500
6550


6600
6650
6700
LTEN
0 (lb)2000
-9 CCL 1
0 GR (GAPI) 300
0 AMP (mV) 100
0 AMPx5 (mV) 20
0 AMPAVG 150
0 AMPMAX 150
0 AMPMIN 150
200 VDL 1200
1 VAD 8
10 60