FORM 4
Rev 12/05

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303)894-2100 Fax:(303)894-2109

SUNDRY NOTICE

Submit original plus one copy. This form is to be used for general, technical and environmental sundry information. For proposed or completed operations, describe in full on Technical Information Page (Page 2 of this form.) Identify well or other facility by API Number or by OGCC Facility ID. Operator shall send an informational copy of all sundry notices for wells located in High Density Areas to the Local Government Designee (Rule 603b.)

1. OGCC Operator Number: 10339		4. Contact Name David Segobia	
2. Name of Operator: Gulfport Energy Corp.		Phone: 405-242-4977	
3. Address: 14313 N May		Fax: 405-848-8816	
City: Oklahoma City	State: OK	Zip: 73134	
5. API Number 05- 081-07664	OGCC Facility ID Number Loc 424085		
6. Well/Facility Name: State	7. Well/Facility Number 41-14-1		
8. Location (QtrQtr, Sec, Twp, Rng, Meridian): Lot 13 Sec 14 T6N R91W Meridian 6			
9. County: Moffat	10. Field Name: Craig		
11. Federal, Indian or State Lease Number:			

Complete the Attachment Checklist

	OP	OGCC
Survey Plat		
Directional Survey		
Surface Eqpmt Diagram		
Technical Info Page		
Other		

General Notice

☐ CHANGE OF LOCATION: Attach New Survey Plat (a change of surface qtr/qtr is substantive and requires a new permit)

	FNL/FSL		FEL/FWL	
Change of **Surface** Footage **from** Exterior Section Lines.				
Change of **Surface** Footage **to** Exterior Section Lines:				
Change of **Bottomhole** Footage **from** Exterior Section Lines:				
Change of **Bottomhole** Footage **to** Exterior Section Lines:				attach directional survey

Bottomhole location Qtr/Qtr, Sec, Twp, Rng, Mer

Latitude ____ Distance to nearest property line ____ Distance to nearest bldg, public rd, utility or RR ____

Longitude ____ Distance to nearest lease line ____ Is location in a High Density Area (rule 603b)? Yes/No ____

Ground Elevation ____ Distance to nearest well same formation ____ Surface owner consultation date: ____

GPS DATA:
Date of Measurement ____ PDOP Reading ____ Instrument Operator's Name ____

☐ CHANGE SPACING UNIT

Formation	Formation Code	Spacing order number	Unit Acreage	Unit configuration

☐ Remove from surface bond
Signed surface use agreement attached

☐ CHANGE OF OPERATOR (prior to drilling):
Effective Date: ____
Plugging Bond: ☐ Blanket ☐ Individual

☐ CHANGE WELL NAME NUMBER
From: ____
To: ____
Effective Date: ____

☐ ABANDONED LOCATION:
Was location ever built? ☐ Yes ☐ No
Is site ready for inspection? ☐ Yes ☐ No
Date Ready for Inspection: ____

☐ NOTICE OF CONTINUED SHUT IN STATUS
Date well shut in or temporarily abandoned: ____
Has Production Equipment been removed from site? ☐ Yes ☐ No
MIT required if shut in longer than two years. Date of last MIT ____

☐ SPUD DATE: ____

☐ REQUEST FOR CONFIDENTIAL STATUS (6 mos from date casing set)

☐ SUBSEQUENT REPORT OF STAGE, SQUEEZE OR REMEDIAL CEMENT WORK *submit cbl and cement job summaries

Method used	Cementing tool setting/perf depth	Cement volume	Cement top	Cement bottom	Date

☐ RECLAMATION: Attach technical page describing final reclamation procedures per Rule 1004.
Final reclamation will commence on approximately ____ ☐ Final reclamation is completed and site is ready for inspection.

Technical Engineering/Environmental Notice

☐ Notice of Intent
Approximate Start Date: ____

☐ Report of Work Done
Date Work Completed: ____

Details of work must be described in full on Technical Information Page (Page 2 must be submitted.)

☐ Intent to Recomplete (submit form 2)	☐ Request to Vent or Flare	☐ E&P Waste Disposal
☐ Change Drilling Plans	☐ Repair Well	☐ Beneficial Reuse of E&P Waste
☐ Gross Interval Changed?	☐ Rule 502 variance requested	☐ Status Update/Change of Remediation Plans for Spills and Releases
☐ Casing/Cementing Program Change	☒ Other: soil samples	

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct and complete.

Signed: David C. Segobia Date: 1/4/2012 Email: dsegobia@gulfportenergy.com

Print Name: David Segobia Title: Sr. Reservoir Engineering Tech, CPT

COGCC Approved: Cleon Fin Title: Env. Sup. Date: 1/6/2012

CONDITIONS OF APPROVAL, IF ANY:

See Attached conditions of approval.
1/6/2012

1/6/2012 [illegible]

Conditions of Approval:

- Analytical results exceed the 910-1 concentration levels. Provide a Form 27 Remediation Work Plan and schedule to implement remediation of the materials by February 3, 2012.
- Remediate materials that were transported to the Weber property (SENW Section 11, Township 6 North, Range 91 West).
- Collect representative samples and analyze for the constituents listed in Table 910-1 (attached) documenting remediation of the material brought onto the Weber property.

Table 910-1
CONCENTRATION LEVELS[1]

Contaminant of Concern	Concentrations
Organic Compounds in Soil	
TPH (total volatile and extractable petroleum hydrocarbons)	500 mg/kg
Benzene	0.17 mg/kg[2]
Toluene	85 mg/kg[2]
Ethylbenzene	100 mg/kg[2]
Xylenes (total	175 mg/kg[2]
Acenaphthene	1,000 mg/kg[2]
Anthracene	1,000 mg/kg[2]
Benzo(A)anthracene	0.22 mg/kg[2]
Benzo(B)fluoranthene	0.22 mg/kg[2]
Benzo(K)fluoranthene	2.2 mg/kg[2]
Benzo(A)pyrene	0.022 mg/kg[2]
Chrysene	22 mg/kg[2]
Dibenzo(A,H)anthracene	0.022 mg/kg[2]
Fluoranthene	1,000 mg/kg[2]
Fluorene	1,000 mg/kg[2]
Indeno(1,2,3,C,D)pyrene	0.22 mg/kg[2]
Napthalene	23 mg/kg[2]
Pyrene	1,000 mg/kg[2]
Organic Compounds in Ground Water	
Benzene	5 μg/l[3]
Toluene	560 to 1,000 μg/l[3]
Ethylbenzene	700 μg/l[3]
Xylenes (Total)	1,400 to 10,000 μg/l[3,4]
Inorganics in Soils	
Electrical Conductivity (EC)	<4 mmhos/cm or 2x background
Sodium Adsorption Ratio (SAR)	<12[5]
pH	6-9
Inorganics in Ground Water	
Total Dissolved Solids (TDS)	<1.25 x background[3]
Chlorides	<1.25 x background[3]
Sulfates	<1.25 x background[3]
Metals in Soils	
Arsenic	0.39 mg/kg[2]
Barium (LDNR True Total Barium)	15,000 mg/kg[2]
Boron (Hot Water Soluble)	2 mg/l[3]
Cadmium	70 mg/kg[3,6]
Chromium (III)	120,000 mg/kg[2]
Chromium (VI)	23 mg/kg[2,6]
Copper	3,100 mg/kg[2]
Lead (inorganic)	400 mg/kg[2]
Mercury	23 mg/kg[2]
Nickel (soluble salts)	1,600 mg/kg[2,6]
Selenium	390 mg/kg[2,6]
Silver	390 mg/kg[2]
Zinc	23,000 mg/kg[2,6]
Liquid Hydrocarbons in Soils and Ground Water	
Liquid hydrocarbons including condensate and oil	Below detection level

COGCC recommends that the latest version of EPA SW 846 analytical methods be used where possible and that analyses of samples be performed by laboratories that maintain state or national accreditation programs.

[1] Consideration shall be given to background levels in native soils and ground water.

[2] Concentrations taken from CDPHE-HMWMD Table 1 Colorado Soil Evaluation Values (December 2007).

[3] Concentrations taken from CDPHE-WQCC Regulation 41 - The Basic Standards for Ground Water.

[4] For this range of standards, the first number in the range is a strictly health-based value, based on the WQCC's established methodology for human health-based standards. The second number in the range is a maximum contaminant level (MCL), established under the Federal Safe Drinking Water Act which has beendetermined to be an acceptable level of this chemical in public water supplies, taking treatability and laboratory detection limits into account. The WQCC intends that control requirements for this chemical be implemented to attain a level of ambient water quality that is at least equal to the first number in the range except as follows: 1) where ground water quality exceeds the first number in the range due to a release of contaminants that occurred prior to September 14, 2004 (regardless of the date of discovery or subsequent migration of such contaminants) clean-up levels for the entire contaminant plume shall be no more restrictive than the second number in the range or the ground water quality resulting from such release, whichever is more protective, and 2) whenever the WQCC has adopted alternative, site-specific standards for the chemical, the site-specific standards shall apply instead of these statewide standards.

[5] Analysis by USDA Agricultural Handbook 60 method (20B) with soluble cations determined by method (2). Method (20B) = estimation of exchangeable sodium percentage and exchangeable potassium percentage
from soluble cations. Method (2) = saturated paste method (note: each analysis requires a unique sample of at least 500 grams). If soils are saturated, USDA Agricultural Handbook 60 with soluble cations determined by method (3A) saturation extraction method.

[6] The table value for these inorganic constituents is taken from the CDPHE-HMWMD Table 1 Colorado Soil
Evaluation Values (December 2007). However, because these values are high, it is possible that site - specific geochemical conditions may exist that could allow these constituents to migrate into ground water at levels exceeding ground water standards even though the concentrations are below the table values.
Therefore, when these constituents are present as contaminants, a secondary evaluation of their leachability must be performed to ensure ground water protection.