

THE DATA DELIVERED, INTERPRETATIONS AND RECOMMENDATIONS CONTAINED HEREIN ARE PROVIDED BY WARRIOR ENERGY SERVICES IN GOOD FAITH BUT WARRIOR ENERGY SERVICES MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS OR RELIABILITY OF THE DATA, INTERPRETATIONS OR RECOMMENDATIONS AND ASSUMES NO RESPONSIBILITY FOR ANY LOSS, DAMAGE OR EXPENSE INCURRED IN CONNECTION WITH THE USE THEREOF. IN NO EVENT SHALL WARRIOR ENERGY SERVICES BE LIABLE FOR SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

CONFIDENTIAL

THANK YOU FOR CHOOSING
WARRIOR ENERGY SERVICES
1000 WARRIOR WAY
WARRIOR ENERGY SERVICES
CITY, STATE 12345
(555) 555-5555
UNITED STATES

MAIN PASS

Company: WARRIOR ENERGY SERVICES
Well: 1-TEST-1 (SURFACE)
Field: UNDEFINED
County: RED RIVER
State: TEXAS
API: 42-999-99999
Location: SEC 1 BLK 1 TEST SURVEY
Elevation: 1000 KB
Permanent Datum: GROUND LEVEL
Log Measured From: KB
Drilling Measured From: KB
Run Number: ONE
Date: 10-Jan-2011
Depth Driller: 10000
Depth Logger: 10000
Bottom Log Interval: 10000
Top Log Interval: 0
Casing Driller: 9.625 @ 1000
Casing Logger: 1000
Bit Size: 8.5
Type Fluid in Hole: WBM
Density: 10.2
Viscosity: 50
Fluid Loss: 4.5
Source of Sample: FLOWLINE
Rm @ Measured Temp: 0.1 @ 150
Rmf @ Measured Temp: 0.08 @ 150
Rmc @ Measured Temp: 0.12 @ 150
Source of Rmf and Rmc: MEASURED
Rm @ BHT: 0.05 @ 200
Time Circulation Stopped: 10:00
Time Logger on Bottom: 14:00
Maximum Recorded Temperature: 200
Equipment Number: 1
Location: SEC 1 BLK 1 TEST SURVEY
Recorded By: J. DOE
Witnessed By: J. SMITH

Gamma Ray (API) 0 150 | Resistivity (ohm.m) 0.2 2000 | Porosity (%) 45 -15

REPEAT PASS

Company: WARRIOR ENERGY SERVICES
Well: 1-TEST-1 (SURFACE)
Field: UNDEFINED
County: RED RIVER
State: TEXAS
API: 42-999-99999
Location: SEC 1 BLK 1 TEST SURVEY
Elevation: 1000 KB
Permanent Datum: GROUND LEVEL
Log Measured From: KB
Drilling Measured From: KB
Run Number: TWO
Date: 11-Jan-2011
Depth Driller: 10000
Depth Logger: 10000
Bottom Log Interval: 10000
Top Log Interval: 0
Casing Driller: 9.625 @ 1000
Casing Logger: 1000
Bit Size: 8.5
Type Fluid in Hole: WBM
Density: 10.2
Viscosity: 50
Fluid Loss: 4.5
Source of Sample: FLOWLINE
Rm @ Measured Temp: 0.1 @ 150
Rmf @ Measured Temp: 0.08 @ 150
Rmc @ Measured Temp: 0.12 @ 150
Source of Rmf and Rmc: MEASURED
Rm @ BHT: 0.05 @ 200
Time Circulation Stopped: 10:00
Time Logger on Bottom: 14:00
Maximum Recorded Temperature: 200
Equipment Number: 1
Location: SEC 1 BLK 1 TEST SURVEY
Recorded By: J. DOE
Witnessed By: J. SMITH

Gamma Ray (API) 0 150 | Resistivity (ohm.m) 0.2 2000 | Porosity (%) 45 -15

Final Reading 10000

Name	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			CABLE	5.00	1.44	11.00
			1.750 in. HD	5.00	1.69	15.00
			1.750 in. HD			
TEMP	10.00					
SHUT OFF	15.00		CBL TEMP (TEMPERATURE ARCHIVE SONDE)	6.67	1.69	20.00
SHUT OFF	15.00		TEMP (TEMPERATURE SONDE)			
SHUT OFF	15.00					
			1.750 in. HD	5.00	1.69	15.00
			1.750 in. HD			
SHUT OFF	11.00					
SHUT OFF	11.00					
			CCL (Tool) (CASING COLLAR LOCATOR)	1.00	1.69	4.00
CCL	4.40		CCL (Tool) (CASING COLLAR LOCATOR)			
			GR (Tool) (GAMMA RAY) (NATURAL GAMMA RAY)	4.73	1.69	15.00
GR	4.40		GR (Tool) (GAMMA RAY) (NATURAL GAMMA RAY)			
			1.750 in. HD	5.00	1.69	15.00
			1.750 in. HD			
			Cablehead (CABLEHEAD) (CABLE HEAD)	0.50	1.69	5.00
			ACCESS TO SELECT ALL Perforation Gunsel (PERF GUN)			