Company	Halliburton Energy Services
Well	Mississippi Canyon 252 #1
Field	Mississippi Canyon 252
Location	Gulf of Mexico
Coordinate System	NAD83
Datum	Mean Sea Level
Permanent Datum	Mean Sea Level
Elevation	0 ft
Log Measured From	Rig Floor
Drilling Measured From	Rig Floor
Elevation	0 ft
Date	2010-04-20
Run Number	1
Depth Driller	18,360 ft
Depth Logger	18,360 ft
Bottom Logged Interval	18,360 ft
Top Logged Interval	17,500 ft
Drilling Fluid Type	Synthetic Oil-Based Mud
Density	14.2 ppg
Viscosity	58 s
Fluid Loss	3.2 cc/30min
Max Recorded Temperature	198 °F
Max Recorded Pressure	12,450 psi
Estimated Surface Temperature	85 °F
Equipment Number	HES-GR-0042
Location	Houma, LA
Recorded By	J. Thibodeaux
Witnessed By	M. Arceneaux

Run	Logged Interval	Bit Size	Casing Size	Weight	Grade	Top	Bottom
1	17,500 – 18,360 ft	8.5 in	7 in	29 lb/ft	P-110	17,500 ft	18,360 ft

Mnemonic	Description	Unit
GR	Gamma Ray	API
RT	Deep Resistivity	ohm.m
RM	Medium Resistivity	ohm.m
RS	Shallow Resistivity	ohm.m
DEN	Bulk Density	g/cm3
NPHI	Neutron Porosity	v/v
PEF	Photoelectric Factor	b/e
CALI	Caliper	in
DT	Sonic Transit Time	us/ft

TIGHE FOX 5TH SOUTHEAST GR-RES-DEN
DEPTH REFERENCED TO CABLE HEAD 14,000 FEET ABOVE MEAN SEA LEVEL

Company	Halliburton Energy Services
Well	Mississippi Canyon 252 #1
Field	Mississippi Canyon 252
Location	Gulf of Mexico
Coordinate System	NAD83
Datum	Mean Sea Level
Permanent Datum	Mean Sea Level
Elevation	0 ft
Log Measured From	Rig Floor
Drilling Measured From	Rig Floor
Elevation	0 ft
Date	2010-04-20
Run Number	1
Depth Driller	18,360 ft
Depth Logger	18,360 ft
Bottom Logged Interval	18,360 ft
Top Logged Interval	17,500 ft
Drilling Fluid Type	Synthetic Oil-Based Mud
Density	14.2 ppg
Viscosity	58 s
Fluid Loss	3.2 cc/30min
Max Recorded Temperature	198 °F
Max Recorded Pressure	12,450 psi
Estimated Surface Temperature	85 °F
Equipment Number	HES-GR-0042
Location	Houma, LA
Recorded By	J. Thibodeaux
Witnessed By	M. Arceneaux

Run	Logged Interval	Bit Size	Casing Size	Weight	Grade	Top	Bottom
1	17,500 – 18,360 ft	8.5 in	7 in	29 lb/ft	P-110	17,500 ft	18,360 ft

Mnemonic	Description	Unit
GR	Gamma Ray	API
RT	Deep Resistivity	ohm.m
RM	Medium Resistivity	ohm.m
RS	Shallow Resistivity	ohm.m
DEN	Bulk Density	g/cm3
NPHI	Neutron Porosity	v/v
PEF	Photoelectric Factor	b/e
CALI	Caliper	in
DT	Sonic Transit Time	us/ft


4000
4100
4200
4300
4400
4500
4600
4700
4800
4900
5000
5100
5200
Gamma Ray
Casing Collar Locator
Variable Density
Amplitude
Amplified Amplitude
0 GR (GAPI) 200
-0 CCL 1
0 Amplitude (mV) 100 200
0 Amplified Amplitude (mV) 30
Variable Density 1200