

ACTUAL P&A'D WELLBORE SCHEMATIC

DESCRIPTION

KB
GL

DEPTH
6030'
6079'

WELLBORE

DEPTH

TOC Surface string
27' ex Class G in annulus
15' ex Class G in casing

TOC Production String (CBL)
6.2 bbl 8.58 kill fluid
Approximate top of plug
20' ex Class G balanced plug

Surface Casing
8 5/8"

12 1/4" Hole

492'

558'

3416'

3880'

4003'

Not to scale

4159'
FC
7 7/8" Hole
TD

4159'
4209'
4259'

4159'

68.2 bbl 8.58 kill fluid
Approximate top of plug
60' ex Class G balanced plug (35' ex squeezed into parts)



WELL:

LOCATION:

COUNTY, STATE:

API #:

Legal Description:

CLASSIFICATION:

CURRENT STATUS:

WI:

NRI:

CUM PRODUCTION:

CURRENT PRODUCTION:

Kaline State #13

Sec 23-112N-R04W

Moffat, CO

05-081-47207

880' FNL & 660' FWL

CBM

Completion

SPUD: 2/15/2005

UPDATED: 2/2/2011

MMCF

MBOW

0 BOPD

0 MCFD

TYPE SIZE WEIGHT GRADE TOP BOTTOM 80% INTERNAL YIELD PSI

Surface 8 5/8 45.5 405 492

Intermediate 0 0 0 0

Liner 0 0 0 0

Production 5 1/2 15.58 J-55 4256' 3648

Cement Detail:

Surface Casing Cement

Production Casing Cement

Liner Casing Cement

Tubing Detail:

Well History

8271585 Spud