



02542240

radio Commission



1120 Lincoln Street, Suite 601, Denver, Colorado 80203 Phone: (303)894-2100 Fax: (303)894-2109

SUNDRY NOTICE

Submit original plus one copy. This form is to be used for general, technical and environmental sundry information. For proposed or completed operations, describe in full on Technical Information Page (Page 2 of this form.) Identify well or other facility by API Number or by OGCC Facility ID. Operator shall send an informational copy of all sundry notices for wells located in High Density Areas to the Local Government Designee (Rule 603b.)



Form with fields for OGCC Operator Number (10316), Name of Operator (Mesa Energy Partners, LLC), Address (1001 17th St., Ste 1140), Contact Name (Dave Cesark), Phone (970-683-5447), API Number (05-103-11908), Well/Facility Name (Coyote Basin Unit), Well/Facility Number (29-12-397), Location (NWSW Sec. 29 T3N, R97W, 6th P.M.), County (Rio Blanco), Field Name (Colorow Gulch), and Federal, Indian or State Lease Number (COC 65818).

General Notice

General Notice section with checkboxes for CHANGE OF LOCATION, CHANGE SPACING UNIT, CHANGE OF OPERATOR, ABANDONED LOCATION, SPUD DATE, SUBSEQUENT REPORT OF STAGE, SQUEEZE OR REMEDIAL CEMENT WORK, and RECLAMATION. Includes fields for Attach New Survey Plat, GPS DATA, and various technical specifications.

Technical Engineering/Environmental Notice

Technical Engineering/Environmental Notice section with checkboxes for Notice of Intent (checked) and Report of Work Done, including Approximate Start Date (3/29/12) and Date Work Completed.

Details of work must be described in full on Technical Information Page (Page 2 must be submitted.)

Form with checkboxes for Intent to Recomplete, Change Drilling Plans (checked), Gross Interval Changed?, Casing/Cementing Program Change, Request to Vent or Flare, Repair Well, Rule 502 variance requested, Other, E&P Waste Disposal, Beneficial Reuse of E&P Waste, and Status Update/Change of Remediation Plans.

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct and complete.

Signed: James E. Schroeder, Date: 3/29/12, Email: jschroeder@mesa-energy.net, Title: President/CEO

COGCC Approved: [Signature], Title: NWAE, Date: 4/23/12

CONDITIONS OF APPROVAL, IF ANY:



02538011

PAGE 1



Mesa Energy Partners, LLC
Coyote Basin 29-12-397
 2617' FSL 849' FWL (NW/4 SW/4)
 Sec. 29 T3N R97W
 Rio Blanco County, Colorado
 Surface: Federal
 Federal Mineral Lease: CO65818

DRILLING PROGRAM

(Revised 3/29/12)

SURFACE ELEVATION – 5,851' (graded surface elevation)

SURFACE FORMATION – Wasatch – Fresh water possible

ESTIMATED FORMATION TOPS

<u>Formation</u>	<u>Depth</u>	<u>Description</u>
Mesaverde	507'	Sandstones & Shale
Rollins	3021'	Sandstone & Shale
Sego	3571'	Sandstone & Shale
Castlegate	4121'	Sandstone
Mancos	4246'	Shale
Morapos	4468'	Sandstone
Niobrara	7221'	Shale
Frontier	9021'	Sandstone & Shale
Mowry	9271'	Shale
Dakota	9361'	Sand
Morrison	9492'	Sand
TOTAL DEPTH	9742'	

ESTIMATED DEPTHS OF ANTICIPATED WATER, OIL, GAS, OR MINERAL BEARING FORMATIONS

Estimated depths at which water, oil, gas, or other mineral-bearing formations are expected to be encountered:

<u>Formation</u>	<u>Depth</u>	<u>Description</u>
Mesaverde	507'	Water
Rollins	3021'	Water
Sego	3571'	Water
Castlegate	4121'	Possible Water
Mancos	4246'	Possible Water
Morapos	4468'	Possible Water
Niobrara	7221'	Potential Oil/Gas
Frontier	9021'	Potential Oil/Gas

Mowry	9271'	Potential Oil/Gas
Dakota	9361'	Potential Oil/Gas
Morrison	9492'	Potential Oil/Gas

All fresh water and prospectively valuable minerals encountered during drilling will be recorded by depth and protected through complete cementing procedures.

CASING PROGRAM

Depth	String	Hole Diameter	Casing OD	Casing ID	Casing Weight and Grade
0' – 80'	Conductor	20"	16"	15.124	Conductor Casing
0' – 1000'	Surface	13.5"	10.75"	9.894	J-55 40.5# STC
0' – 4750'	Intermediate	9 7/8"	8.625"	7.796	HCK-55 32# LTC
0' – 9742'	Production	7 7/8"	5.5"	4.778	P-110 20.0# LTC

Depth	Stage	Cement	Description, Yield	Volume: sacks, ft ³
0' – 80'	Conductor	Ready Mix	To Surface	--, 113.1
0' – 635'	Surface	Class G, 8% Gel+Add	To Surface, Lead, 1.89	200, 396
635' – 1000'	Surface	Class G	To Surface, Tail, 1.15	200, 230
800' – 3269'	Intermediate: Lead	Class G, 8% Gel+Add	To 800' +50%, Lead, 1.89	247, 467
3269' – 4750'	Intermediate: Tail	Class G, 8% Gel+Add	To 800' +50%, Tail, 1.15	244, 280
7146' – 9742'	Production: Stage 1	50:50 PozMix, 4% Gel + Additives	From 9742' to 7146', 1.35	433, 585
4550' – 7146'	Production: Stage 2	50:50 PozMix, 4% Gel + Additives	From 7146' to 4550', 1.35	433, 585

Cement Calculations performed with 100% excess included for Surface Casing and 50% excess for Intermediate and 30% excess for Production Casing. Actual Cement Volumes will be determined from caliper log with excess included. A Cement Bond Log will be run in the Intermediate Casing from casing point Depth to 200' into the Surface Casing to determine cement top.

To account for the possibility of encountering zones of interest below the intermediate string but above the target zones, a full length cementing profile for the production casing has been included. This design includes production grade cement into the intermediate string from TD of 9742'. A stage cementing tool at approximately 7146', to be placed by drilling results, is expected to fully cement the interval in this design. Some additives and blends are service provider proprietary products. These blends and products may vary slightly based on cement vendor standards. Centralizers installed per approved centralizer program from cement vendor.

PRESSURE CONTROL

See attached Blowout Preventer (BOP) diagram.

BOPs and choke manifold will be installed and pressure tested before drilling out of surface casing (subsequent pressure test will be performed whenever pressure seals are broken), and then will be checked daily as to mechanical operating condition. BOPs will be pressure tested at least once every 30 days. Ram type preventers and related pressure control equipment will be pressure tested to related working pressure of the stack assembly if a test plug is used. If a plug is not used, the stack assembly will be tested to the rated working pressure of the stack assembly or 70% of the minimum internal yield of the casing, whichever is less. Annular type preventers will be pressure tested to 50% of their working pressure. All casing strings will be pressure tested to 0.22 psi/ft or 1,500 psi, whichever is greater, not to exceed 70% of the internal yield.

A manual locking device (i.e. hand wheels) or automatic locking devices shall be installed on the BOP stack. Remote controls capable of both opening and closing all preventers shall be readily accessible to the driller.

The choke manifold and accumulator will meet or exceed Onshore Order No. 2 (OSO #2) standards. The BOP equipment will be tested after any repairs to the equipment. Pipe rams, blind rams, and annular preventer will be activated on each trip and weekly BOP drills will be conducted with each crew. All tests, maintenance, and BOP drills will be documented on rig "tower sheets".

Statement of Accumulator System and Location of Hydraulic Controls

The drilling rig has not been selected for this well. Selection will take place after approval of this application is granted. Manual and/or hydraulic controls will be in compliance with OSO #2 for at least a 3,000 psi system.

A remote accumulator will be used. Pressures, capacities, location of remote hydraulic, and manual controls will be identified at the time of the BLM supervised BOP test.

MUD PROGRAM

Depth	Description	Mud Weight	Fluid Loss	Viscosity
0' – 1000'	Spud Mud	8.5 – 9.0 ppg	NC	20 – 80
1000' – 4150'	Gel/Polymer	8.5 – 9.3 ppg	6 – NC	30 – 100
4150' – 9742'	Gel/Polymer	9.0 – 9.5 ppg	4 – 10	30 – 100

Sufficient mud materials to maintain mud properties, control lost circulation, and to contain a "kick" will be available on location.

AUXILIARY EQUIPMENT

- A. Upper Kelly cock; (lower Kelly cock to be available on rig floor)
- B. Inside BOP or stabbing valve with handle (available on rig floor)

- C. Safety valve(s) and subs to fit all string connections in use
- D. Mud monitoring will be visually observed

LOGGING, CORING, TESTING PROGRAM

- A. Logging
 - a. Triple Combo TD to base of surface casing (GR to surface)
 - b. CBL-CCL-GR TD to 500' above top of cement
 - c. Fracture ID TD to zones of interest
 - d. Sonic Optional
- B. Coring
 - a. Full Bore Possible Sections from Mancos, Niobrara, or Frontier
 - b. Sidewall Possible Selections from Mancos, Niobrara, or Frontier

ABNORMAL CONDITIONS

- A. Pressures No Abnormal conditions are anticipated
- B. Temperatures No abnormal conditions are anticipated
- C. H₂S None anticipated
- D. Estimated bottom hole Using 0.45 psi/ft, 4383.9 psi at TD

ANTICIPATED START DATE

November 2011 – March 2012

COMPLETION

A Sundry Notice (SN) will be submitted with completion program details if warranted. A string of 2-7/8" is anticipated to be run for production purposes.

