

THIS PLOT IS A COMPUTER-PROCESSED INTERPRETATION. THE CUSTOMER, BY USE OF THIS PLOT, AGREES THAT NEITHER SCHLUMBERGER NOR ANY OF ITS AFFILIATED COMPANIES MAKE ANY WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OR CORRECTNESS OF THE PLOT OR ANY INTERPRETATION MADE THEREFROM. THE CUSTOMER AGREES THAT NEITHER SCHLUMBERGER NOR ANY OF ITS AFFILIATED COMPANIES SHALL BE LIABLE FOR ANY LOSS, DAMAGE OR EXPENSE SUFFERED OR INCURRED BY THE CUSTOMER IN CONNECTION WITH THE USE OF THIS PLOT.

Company

THREE TUTTER DIVISIONS NORTHEAST WELL 1, MORGUSTY
Gamma Ray, Caliper, Bit Size, Deep Resistivity, Medium Resistivity, Shallow Resistivity, Neutron Porosity, Density Porosity, Bulk Density, Photoelectric Factor, Delta Rho, Compressional Slowness, Shear Slowness, Mud Weight, Mud Resistivity, Mud Temperature, Rmf Temperature, Rm Temperature, Rmc Temperature, Rmf, Rm, Rmc, Rmf Source, Rm Source, Rmc Source, Hole Temperature

Field: Morgusty Division
Location: Three Tutter Divisions Northeast Well 1
Coordinates: 41° 22' 15" N, 72° 5' 30" W
Permanent Datum: Mean Sea Level
Elevation: 0 ft
Log Measured From: Kelly Bushing
Drilling Measured From: Kelly Bushing

Run Number	1	2	3
Date	2023-04-12	2023-04-18	2023-04-25
Depth Driller	1,200 ft	2,450 ft	3,100 ft
Depth Logger	1,198 ft	2,447 ft	3,098 ft
Bottom Logged Interval	1,198 ft	2,447 ft	3,098 ft
Top Logged Interval	0 ft	1,198 ft	2,447 ft
Casing Driller Size	13 3/8 in @ 1,200 ft	—	—
Casing Logger Size	13 3/8 in @ 1,198 ft	—	—
Bit Size	12 1/4 in	8 1/2 in	8 1/2 in
Type Fluid in Hole	Spud Mud	Water-Based Mud	Water-Based Mud
Density / Viscosity	9.2 lb/gal / 45 s	9.6 lb/gal / 52 s	9.8 lb/gal / 55 s
PH / Fluid Loss	9.0 / 12.0 cm³	9.5 / 8.4 cm³	9.5 / 7.6 cm³
Source of Sample	Flowline	Flowline	Flowline
Rm @ Meas. Temp	0.62 ohm-m @ 68 °F	0.55 ohm-m @ 92 °F	0.52 ohm-m @ 104 °F
Rmf @ Meas. Temp	0.50 ohm-m @ 68 °F	0.44 ohm-m @ 92 °F	0.42 ohm-m @ 104 °F
Rmc @ Meas. Temp	0.74 ohm-m @ 68 °F	0.66 ohm-m @ 92 °F	0.62 ohm-m @ 104 °F
Source Rmf / Rmc	Measured / Measured	Measured / Measured	Measured / Measured
Rm @ BHT	0.31 ohm-m @ 142 °F	0.27 ohm-m @ 178 °F	0.25 ohm-m @ 196 °F
Time Since Circulation	6.0 hr	14.5 hr	22.0 hr
Max Recorded Temp	142 °F	178 °F	196 °F
Equipment Number	4417	4417	4417
Location	Morgusty	Morgusty	Morgusty
Recorded By	J. Whitcomb	J. Whitcomb	J. Whitcomb
Witnessed By	R. Tutter	R. Tutter	R. Tutter

Field: Morgusty Division
Location: Three Tutter Divisions Northeast Well 1
Coordinates: 41° 22' 15" N, 72° 5' 30" W
Permanent Datum: Mean Sea Level
Elevation: 0 ft
Log Measured From: Kelly Bushing
Drilling Measured From: Kelly Bushing

Run Number	1	2	3
Date	2023-04-12	2023-04-18	2023-04-25
Depth Driller	1,200 ft	2,450 ft	3,100 ft
Depth Logger	1,198 ft	2,447 ft	3,098 ft
Bottom Logged Interval	1,198 ft	2,447 ft	3,098 ft
Top Logged Interval	0 ft	1,198 ft	2,447 ft
Casing Driller Size	13 3/8 in @ 1,200 ft	—	—
Casing Logger Size	13 3/8 in @ 1,198 ft	—	—
Bit Size	12 1/4 in	8 1/2 in	8 1/2 in
Type Fluid in Hole	Spud Mud	Water-Based Mud	Water-Based Mud
Density / Viscosity	9.2 lb/gal / 45 s	9.6 lb/gal / 52 s	9.8 lb/gal / 55 s
PH / Fluid Loss	9.0 / 12.0 cm³	9.5 / 8.4 cm³	9.5 / 7.6 cm³
Source of Sample	Flowline	Flowline	Flowline
Rm @ Meas. Temp	0.62 ohm-m @ 68 °F	0.55 ohm-m @ 92 °F	0.52 ohm-m @ 104 °F
Rmf @ Meas. Temp	0.50 ohm-m @ 68 °F	0.44 ohm-m @ 92 °F	0.42 ohm-m @ 104 °F
Rmc @ Meas. Temp	0.74 ohm-m @ 68 °F	0.66 ohm-m @ 92 °F	0.62 ohm-m @ 104 °F
Source Rmf / Rmc	Measured / Measured	Measured / Measured	Measured / Measured
Rm @ BHT	0.31 ohm-m @ 142 °F	0.27 ohm-m @ 178 °F	0.25 ohm-m @ 196 °F
Time Since Circulation	6.0 hr	14.5 hr	22.0 hr
Max Recorded Temp	142 °F	178 °F	196 °F
Equipment Number	4417	4417	4417
Location	Morgusty	Morgusty	Morgusty
Recorded By	J. Whitcomb	J. Whitcomb	J. Whitcomb
Witnessed By	R. Tutter	R. Tutter	R. Tutter


5000
5050
5100
5150
5200
5250
5300
5350
5400
5450
5500
5550
5600
5650
5700
5750
5800
5850
5900
5950
6000
6050
6100
6150
6200
6250
6300
6350
6400
6450
6500
6550
6600
6650
6700
6750
6800
6850
6900
6950
7000