
Schlumberger
Gamma Ray (GR) (API)
Caliper (CALI) (in)
Bit Size (BS) (in)
Deep Resistivity (RT) (ohm.m)
Medium Resistivity (RM) (ohm.m)
Shallow Resistivity (RS) (ohm.m)
Neutron Porosity (NPHI) (%)
Bulk Density (RHOB) (g/cm3)
Photoelectric Factor (PEF) (b/e)
Delta Rho (DRHO) (g/cm3)
Compressional Slowness (DTC) (us/ft)
Shear Slowness (DTS) (us/ft)
Stoneley Slowness (DTST) (us/ft)




HALLIBURTON

MAIN PASS

SCALE: 5"=100'

HALLIBURTON

REPEAT PASS

SCALE: 5"=100'

Database File: encana slater 43-28 db
Dataset Pathname: cbl[main]
Presentation Format: Trial14
Dataset Creation: Fri Oct 12 11:59:10 2012 by Log Halliburton CasedHo
Charted By: Depth in Feet scaled 1:240

Collar Locator
Gamma Ray (GAPI)
0
300
Amplified Amplitude (mV)
Amplitude (mV)
50
200
Variable Density
1200




HALLIBURTON

REPEAT PASS

SCALE: 5"=100'

| | |
|---|---|
| Company | EnCana Oil & Gas (USA) Inc |
| Well | Slater 43-28 |
| Field | Wattenberg |
| County | Weld |
| State | Colorado |

HALLIBURTON

CEMENT BOND LOG

SCALE: 5"=100'