PRELIMINARY
NOT FOR FILING
PURPOSES

Company	
Well	
Field	
County	
State	
Country	
Survey Date	
Log Date	
Run No.	
Depth Driller	
Depth Logger	
Bottom Logged Interval	
Top Logged Interval	
Casing Driller	
Casing Logger	
Bit Size	
Type Fluid in Hole	
Density / Viscosity	
pH / Fluid Loss	
Source of Sample	
Rm @ Measured Temp	
Rmf @ Measured Temp	
Rmc @ Measured Temp	
Source of Rmf / Rmc	
Rm @ BHT	
Time Since Circulation	
Time on Bottom	
Max. Rec. Temp.	
Equip. Location	
Recorded By	
Witnessed By	

PRECISION INDUCTION COMPENSATED RESISTIVITY

Logged: 8/14/2018 at 5:34 PM ENL
Location: Colorado
Recorded By: Witnessed By:

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set forth in our current Price Schedule.

Computed:

Annular volume calculated for 4.5" casing
Annular Circling Rig 1/2
Thread: Buttress Casing (Surface)"
4/14 @ 09:13) 32258.00

No repeat due to hole conditions.

Distance Pipe to Sensor: 1427.46
Distance Pipe to Bit: 1427.46
Preqaulified Depth: 32258
Preqaulified Caption: Depth in Feet scaled 1:240
Created(UTC): Depth in Feet scaled 1:240

Gamma Ray (GAPI) 0 150
Caliper (in) 6 16
Bit Size (in) 6 16

Deep Resistivity (Ohmm) .2 2000
Medium Resistivity (Ohmm) .2 2000
Shallow Resistivity (Ohmm) .2 2000
RX Difference -200 200

Density Porosity (pu) 45 -15
Neutron Porosity (pu) 45 -15

1:60 (5" Metric)