

Company		Noble Energy Inc.	
Well		Lutz E25-30D	
Field		Wattenberg	
County		Weld	
State/Province		Colorado	
Location		SHL 3569 FNL & 165 FWL MNWV	
Borehole		BHL 66 FNL & 67 FWL MNWV	
Sec		25 TYP 6N Rqg 63W	
Log Measured From		ICB	
Date		January 15, 2012	
Depth (m)		7450	
Depth (ft)		7495	
Bottom Logged Interval		7495	
Casing Offset		657	
Casing Logger		CHEN CSH	
Type of Log Hole		CHEN CSH	
Density / Velocity		10.3 / 37	
PVT / Mud Case		130	
Gamma Ray (GAPI)		130	
SP (mV)		180	
ABHV (ft/s)		180	
Temp @ Meas. Temp		3.30 / 75 F	
Temp @ Mud Temp		2.00 / 75 F	
Source of PVT / Mud		Mud / CMC	
Time Correlation Shipped		1.00 / 205 F	
Time Correlation Received		1.00 / 205 F	
Maximum Recorded Temperature		205 F	
Equipment Number		205 F	
Forecast By		Stratton	
Weathered By		Stratton	

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Annular volume calculated for 4.5" casing
Saxon Drilling Rig 144
Thank you for using Phoenix Surveys!!
API # 05-123-32415
Did not reach bottom due to bridge.
No repeat pass due to hole conditions.

