FEI

COMPOSITE LOG

Company: Petroleum Development Oman
Well: Saiwan East-1
Field: Saiwan East
Location: Block 6, Sultanate of Oman
Coordinates: Lat 23°14'22.8"N, Long 57°31'08.4"E
Elevation: KB 412 m above MSL
Permanent Datum: Mean Sea Level
Log Measured From: Kelly Bushing
Drilling Measured From: Kelly Bushing
Date: 14-Mar-2019
Run No.: 1
Depth Driller: 3,612 m
Depth Logger: 3,608 m
Bottom Log Interval: 3,605 m
Top Log Interval: 2,980 m
Casing Driller: 13-3/8" @ 2,985 m
Casing Logger: 2,985 m
Bit Size: 12-1/4"
Type Fluid in Hole: WBM
Density / Viscosity: 1.18 SG / 52 s
pH / Fluid Loss: 9.2 / 4.8 cc
Source of Sample: Flowline
Rm @ Meas. Temp: 0.142 @ 68 °C
Rmf @ Meas. Temp: 0.118 @ 68 °C
Rmc @ Meas. Temp: 0.186 @ 68 °C
Source Rmf / Rmc: Measured / Calculated
Rm @ BHT: 0.098 @ 112 °C
Time Since Circulation: 14 hrs
Max. Recorded Temp: 112 °C
Equipment / Truck No.: Schlumberger Platform Express / Truck 4
Recorded By: A. Al-Rashdi
Witnessed By: M. Al-Hinai

DISCLAIMER

All interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not guarantee the accuracy or correctness of any interpretation, and we shall not be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our General Terms and Conditions as set out in our current price schedule.

CONFIDENTIAL

Annular volume calculated for 8-1/2" casing
Energy Drilling Rig 17
Thank you for using Schlumberger!
API # 34-121-24033-00

Distance Pos: 1,607 ft
Distance Run: 1,607 ft
Depth Driller: 3,612 m
Depth Logger: 3,608 m
Logging Speed: 1,800 ft/hr
Depth Scale: 1:200

Gamma Ray (GAPI) 0 — 150
Caliper (in) 6 — 16
SP (mV) -160 — 40

Deep Resistivity (Ohmm) .2 — 2000
Medium Resistivity (Ohmm) .2 — 2000
Shallow Resistivity (Ohmm) .2 — 2000
Micro Resistivity (Ohmm) .2 — 2000

Density Porosity (pu) 45 — -15
Neutron Porosity (pu) 45 — -15

Gamma Ray (GAPI) 0 — 150
Caliper (in) 6 — 16
SP (mV) -160 — 40

Deep Resistivity (Ohmm) .2 — 2000
Medium Resistivity (Ohmm) .2 — 2000
Shallow Resistivity (Ohmm) .2 — 2000
Micro Resistivity (Ohmm) .2 — 2000

Density Porosity (pu) 45 — -15
Neutron Porosity (pu) 45 — -15

Distance Pos: 1,607 ft
Distance Run: 1,607 ft
Depth Driller: 3,612 m
Depth Logger: 3,608 m
Logging Speed: 1,800 ft/hr
Depth Scale: 1:200

Gamma Ray (GAPI) 0 — 150
Caliper (in) 6 — 16
SP (mV) -160 — 40

Deep Resistivity (Ohmm) .2 — 2000
Medium Resistivity (Ohmm) .2 — 2000
Shallow Resistivity (Ohmm) .2 — 2000
Micro Resistivity (Ohmm) .2 — 2000

Density Porosity (pu) 45 — -15
Neutron Porosity (pu) 45 — -15

Gamma Ray (GAPI) 0 — 150
Caliper (in) 6 — 16
SP (mV) -160 — 40

Deep Resistivity (Ohmm) .2 — 2000
Medium Resistivity (Ohmm) .2 — 2000
Shallow Resistivity (Ohmm) .2 — 2000
Micro Resistivity (Ohmm) .2 — 2000

Density Porosity (pu) 45 — -15
Neutron Porosity (pu) 45 — -15