

FORM
5A

Rev
06/12

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400280343

Date Received:

06/07/2012

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 10261
2. Name of Operator: BAYSWATER EXPLORATION AND PRODUCTION
3. Address: 730 17TH ST STE 610
City: DENVER State: CO Zip: 80202
4. Contact Name: CLAYTON DOKE
Phone: (970) 669-7411
Fax: (970) 669-4077

5. API Number 05-123-34198-00
6. County: WELD
7. Well Name: Robel
Well Number: 14-28
8. Location: QtrQtr: SESW Section: 28 Township: 7N Range: 64W Meridian: 6
9. Field Name: GALETON Field Code: 27930

Completed Interval

FORMATION: CODELL Status: PRODUCING Treatment Type: FRACTURE
Treatment Date: 11/18/2011 End Date: 11/18/2011 Date of First Production this formation: 11/29/2011
Perforations Top: 7249 Bottom: 7263 No. Holes: 56 Hole size: 042/100

Provide a brief summary of the formation treatment:

Open Hole: ☐

261,043 gals, 175,686 gals SLF, 182,500lbs 30/50 White

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 6215

Max pressure during treatment (psi): 5100

Total gas used in treatment (mcf):

Fluid density at initial fracture (lbs/gal): 0.25

Type of gas used in treatment:

Number of staged intervals: 1

Total acid used in treatment (bbl):

Max frac gradient (psi/ft): 0.85

Recycled water used in treatment (bbl):

Flowback volume recovered (bbl): 6212

Fresh water used in treatment (bbl): 2032

Disposition method for flowback: DISPOSAL

Total proppant used (lbs): 182500

Rule 805 green completion techniques were utilized: ☐

Reason why green completion not utilized: PIPELINE

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 12/13/2011 Hours: 20 Bbl oil: 117 Mcf Gas: 90 Bbl H2O: 15
Calculated 24 hour rate: Bbl oil: 140 Mcf Gas: 108 Bbl H2O: 18 GOR: 769
Test Method: Flowing Casing PSI: 1250 Tubing PSI: Choke Size: 012/64
Gas Disposition: SOLD Gas Type: WET Btu Gas: 1354 API Gravity Oil: 44
Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

Bridge Plug Depth: Sacks cement on top:

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Clayton Doke

Title: Consultant Date: 6/7/2012 Email cdoke@petersonenergy.com
:

Attachment Check List

Att Doc Num	Name
400280343	FORM 5A SUBMITTED

Total Attach: 1 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>

Total: 0 comment(s)