

P&A Procedure for the Young Cattle Co H23-6-104

23-6S-104W Garfield County, Colo.

9 5/8" @ 170' TOC at Surface

7" @ 937' TOC surface

4 1/2" 11.6# @ 5,171' TOC at 4,650' (CBL)

Perfs: 4,696'-4,716', 4,746'-4,772'

5,134'-5,140'

MIRU, NDWH, NUBOP

POH and lay down tubing

MIRU wireline, and run gauge ring to 5,080'

POH, RIH and set CIBP at 5,080' and dump bail 35' of cement

MIRU wireline, and run gauge ring to 4,640'

POH, RIH and set CIBP at 4,640' and dump bail 35' of cement

Load hole

Pressure test casing to 500#, if it fails call for orders

Perforate at 987' (50' below the base of surface),

and establish circulation

Spot 60 sxs (312' in 7" casing) at perfs, leave 150' in the casing

WOC and tag, cement must be 100' above the shoe.

Add cement if necessary

POH and NDBOP

RIH to 100' and circulate cement to surface

Cut off wellhead

RIH in 7" x 9 5/8" annulus to 100' with 1" tubing and circulate

cement to surface, top off cement in all annuluses

Weld a plate with well information, RDMO

All cement is 15.8# class G neat with a 1.15 cuft/sack yield

Well Name: Young Cattle Co H23-6-104

API #: 0504506204

Location: Sec. 23-6S-104W

KB: 6,339' (9' AGL)


GL: 6,030'

County/St: Garfield, CO

Created By: M. Bale

Date: 6/12/2012

Current Wellbore



API #: 0504506204

KB: 6,339' (9' AGL)

GL: 6,030'

Created By: M. Bale

Date: 6/12/2012

Proposed Wellbore

