Company: Petroleum Service Inc.
Well: Rogers 24 & Gore 4-65A Inc
Field: Wattenberg
County, State: Weld, Colorado
Location: Sec. 24 T3N R67W, 1,320' FNL & 1,320' FWL
Sec. 24 T3N R67W, 1,320' FNL & 1,320' FWL
Elevation: K.B. 4,911 ft
G.L. 4,901 ft
D.F.
Permanent Datum: Ground Level
Log Measured From: K.B. 10 ft above Perm. Datum
Drilling Measured From: K.B.
Date: 04-Jul-21
Run Number: ONE
Depth-Driller: 7,900 ft
Depth-Logger: 7,900 ft
Bottom Logged Interval: 7,900 ft
Top Logged Interval: 6,500 ft
Casing-Driller: 9.625 in @ 1,000 ft
Casing-Logger: 1,000 ft
Bit Size: 8.75 in
Type Fluid in Hole: Water Based Mud
Density: 9.2 lb/gal
Viscosity: 40 s
PH: 9.5
Fluid Loss: 6.4 cc
Source of Sample: Flowline
Rm @ Meas. Temp: 0.1 @ 70 °F
Rmf @ Meas. Temp: 0.1 @ 70 °F
Rmc @ Meas. Temp: 0.1 @ 70 °F
Source of Rmf / Rmc: Measured / Measured
Rm @ BHT: 0.1 @ 70 °F
Time Since Circulation: 4 hrs
Max. Rec. Temp. Deg. F: 70 °F
Equipment / Base: 1,000 / Greeley
Recorded By: Jeff Rowe
Witnessed By: Bruce Wayne

All data interpretation or opinions based on information that is beyond or above measurements we are current as to not guarantee the accuracy or correctness of any interpretation, and we shall not be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current price schedule.

Comments

Annular volume calculated for 4-1/2" casing
Ensign Drilling Rig 122
Thank you for using Phoenix Surveys!!
API # 05-123-32428-00

Database File: CBT1.db
Dataset Pathname: final
Presentation Format: porosity
Dataset Creation: Sat Mar 19 04:27:22 2022
Charted by: Depth in Feet scaled 1:240

Gamma Ray (GR): 0 to 150
Caliper (in): 16 to 6
Density Correction (in): -0.5 to 0.5
SP (mV): -100 to 100
Deep Resistivity (Ohmm): 200 at
Medium Resistivity (Ohmm): 200 at
Shallow Resistivity (Ohmm): 200 at
Density Porosity (pu): 45 to -15
Neutron Porosity (pu): 45 to -15
Hi (Ohmm): 200
Lo (Ohmm): 0.2

Database File: CBT1.db
Dataset Pathname: final
Presentation Format: porosity
Dataset Creation: Sat Mar 19 04:27:22 2022
Charted by: Depth in Feet scaled 1:240

Gamma Ray (GR): 0 to 150
Caliper (in): 16 to 6
Density Correction (in): -0.5 to 0.5
SP (mV): -100 to 100
Deep Resistivity (Ohmm): 200 at
Medium Resistivity (Ohmm): 200 at
Shallow Resistivity (Ohmm): 200 at
Density Porosity (pu): 45 to -15
Neutron Porosity (pu): 45 to -15
Hi (Ohmm): 200
Lo (Ohmm): 0.2

Database File: CBT1.db
Dataset Pathname: final
Presentation Format: porosity
Dataset Creation: Sat Mar 19 04:27:22 2022
Charted by: Depth in Feet scaled 1:240

Caliper (in): 16 to 6
Gamma Ray (GR): 0 to 150
SP (mV): -100 to 100
Deep Resistivity (Ohmm): 200 at
Medium Resistivity (Ohmm): 200 at
Shallow Resistivity (Ohmm): 200 at
Density Porosity (pu): 45 to -15
Neutron Porosity (pu): 45 to -15
Hi (Ohmm): 200
Lo (Ohmm): 0.2

Database File: CBT1.db
Dataset Pathname: final
Presentation Format: porosity
Dataset Creation: Sat Mar 19 04:27:22 2022
Charted by: Depth in Feet scaled 1:240

Caliper (in): 16 to 6
Gamma Ray (GR): 0 to 150
SP (mV): -100 to 100
Deep Resistivity (Ohmm): 200 at
Medium Resistivity (Ohmm): 200 at
Shallow Resistivity (Ohmm): 200 at
Density Porosity (pu): 45 to -15
Neutron Porosity (pu): 45 to -15
Hi (Ohmm): 200
Lo (Ohmm): 0.2