

FORMATION: CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 05/11/2012 End Date: 05/18/2012 Date of First Production this formation: 05/22/2012
Perforations Top: 7074 Bottom: 7090 No. Holes: 64 Hole size: 0.4

Provide a brief summary of the formation treatment: _____ Open Hole:

Pumped 237,222 lbs of Ottawa Proppant and 114,767 gallons of 15% HCL, Slick Water, and Silverstim.
The Codell is producing through a composite flow through plug.
Commingling the Niobrara and Codell.

This formation is commingled with another formation: Yes No

Total fluid used in treatment (bbl): 2733 Max pressure during treatment (psi): 4645

Total gas used in treatment (mcf): _____ Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: _____ Max frac gradient (psi/ft): 0.72

Total acid used in treatment (bbl): _____ Number of staged intervals: 11

Recycled water used in treatment (bbl): _____ Flowback volume recovered (bbl): _____

Fresh water used in treatment (bbl): _____ Disposition method for flowback: RECYCLE

Total proppant used (lbs): 237222 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: _____

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: _____ Hours: _____ Bbl oil: _____ Mcf Gas: _____ Bbl H2O: _____

Calculated 24 hour rate: Bbl oil: _____ Mcf Gas: _____ Bbl H2O: _____ GOR: _____

Test Method: _____ Casing PSI: _____ Tubing PSI: _____ Choke Size: _____

Gas Disposition: _____ Gas Type: _____ Btu Gas: _____ API Gravity Oil: _____

Tubing Size: _____ Tubing Setting Depth: _____ Tbg setting date: _____ Packer Depth: _____

Reason for Non-Production: _____

Date formation Abandoned: _____ Squeeze: Yes No If yes, number of sacks cmt _____

** Bridge Plug Depth: _____ ** Sacks cement on top: _____ ** Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA-CODELL Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 05/11/2012 End Date: 05/18/2012 Date of First Production this formation: 05/22/2012

Perforations Top: 6782 Bottom: 7090 No. Holes: 112 Hole size: _____

Provide a brief summary of the formation treatment: _____ Open Hole:

This formation is commingled with another formation: Yes No

Total fluid used in treatment (bbl): _____ Max pressure during treatment (psi): _____

Total gas used in treatment (mcf): _____ Fluid density at initial fracture (lbs/gal): _____

Type of gas used in treatment: _____ Max frac gradient (psi/ft): _____

Total acid used in treatment (bbl): _____ Number of staged intervals: _____

Recycled water used in treatment (bbl): _____ Flowback volume recovered (bbl): _____

Fresh water used in treatment (bbl): _____ Disposition method for flowback: _____

Total proppant used (lbs): _____ Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: _____

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 05/25/2012 Hours: 24 Bbl oil: 41 Mcf Gas: 225 Bbl H2O: 40

Calculated 24 hour rate: Bbl oil: 41 Mcf Gas: 225 Bbl H2O: 40 GOR: 5488

Test Method: Flowing Casing PSI: 1050 Tubing PSI: 0 Choke Size: 12/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1283 API Gravity Oil: 55

Tubing Size: 2 + 3/8 Tubing Setting Depth: 7056 Tbg setting date: 07/02/2012 Packer Depth: _____

Reason for Non-Production:

Date formation Abandoned: _____ Squeeze: Yes No If yes, number of sacks cmt _____

** Bridge Plug Depth: _____ ** Sacks cement on top: _____ ** Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 05/18/2012 End Date: 05/18/2012 Date of First Production this formation: 05/22/2012
Perforations Top: 6782 Bottom: 6891 No. Holes: 48 Hole size: 0.69

Provide a brief summary of the formation treatment: Open Hole:

Pumped 259,026 lbs of Ottawa Proppant and 158,773 gallons of Slick Water and Silverstim. Commingle the Niobrara and Codell.

This formation is commingled with another formation: Yes No

Total fluid used in treatment (bbl): 3780 Max pressure during treatment (psi): 4742

Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: Max frac gradient (psi/ft): 0.97

Total acid used in treatment (bbl): Number of staged intervals: 9

Recycled water used in treatment (bbl): Flowback volume recovered (bbl):

Fresh water used in treatment (bbl): Disposition method for flowback: RECYCLE

Total proppant used (lbs): 259026 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: Hours: Bbl oil: Mcf Gas: Bbl H2O:

Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:

Test Method: Casing PSI: Tubing PSI: Choke Size:

Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:

Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: Yes No If yes, number of sacks cmt

** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Sarah Finnegan
Title: Regulatory Analyst Date: Email: sfinnegan@nobleenergyinc.com

Attachment Check List

Att Doc Num	Name

Total Attach: 0 Files

General Comments

User Group	Comment	Comment Date

Total: 0 comment(s)