
Schlumberger
Wireline Services
Gamma Ray (GR)
Caliper (CALI)
Bit Size
Deep Resistivity (RT)
Medium Resistivity (RM)
Shallow Resistivity (RS)
Neutron Porosity (NPHI)
Bulk Density (RHOB)
Photoelectric Factor (PEF)
Delta Rho (DRHO)
Spectral Gamma Ray (SGR)
Potassium (POTA)
Thorium (THOR)
Uranium (URAN)
Differential Caliper (DCAL)
Stand Off (STOF)
Acoustic Porosity (APLC)
Compressional Slowness (DTCO)
Shear Slowness (DTSM)
Stoneley Slowness (DTST)
Tension (TENS)
Cable Speed (CS)
Mud Weight (MW)
Mud Resistivity (RMUD)
Mud Temperature (TMUD)
Rm @ BHT
Rmf @ BHT
Rmc @ BHT
Mud Type
Source
Time Since Circulation
Max Recorded Temperature
Equipment Number
Location
Recorded By
Witnessed By
Run Number
Depth Driller
Depth Logger
Bottom Logged Interval
Top Logged Interval
Casing Driller Size @ Depth
Casing Logger Size @ Depth
Bit Size
Type Fluid in Hole
Density
Viscosity
PH
Fluid Loss
Source of Sample
Rm @ Measured Temperature
Rmf @ Measured Temperature
Rmc @ Measured Temperature
Source of Rmf and Rmc
Rm @ BHT
Rmf @ BHT
Rmc @ BHT
Max Recorded Temperature
Circulation Stopped Time
Logger on Bottom Time
Unit Number


MAIN PASS

TEMP	0.58		TEMP-1.375TEMP (2011-05) Temperature Tool	1.88	1.38	30.00

Dataset:	kp_444_18 tl.db: field/well/run1/pass2
Total Length:	3.67 ft
Total Weight:	37.50 lb
O.D.	1.38 in

PDP wireline, llc

Company	WPX ENERGY
Well	KP-444-18
Field	KOKOPELLI
County	GARFIELD
State	COLORADO