J-W WIRELINE COMPANY

CEMENT BOND
GAMMA RAY
COLLAR CORRELATION LOG

Company NOBLE ENERGY INC.
Well LDS D 08-28D
Field WATTENBERG
County WELD
State COLORADO

Company	NOBLE ENERGY INC.		
Well	LDS D 08-28D		
Field	WATTENBERG		
County	WELD	State	COLORADO
Location:	API # : 05-123-31993-00 BHL: 189' FSL & 1362' FWL SE SW BHL: 201' FSL & 2383' FWL SE SW SEC. 05 TWP. 3N RGE. 64W	Other Services	NONE
	SEC TWP RGE		
Permanent Datum	GROUND LEVEL	Elevation 4753	Elevation K.B. 4766 D.F. 4766 G.L. 4753
Log Measured From	KELLY BUSHING		
Drilling Measured From	KELLY BUSHING		

Date	02-APRIL-2012
Run Number	ONE
Depth Driller	7284
Depth Logger	7205
Bottom Logged Interval	7204
Top Log Interval	1800
Open Hole Size	7 7/8
Type Fluid	WATER
Density / Viscosity	---
Max. Recorded Temp.	240
Estimated Cement Top	1984
Time Well Ready	---
Time Logger on Bottom	---
Equipment Number	2405/1 11/16 TECKO
Location	BRIGHTON
Recorded By	HAYES
Witnessed By	MR.TROY SETTLE

Borehole Record			Tubing Record			
Run Number	Bit	From	To	Size	Weight	From	To

Casing Record	Size	Wgt/Ft	Top	Bottom
Surface String	8 5/8	24#	SURFACE	744
Prot. String				
Production String	4.5	11.6#	SURFACE	7274
Liner				

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

LOG CORRELATED TO CD, CN,ML LOG
DATED 25-MARCH-2012

LOG SPLIT FOR CORRELATION PURPOSES



Sensor	Offset (ft)	Description	Len (ft)	OD (in)	Wt (lb)
CCL	20.25	CCL-169TEKCO (169) 1 11/16" Tekco Logging	1.67	1.69	20.00
		CENT-TekCo (1 11/16 Adj.) (001) 1 11/16" Tekco Cent	2.92	1.69	10.00
		CBL-3-5tekco169 (1) 1 11/16 Tekco w/o Temp	9.75	1.69	70.00
WVF3	11.00				
WVF5	10.17				
		CENT-TekCo (1 11/16 Adj.) (002) 1 11/16" Tekco Cent	2.92	1.69	10.00
		GR-1.69TEKCO (576) 1 11/16 Tekco Logging GR	3.83	1.69	50.00
GR	1.00				

Dataset: lds d 08-28d.db: field/well/run1/pass2
Total Length: 21.08 ft
Total Weight: 160.00 lb
O.D. 1.69 in

Database File: lds d 08-28d.db
Dataset Pathname: pass2
Presentation Format: cblx
Dataset Creation: Tue Apr 03 00:34:27 2012 by Log Std Casedhole 10121
Charted by: Depth in Feet scaled 1:240

30	Gamma Ray (GAPI)	130	0	3' Amplitude (mV)	100	200	Variable Density	1200
4	CCL	-0.25	0	Amplified Amplitude (mV)	30			
300	TT3 (usec)	200						



Database File: lds d 08-28d.db
Dataset Pathname: pass1
Presentation Format: cblx
Dataset Creation: Tue Apr 03 00:04:45 2012 by Log Std Casedhole 10121
Charted by: Depth in Feet scaled 1:240

Calibration Report

Database File: lds d 08-28d.db
Dataset Pathname: pass2
Dataset Creation: Mon Apr 02 23:34:27 2012 by Log Std Casedhole 10121

Gamma Ray Calibration Report

Serial Number:	576	
Tool Model:	1.69TEKCO	
Performed:	Thu Jan 12 13:03:35 2012	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	1.0000	GAPI/cps

Cement Bond Log Calibration Report

Serial Number:	1		
Tool Model:	3-5tekco169		
Performed:	Mon Apr 02 23:44:33 2012		
Depth:	1224.21	ft	
Casing Diameter:	4.5	in	
	3' Spacing	5' Spacing	
Signal Zero:	3	3	mV
Calibrated Amplitude:	81.1961	81.1961	mV
Reading at Signal Zero:	-0.2	0	V
Reading in Free Pipe:	2.5	2.5	V
Gain:	28.9615	31.2784	
Offset:	8.7923	3	